



**STI-Taps (Second Lead)**  
for Wire-Thread-Inserts

**Maschi STI**  
per inserti riportati



**Form D HSS-G**

Nominal Diameter D	B	L1	L2	D2	∅	Art.-No.
<b>G (BSP)</b>						
1/8 x 28	10.8	59.0	15.0	8.0	6.30	03301
1/4 x 19	14.7	67.0	19.0	11.2	9.00	03302
3/8 x 19	18.3	75.0	21.0	14.0	11.20	03303
1/2 x 14	23.1	87.0	26.0	16.0	12.50	03304
5/8 x 14	25.0	91.0	26.0	18.0	14.00	03305
3/4 x 14	28.6	96.0	28.0	20.0	16.00	03306
1" x 11	36.0	109.0	33.0	25.0	20.00	03307
<b>BA</b>						
BA 0	7.1	66.0	19.0	7.1	5.60	03321
BA 2	5.6	66.0	19.0	6.3	5.00	03323
BA 4	4.4	53.0	13.0	4.5	3.55	03325
BA 6	3.4	50.0	13.0	3.55	2.80	03327
<b>BS. Brass</b>						
1/4 x 26	7.5	69.0	19.0	8.0	6.30	03341
5/16 x 26	9.1	76.0	20.0	10.0	8.00	03342
3/8 x 26	10.7	82.0	22.0	8.0	6.30	03343
7/16 x 26	12.3	84.0	24.0	9.0	7.10	03344
1/2 x 26	13.9	90.0	25.0	11.2	9.00	03345

