

# EC-TYPE EXAMINATION CERTIFICATE



[1]

[2]

## Equipment or Protective System intended for use in Potentially Explosive Atmospheres Directive 94/9/EC

[3]

EC-Type Examination Certificate Number: **DEMKO 14 ATEX 1310896X Rev.1**

[4]

Equipment or Protective System: **Intrinsically Safe Flashlight, Model 9415Z0**

[5]

Manufacturer: **Pelican Products Inc.**

[6]

Address: **23215 Early Avenue, Torrance, CA 90505 USA**

[7]

This equipment or protective system and any acceptable variation thereto are specified in the schedule to this certificate and the documents therein referred to.

[8]

UL International Demko A/S, notified body number 0539 in accordance with Article 9 of the Council Directive 94/9/EC of 23 March 1994, certifies that this equipment or protective system has been found to comply with the Essential Health and Safety Requirements relating to design and construction of equipment and protective systems intended for use in potentially explosive atmospheres given in Annex II to the Directive.

The examination and test results are recorded in confidential report no. **1933390.403536**

[9]

Compliance with the Essential Health and Safety Requirements has been assured by compliance with:

**EN 60079-0:2012+A11:2013**

**EN 60079-11:2012**

**EN 60079-26:2007**

[10]

If the sign "X" is placed after the certificate number, it indicates that the equipment or protective system is subject to special conditions for safe use specified in the schedule to this certificate.

[11]

This EC-Type examination certificate relates only to the design, examination and tests of the specified equipment or protective system in accordance to the Directive 94/9/EC. Further requirements of the Directive apply to the manufacturing process and supply of this equipment or protective system.

These are not covered by the certificate.

[12]

The marking of the equipment or protective system shall include the following:

II 1G Ex ia IIC T4 Ga

**Certification Manager**  
Jan-Erik Storgaard

This is to certify that the sample(s) of the Equipment described herein ("Certified Equipment") has been investigated and found in compliance with the Standard(s) indicated on this Certificate, in accordance with the ATEX Equipment Certification Program Requirements. This certificate and test results obtained apply only to the equipment sample(s) submitted by the Manufacturer. UL did not select the sample(s) or determine whether the sample(s) provided were representative of other manufactured equipment. UL has not established Follow-Up Service or other surveillance of the equipment. The Manufacturer is solely and fully responsible for conformity of all equipment to all applicable Standards, specifications, requirements or Directives. The test results may not be used, in whole or in part, in any other document without UL's prior written approval.

**Date of issue:** 2014-08-29

**Re-issued:** 2014-09-26

**Notified Body**

UL International Demko A/S, Borupvang 5A, 2750 Ballerup, Denmark  
Tel. +45 44 85 65 65, [info.dk@ul.com](mailto:info.dk@ul.com), [www.ul.com](http://www.ul.com)



[13]

## Schedule

[14]

# EC-TYPE EXAMINATION CERTIFICATE No.

DEMKO 14 ATEX 1310896X Rev. 1

Report: 1933390.403536

[15]

Description of Equipment or protective system:

The model 9415Z0 is an intrinsically safe, portable, hand-held LED flashlight powered by Pelican Battery Pack Cat. No. 9418Z0. Battery Pack replacement and recharging is only intended for non-hazardous areas.

The optical radiation output of the apparatus with respect to explosion protection, according to Annex II clause 1.3.1 of the Directive 94/9/EC is not covered in this certificate.

Temperature range:

The ambient temperature range is -20°C to +40 °C.

Electrical data:

Intrinsically safe specifications:

Battery Pack Cat. No. 9415Z0 utilizes only the following batteries:  
Dison Part No. DS-MH500CM or Tenergy Part No. 10207

Routine tests:

N/A

[16]

Report No.

Project Report No.: 1933390.403536 (Hazardous Location Testing)

Documents:

Description:	Drawing No.:	Rev. Level:	Date:
Approval Insert (Markings)	9415-001-Z0	A	2014-07-30
Instruction Manual	9415-318-500	A	2014
Overall Assembly	9415-001-CLRE-Z0-AP	A	2014-07-17
Head Assembly	9415-350-000	B	2014-08-07
Top Housing	9415-949-CLR	A	2014-07-10
Bottom Housing	9415-948-CLR	A	2014-07-10
Front Cover	9415-350-CLR-09	B	2014-08-07
Back Cover	9415-350-CLR-11	B	2014-08-07
Clear Lens	9415-350-000-07	A	2014-08-07
Switch Assembly	9416-620-110-AP	A	2013-01-14
PCB Assembly, including Schematic, Component and Circuit Trace Layouts, Bill of Materials	9415-342-000	A	2013-01-14
Battery Pack Assembly	9415-302-000	A	2013-04-10
Battery Pack Label	9415-302-000-022	A	2014-05-13

[17]

Specific conditions of use:

- The LED Head Assembly is covered with conductive coating to avoid build-up of electrostatic charge. The coating is humidity independent and the operating temperature is up to 155°C. Do not use in Hazardous Area if the coating is flaking or peeling.
- The maximum measured capacitance of exposed metal parts is 13pF.

[18]

Essential Health and Safety Requirements

Concerning ESRs this Schedule verifies compliance with the Annex III of ATEX directive only. By placing the product on the market, the manufacturer declares compliance with other relevant Directives, and all other safety related requirements including those of Annex II of this Directive.

Additional information

The manufacturer shall inform the notified body concerning all modifications to the technical documentation as described in ANNEX III to Directive 94/9/EC of the European Parliament and the Council of 23 March 1994.

The trademark **PELI™** will be used as the company identifier on the marking label.

This certificate was issued as "Accredited by DANAK under registration number 7011 to certification of products".

