

SURVIVOR® RIGHT-ANGLE, ATEX RATED FIREFIGHTER'S TORCH

Approved for Zone 0. The redesigned Survivor features a low-profile bezel that doesn't interfere with gear and equipment. Its spring-loaded clip securely grabs onto gear, and the reinforced D-ring allows your light to hang forward.



Low-profile design doesn't interfere with gear and equipment

Specialized optic combines low profile with strong performance and a wide beam





Interchangeable Smoke-Cutter® plugs for preferred beam pattern:

- · Black plug significantly reduces peripheral light for a tighter beam
- · Amber plug reduces peripheral light and eye fatigue caused by glare



DUAL POWER SOURCE:

Rechargeable lithium ion battery; also accepts 4 "AA" alkaline or lithium batteries



Strong spring-loaded clip securely grabs onto belts and gear, D-ring provides forward hanging orientation



High, low, emergency flash and moonlight modes:

- High for a super-bright beam that pierces through smoke: 41,000 candela; 175 lumens; 405m beam distance; runs 3.5 hours (lithium rech); runs 8 hours (AA alkaline or AA lithium)
- Low for bright light and longer run time: 14,000 candela; 60 lumens; 237m beam distance; runs 10 hours (lithium rech); runs 20 hours (AA alkaline or AA lithium)
- Flash for signaling: runs 5 hours
- Moonlight mode provides low-level lighting for battery conservation: runs 15 days Optimized electronics provide regulated intensity

Unbreakable polycarbonate lens with silicone anti-scratch coating is assembled in a heavy-duty bezel









FTZU 15 ATEX 0046X; IEC Ex FTZU 15.0029X II 1G Ex ia op is IIB T3/T4 Ga; II 2G Ex ia op is IIC T3/T4 Gb

INMETRO: DNV 16.0014X; Ex ia op is IIB T3/T4 Ga; Ex ia op is T3/T4 Gb

IP66 rated design; dust tight and water resistant; 2 meter impact resistance tested

17.92 cm; 388g (with lithium rechargeable or AA alkaline); 354g (with AA lithium)

Limited Lifetime Warranty Visit streamlight.com for full warranty information

See reverse for item numbers