

SELF DUMPING HOOPER



SBTCUC



SBTCMIN
Low height model

SBTCUC-Series / SBTCMIN-Series



DESCRIPTION


The Mini Chip Container SBTCMIN series is the ideal container for production and factory floors, etc., where space is limited. With its compact dimensions, light weight and yet very large volume it is a very popular product.

The Mini Tipper Container fits under almost any machine, due to its extremely low construction: presses, punches, drills, saws, lathes, and so on.

This Universal tipper container SBTCUC is the optimal solution for collecting and transporting all kinds of bulk materials. The UC series is perfect to fit on many machines due to its moderate height. Fitted with special tension spring between the base and the base to ensure the smooth emptying of the tipping skip. Equipped with a safe and stable unlocking mechanism, which can be operated by a pull cord from the driver's seat of a forklift. For additional safety a safety chain can be connected on the forklift. Add a Safety chain and cable set to your order.

The SBTCUC-Series is characterized by its high loading and carrying capacity, from 1100 kgs upto 1800 kgs. Thanks to the use of high-quality steel sheets and excellent finishing, the Tipping Bins are very durable and robust. Finished with powder coating in standard color RAL5010. Tipper container Application: wood, metal, aluminum RVS, plastic, glass, sand, stones.

[Click Here for YouTube Video](#)



Forklift pockets dimensions

TECHNICAL SPECIFICATIONS

Reference	Volume in L	Length in mm	width in mm	height in mm	Weight in Kg	Load capacity inKg	Dimensions of lift pockets: A in mm
SBTCUC150L (mini)	150	1210	747	419	59	500	(A) 128 mm x (B) 204 mm x (C) 62 mm
SBTCUC250L (mini)	250	1210	1047	419	68	600	(A) 128 mm x (B) 204 mm x (C) 62 mm
SBTCUC300L	300	1393	780	577	80	1300	(A) 128 mm x (B) 204 mm x (C) 62 mm
SBTCUC500L	500	1648	812	727	94	1300	(A) 128 mm x (B) 204 mm x (C) 62 mm
SBTCUC750L	750/26.5	1627	1162	727	135	1500	(A) 328 mm x (B) 204 mm x (C) 62 mm
SBTCUC1000L	1000	1707	1282	727	150	1800	(A) 328 mm x (B) 204 mm x (C) 62 mm
SBTCUC1250L	1250	1774	1282	907	165	1800	(A) 328 mm x (B) 204 mm x (C) 62 mm
SBTCUC1500L	1500	1774	1482	907	180	1800	(A) 500 mm x (B) 200 mm x (C) 60 mm