

FS30E

**POWERFUL AND STABLE ELECTRIC FLOOR SAW, IDEAL FOR CUTTING JOBS INSIDE BUILDINGS.
QUICKLY TO DISMANTLE INTO 3 PARTS FOR EASY TRANSPORT TO DIFFERENT FLOORS.**


7,5 kW or 11 kW 3-phase electric motor

Blade-Ø 800 mm (32")

Cutting depth 330 mm (13")

- Compact and solid chassis, demountable into 3 parts
- Adjustable handle bars for operators comfort
- Continuously adjustable cutting depth
- E-Motor easy to remove by quick mount plate
- Right- and Lefthand blade operation
- Divisible blade guard - can be raised for cutting against walls
- GK water connection to connect to external water supply
- Emergency stop
- Parking brake

Scan here for the product video



E-Motor easy to remove by quick mount plate



Adjustable handles



Demountable in parts

Accessories

Blade guard for flush cutting near a wall (distance 5 mm)

Order number

0282 030 1010



Specifications

FS30E

Max Cutting depth	320 mm (12,6")	
Blade diameter	800 mm (31,5")	
Shaft size	25,4 mm (1")	
Water-connection	No	
Engine	3-phase electric	
Engine power	400V; 7,5kW; 16A	400V; 11kW; 32A
Shaft speed	1430 min ⁻¹	
Feed motion	Push	
Cutting depth adjustment	Handwheel	
Power transmission	V-belt Kit	
Dimensions (LxWxH)	1.220 x 680 x 880 mm	
Weight	118 kg	142 kg
Order number	0282 030 1000	0282 030 2000

Suitable diamond tools – our recommendations

Material	Concrete Reinf. Concr.	Concrete Reinf. Concr.
Type	CS21	CS23
Order number	CS21 800	CS23 800

Find further suitable diamond tools in our diamond tool catalog.

