

# FS250

**POWERFUL, SELF-PROPELLED WALK BEHIND SAW WITH HONDA GAS ENGINE OR HATZ DIESEL ENGINE. ROBUST AND HIGH PERFORMANCE FOR CUTTING ASPHALT AND CONCRETE.**



Divisible blade guard  
- can be raised for  
intersections



User friendly control  
panel with cutting  
depth adjustment



**25HP Honda Gas Engine/  
23HP Norwik Diesel Engine  
Blade Ø 800 mm (32")  
Cutting depth 310 mm (12,2")**

- Adjustable handle bars for operators comfort
- Control panel - user friendly
- Continuously adjustable cutting depth
- Cutting depth indicator
- Blade depth control and rapid blade lift by electro-hydraulic
- Self adjusting belt tensioner
- Self-priming water pump
- Right- and lefthand cutting
- Divisible blade guard - can be raised for intersections
- Electro-hydraulic drive, detachable. Saw can be moved without blade running
- Lifting eye
- Well balanced chassis for best cutting performance

| Specifications           | FS250B                               | FS250D                  |
|--------------------------|--------------------------------------|-------------------------|
| Max Cutting depth        | 310 mm (12,2")                       | 310 mm (12,2")          |
| Blade diameter           | 800 mm (31,5")                       | 800 mm (31,5")          |
| Shaft size               | 25,4 mm (1")                         | 25,4 mm (1")            |
| Water tank               | No                                   | No                      |
| Engine                   | Honda GX690                          | Norwik NK292F           |
| Engine power (net power) | 25 HP / 18,5 kW<br>(22 HP / 16,5 kW) | 23 HP / 16,9 kW         |
| Shaft speed              | 1.600 min <sup>-1</sup>              | 1.450 min <sup>-1</sup> |
| Feed motion              | Electro-hydraulic drive              | Electro-hydraulic drive |
| Cutting depth adjustment | Lowering valve                       | Lowering valve          |
| Dimensions (LxWxH)       | 1.340 x 880 x 1.040 mm               | 1.340 x 880 x 1.040 mm  |
| Weight                   | 285 kg (627 lbs)                     | 346 kg (761 lbs)        |
| Order number             | 0282 250 4506                        | 0282 250 4510           |

**Suitable diamond tools – our recommendations**

| Material  | Concrete Reinf. Concr. | Asphalt Standard | Asphalt Premium |
|-----------|------------------------|------------------|-----------------|
| Type      | CS23                   | AS22             | AS25            |
| Order no. | CS23 800               | AS20 80048       | AS25 80046      |

Find further suitable diamond tools in our diamond tool catalog.

