

FS175

COMPACT AND SOLID PUSH SAW FOR SMALL SERVICES AND REPAIR JOBS IN ROADWORKS. THE HEIGHT ADJUSTABLE ANTI-VIBRATION HANDLES HAVE A CLEAR FOCUS ON OPERATORS CONVENIENCE. COMPACT - ROBUST - COMFORTABLE.



Scan here for the product video



13 HP Honda or 14 HP KOHLER gas engine
Blade-ø 500mm (19,7")
Cutting depth 190 mm (7,5")

- Adjustable anti vibration handles for operators comfort
- Cutting depth adjustment by handwheel
- Cutting depth indicator
- Front cutting guide
- Parking brake
- Lifting frame
- 25 Liter water tank, easy to fill
- Big rear wheels for good chassis clearance



FS175 TWIN – perfect for parallel cut in a single operation

Specifications	FS175	
Max Cutting depth	190 mm (7,5")	190 mm (7,5")
Blade diameter	500 mm (19,7")	500 mm (19,7")
Shaft size	25,4 mm (1")	25,4 mm (1")
Water tank	25 Liter (6,6 gal)	25 Liter (6,6 gal)
Engine	Honda GX390	KOHLER Motor CH440
Engine power (net power)	13 HP / 9,5 kW (11,8 HP / 8,7 kW)	14 HP / 10,5 kW (12,7 HP / 9,4 kW)
Shaft speed	2.300 min ⁻¹	2.300 min ⁻¹
Feed motion	Push	Push
Cutting depth adjustment	Handwheel	Handwheel
Power transmission	V-Belt Kit	V-Belt Kit
Hand Arm Vibrations	4,5 m/s ²	2,2 m/s ²
Dimensions (LxWxH)	1.220x520x1.100 mm	1.220x520x1.100 mm
Weight	128 kg (282 lbs)	130 kg (287 lbs)
Order number	0282 175 6000	0282 175 6020

Accessory	Order number
Conversion kit for FS175 TWIN	0282 175 9074

Suitable diamond tools – our recommendations



Material	Beton Standard	Beton Premium	Concrete + Asphalt	Asphalt Standard	Asphalt Premium
Type	CT30	CT40	ALLMIX	AS60	GX-A80
Order no.	CT30 501	CT40 501	04978700501	AS60 501	AS75 501

Find further suitable diamond tools in our diamond tool catalog.

