

FS125

ROBUST AND USERFRIENDLY FOR SMALL ROAD REPAIR JOBS OR CUTTING SMALL TRENCHES FOR PIPING. THE ALTERNATIVE SOLUTION TO A CUT OFF SAW ON CART. COMPACT - LIGHTWEIGHT - QUIET - STABLE

6,5 HP Honda gas engine

Blade-ø 350mm (14")

Cutting depth 120 mm (5")

- Adjustable anti vibration handles for operators comfort
- Cutting depth adjustment by handwheel
- Cutting depth indicator
- Front cutting guide
- Parking brake
- Lifting frame
- 25 Liter water tank, easy to fill
- Big rear wheels for good chassis clearance
- Durable Poly-V belt for an optimum of power transmission



Specifications	FS125
Max Cutting depth	120 mm (4,7")
Blade diameter	350 mm (13,8")
Shaft size	25,4 mm (1")
Water tank	25 Liter (6,6 gal)
Engine	Honda GX200
Engine power (net power)	6,5 HP / 4,8 kW (5,5 HP / 4,1 kW)
Shaft speed	2.730 min ⁻¹
Feed motion	Push
Cutting depth adjustment	Handwheel
Power transmission	V-Belt Kit
Hand Arm Vibrations	4,5 m/s ²
Dimensions (LxWxH)	950 x 460 x 940 mm
Weight	77 kg (170 lbs)
Order number	0282 125 6000

Suitable diamond tools – our recommendations



Material	Concrete Standard	Concrete Premium	Concrete + Asphalt	Asphalt Standard	Asphalt Premium
Type	CT30	CT40	ALLMIX	AS60	GX-A80
Order no.	CT30 351	CT40 351	04978700351	AS60 351	GX-A80 351

Find further suitable diamond tools in our diamond tool catalog.