

ACCESSORY RESOURCE GUIDE
7.1.2020



ACCESSORY RESOURCE
GUIDE 7.1.2020

Transducers

Transom Transducers.....	3-6
In-Hull Transducers.....	6-7
Trolling Motor Transducers.....	7-11
Portable Transducers.....	11
S.S & Bronze Thru Hull Transducers.....	11-12
Plastic Thru Hull Transducers.....	12-14
Ice Transducers.....	14
Trolling Motor Transducer Kit.....	15

Mounts, Hardware, Sensors

Transom Mounting Hardware & Adapters	16
Portable Mounting Hardware.....	16
In-Dash Mounts.....	17-18
Mounting Hardware.....	18-19
Temperature and Speed Sensors.....	19

Cables

Extension Cables.....	19-20
Power Cables.....	21
Adapter Cables.....	22-23
Ethernet Cables.....	23-25

Other Accessories and Systems






MEGA 360 Imaging.....	26-27
Sonar Modules.....	27
Advanced Fishing Systems.....	27-29
Unit Covers.....	29-31
Portable Configurations.....	31
Ice Accessories.....	31-32
Autopilot and Accessories.....	32-34
RADAR.....	34






TRANSOM TRANSDUCERS – 2D Sonar	Item Number	Description	Compatible Units
 <p>XNT 9 HW T</p>	710274-1	Transom mount Dual Spectrum CHIRP Transducer with temperature sensor and 20' cable	<ul style="list-style-type: none"> • All HELIX models with CHIRP <ul style="list-style-type: none"> ○ G2/G2N and newer models • All ICE HELIX models with CHIRP <ul style="list-style-type: none"> ○ G2/G2N and newer models
 <p>XNT 14 HW T</p>	710285-1	Transom mount Dual Spectrum CHIRP transducer with temperature sensor and 20' cable	<ul style="list-style-type: none"> • SOLIX 10, 12, 15 <ul style="list-style-type: none"> ○ All models
 <p>XNT 9 20 T</p>	710198-1	Transom Mount Single/Dual Beam 20/60 Degree 200/83kHz Temperature Sensor	<ul style="list-style-type: none"> • All 100, 300, 500, 600, 700, 800, 900, 1100 except DI models • All HELIX Series except DI models
 <p>XNT 9 28 T</p>	710236-1	Transom mount Dual Beam, 28/16 Degree, 200/455kHz, Temp	<ul style="list-style-type: none"> • PiranhaMAX 4 and PiranhaMAX 4 PT
 <p>XNT 9 DB 74 T</p>	710237-1	Transom mount Dual Beam, 20/74 Degrees, 200/50 kHz with built in temp for use with extended depth models	<ul style="list-style-type: none"> • 1159ci HD XD Combo • 859ci HD XD Combo • 678c HD XD • 688ci HD XD Combo • 959ci HD XD Combo • All HELIX models except HELIX 7 SONAR G2, HELIX 7 SI GPS, HELIX 7 DI GPS, HELIX 7 SONAR GPS, HELIX 7 DI, HELIX 5 DI G2, HELIX 5 SI GPS, HELIX 5 DI GPS, HELIX 5 SONAR GPS, HELIX 5 DI, HELIX 5 SONAR



 <p>XNT 14 20 T</p>	710247-1	Transom mount Dual Beam transducer 20/60 degree, 200/83 kHz, temp included	<ul style="list-style-type: none"> • ION* Series • ONIX10ci COMBO • ONIX 10ci COMBO NT • ONIX8ci COMBO • ONIX 8ci COMBO NT • SOLIX 10 CHIRP GPS • SOLIX 12 CHIRP GPS • SOLIX 15 CHIRP GPS <p>*Must also have the Sonar Module</p>
TRANSOM TRANSDUCERS – Down Imaging			
	Item Number	Description	Compatible Units
 <p>XNT 9 HW MDI 75 T</p>	710295-1	Transom Mount transducer with MEGA Down Imaging, Dual Spectrum CHIRP, temperature sensor and 20' cable	<ul style="list-style-type: none"> • HELIX 7 and 8 CHIRP MDI oG3/G3N and newer models
 <p>XM 9 HW MDI T</p>	710280-1	Transom Mount transducer with MEGA Down Imaging+, Dual Spectrum CHIRP, temperature sensor and 20' cable	<ul style="list-style-type: none"> • HELIX 9/10/12 CHIRP MEGA DI+ oG3 / G3N and newer models
 <p>XM 14 HW MDI T</p>	710290-1	Transom Mount transducer with MEGA Down Imaging+, Dual Spectrum CHIRP, temperature sensor and 20' cable	<ul style="list-style-type: none"> • SOLIX 10 CHIRP MEGA DI+ GPS G2 • SOLIX 12 CHIRP MEGA DI+ GPS G2 • SOLIX 15 CHIRP MEGA DI+ GPS G2
 <p>XM 9 MDI T</p>	710269-1	Transom mount MEGA DI, DualBeam PLUS, 20/60/86/55 degrees, 200/83/455/800 kHz and 1.2 MHz, temperature built-in	<ul style="list-style-type: none"> • HELIX 9 CHIRP MEGA DI GPS G2N • HELIX 10 CHIRP MEGA DI GPS G2N • HELIX 12 CHIRP MEGA DI GPS G2N

 <p>XNT 9 DI T</p>	710226-1	Transom Mount Down Imaging 83/200/455 kHz Temperature Sensor	<ul style="list-style-type: none"> • 1159ci HD DI, 959ci HD DI, 859ci HD DI, 571 HD DI, 561 DI, 386ci DI, 346c DI, 688ci DI, 678 DI, 1158c DI, 958c HD DI, 958c DI, 858c HD DI, 858c DI, 798ci SI and 798ci HD SI and 899ci HD SI • PiranhaMAX 4 DI • All HELIX non-CHIRP DI models
TRANSOM TRANSDUCERS – Side Imaging			
	Item Number	Description	Compatible Units
 <p>XNT 9 HW MSI 150 T</p>	710297-1	Transom mount MEGA Side Imaging, MEGA Down Imaging, Dual Spectrum CHIRP transducer with temperature sensor and 20' cable	<ul style="list-style-type: none"> • HELIX 7 CHIRP MSI models oG3/G3N and newer models
 <p>XM 9 HW MSI T</p>	710282-1	Transom mount MEGA Side Imaging+, MEGA Down Imaging+, Dual Spectrum CHIRP transducer with temperature sensor and 20' cable	<ul style="list-style-type: none"> • HELIX 8 / 9 / 10 / 12 CHIRP MSI+ oG3N models only
 <p>XM 14 HW MSI T</p>	710292-1	Transom mount MEGA Side Imaging+, MEGA Down Imaging+, Dual Spectrum CHIRP transducer with temperature sensor and 20' cable	<ul style="list-style-type: none"> • SOLIX 10 MEGA SI+ GPS G2 • SOLIX 12 MEGA SI+ GPS G2 • SOLIX 15 MEGA SI+ GPS G2
 <p>XM 9 20 MSI T</p>	710262-1	Transom mount MEGA SI, MEGA DI, DualBeam PLUS, 20/60/86/55 degrees, 200/83/455/800 kHz and 1.2 MHz, temperature built-in	<ul style="list-style-type: none"> • HELIX 9 CHIRP MEGA SI GPS G2N • HELIX 10 CHIRP MEGA SI GPS G2N • HELIX 12 CHIRP MEGA SI GPS G2N

 <p>XM 14 20 MSI T</p>	710265-1	<p>Transom mount MEGA SI, MEGA DI, DualBeam PLUS, 20/60/86/55 degrees, 200/83/455/800 kHz and 1.2 MHz, temperature built-in</p>	<ul style="list-style-type: none"> • SOLIX 10 MEGA SI GPS • SOLIX 12 MEGA SI GPS • SOLIX 15 MEGA SI GPS
 <p>XHS 9 HDSI 180 T</p>	710201-1	<p>Transom Mount Dual/HD Side Imaging 20/74/84 Degree 200/83/455/800 kHz Temperature Sensor</p>	<ul style="list-style-type: none"> • 1199ci SI, 999ci HD SI, 898c HD SI, 899ci HD SI, 998c HD SI • HELIX 9 SI GPS • HELIX 10 SI GPS • HELIX 12 SI GPS
 <p>XNT 9 SI 180 T</p>	710200-1	<p>Transom Mount Compact Dual/Side Imaging 20/74/84 Degree 83/200/455/800 kHz Temperature Sensor</p>	<ul style="list-style-type: none"> • 398C SI, 698ci HD SI, 798ci SI, 899CI HD SI • HELIX 5 SI GPS • HELIX 5 CHIRP SI GPS G2 • HELIX 7 SI GPS • HELIX 7 CHIRP SI GPS G2 • HELIX 7 CHIRP SI GPS G2N • HELIX 9 SI GPS
<p>IN-HULL TRANSDUCERS – 2D sonar</p>	<p>Item Number</p>	<p>Description</p>	<p>Compatible Units</p>
 <p>XP 9 HW</p>	710275-1	<p>In-Hull Dual Spectrum CHIRP Narrow Beam - 25 Degrees, 180-240 kHz Wide Beam - 42 Degrees, 140-200 kHz</p>	<ul style="list-style-type: none"> • HELIX 5 CHIRP G2 (GPS models) • HELIX 7 CHIRP G2/G3 models • HELIX 7 CHIRP G2N/G3N models • HELIX 8 CHIRP G3N models • HELIX 9 CHIRP G2N/G3N models • HELIX 10 CHIRP G2N/G3N models • HELIX 12 CHIRP G2N/G3N models • ICE HELIX CHIRP G2/G3/G3N models
 <p>XP 9 HW T</p>	710276-1	<p>In-Hull Dual Spectrum CHIRP Narrow Beam - 25 Degrees, 180-240 kHz Wide Beam - 42 Degrees, 140-200 kHz with Temperature Sensor</p>	<ul style="list-style-type: none"> • HELIX 5 CHIRP G2 (GPS models) • HELIX 7 CHIRP G2/G3 models • HELIX 7 CHIRP G2N/G3N models • HELIX 8 CHIRP G3N models • HELIX 9 CHIRP G2N/G3N models • HELIX 10 CHIRP G2N/G3N models • HELIX 12 CHIRP G2N/G3N models • ICE HELIX CHIRP G2/G3/G3N models

 <p>XP 14 HW</p>	710286-1	In-Hull Dual Spectrum CHIRP Narrow Beam - 25 Degrees, 180-240 kHz Wide Beam - 42 Degrees, 140-200 kHz	<ul style="list-style-type: none"> • SOLIX 10 Series - All models • SOLIX 12 Series - All models • SOLIX 15 Series - All models
 <p>XP 14 HW T</p>	710287-1	In-Hull Dual Spectrum CHIRP Narrow Beam - 25 De- grees, 180-240 kHz Wide Beam - 42 Degrees, 140-200 kHz Temperature Sensor	<ul style="list-style-type: none"> • SOLIX 10 Series - All models • SOLIX 12 Series - All models • SOLIX 15 Series - All models
 <p>XP 9 20 T</p>	710147-1	In-Hull Mount Single or Dual Beam 20°/60° 200/83 kHz Temp. Sensor Pigtail	<ul style="list-style-type: none"> • All 100 and 300 Series except DI • All 500 Series except DI • All 600 Series except DI • All 700 Series except DI • All 800 Series except DI • All 900 Series except DI, models • All 1100 Series except DI models • All HELIX Series except DI models • HDR650
 <p>XP 14 20 T</p>	710248-1	In-Hull transducer Dual Beam, 20/60 degrees, 200/83 kHz, temp pigtail. For use in single layer fiberglass hull boats	<ul style="list-style-type: none"> • All ONIX Series • SOLIX 10 CHIRP GPS • SOLIX 12 CHIRP GPS • SOLIX 15 CHIRP GPS • ION* Series <p>*Must also have the Sonar Module</p>
TROLLING MOTOR TRANSDUCERS– 2D Sonar	Item Number	Description	Compatible Units
 <p>XTM 9 HW T</p>	710277-1	Trolling Motor Mount Dual Spectrum CHIRP Narrow Beam - 25 Degrees, 180-240 kHz Wide Beam - 42 Degrees, 140-200 kHz temperature Sensor	<ul style="list-style-type: none"> • HELIX 5 CHIRP G2 (GPS models) • HELIX 7 CHIRP G2/G3 models • HELIX 7 CHIRP G2N/G3N models • HELIX 8 CHIRP G3N models • HELIX 9 CHIRP G2N/G3N models • HELIX 10 CHIRP G2N/G3N models • HELIX 12 CHIRP G2N/G3N models • ICE HELIX CHIRP G2/G3/G3N models

 <p>XTM 14 HW T</p>	710288-1	<p>Trolling Motor Mount Dual Spectrum CHIRP Narrow Beam - 25 Degrees, 180-240 kHz Wide Beam - 42 Degrees, 140-200 kHz 20' cable with temperature sensor</p>	<ul style="list-style-type: none"> • SOLIX 10 Series - All Models • SOLIX 12 Series - All Models • SOLIX 15 Series - All Models
 <p>XTM 9 20 T</p>	710160-1	<p>Trolling Motor Mount Single/Dual Beam 20/60 Degree 200/83kHz 20' cable and with temp</p>	<ul style="list-style-type: none"> • All 100 and 300 Series except DI • All 500 Series except DI models • All 600 Series except DI models • All 700 Series except DI models • All 800 Series except DI models • All 800 Series except DI models • All 900 Series except DI, 3D models • All 1100 Series except DI • All HELIX Series except DI
 <p>XTM 9 28 T</p>	710246-1	<p>Trolling Motor Mount Dual Beam, 28/16 Degree, 200/455kHz, 20' cable and temperature sensor</p>	<ul style="list-style-type: none"> • PiranhaMAX 4, PiranhaMAX 4 PT
 <p>XTM 14 20 T</p>	710250-1	<p>Trolling Motor Mount Dual Beam, 20/60 degrees, 200/83 kHz, 20' cable and temperature sensor</p>	<ul style="list-style-type: none"> • SOLIX 10 Series - All Models • SOLIX 12 Series - All Models • SOLIX 15 Series - All Models • ION Series * • All ONIX Series <p>*Must also have the Sonar Module</p>
<p>TROLLING MOTOR TRANSDUCERS– Down Imaging</p>	<p>Item Number</p>	<p>Description</p>	<p>Compatible Units</p>
 <p>XTM 9 HW MDI 75 T</p>	710296-1	<p>Trolling Motor Mount MEGA Down Imaging, Dual Spectrum CHIRP and temperature sensor</p>	<ul style="list-style-type: none"> • HELIX 7 CHIRP MEGA DI GPS G3 • HELIX 7 CHIRP MEGA DI GPS G3N • HELIX 8 CHIRP MEGA DI GPS G3N






 <p>XTM 9 HW MDI T</p>	<p>710281-1</p>	<p>Trolling Motor Mount MEGA Down Imaging+ Dual Spectrum CHIRP temperature Sensor</p>	<ul style="list-style-type: none"> • HELIX 8 MEGA DI GPS G3N • HELIX 9 MEGA DI+ G3N • HELIX 10 MEGA DI+ G3N • HELIX 12 MEGA DI+ G3N
 <p>XTM 14 HW MDI T</p>	<p>710291-1</p>	<p>Trolling Motor Mount MEGA Down Imaging+ Dual Spectrum CHIRP 20' cable with temperature sensor</p>	<ul style="list-style-type: none"> • SOLIX 10 MEGA DI+ GPS G2 • SOLIX 12 MEGA DI+ GPS G2 • SOLIX 15 MEGA DI+ GPS G2
 <p>XTM 9 MDI T</p>	<p>710270-1</p>	<p>Trolling Motor Mount MEGA Down Imaging, DualBeam sonar transducer with temperature sensor</p>	<ul style="list-style-type: none"> • HELIX 9 MEGA DI G2N • HELIX 10 MEGA DI G2N • HELIX 12 MEGA DI G2N
 <p>XTM 9 DI 25 T</p>	<p>710234-1</p>	<p>Trolling Motor Mount Down Imaging/ DualBeam Plus 75/45/ 25/16 Degree 200/455 kHz 455/800 kHz (DI) 20' cable, with temp sensor</p>	<ul style="list-style-type: none"> • HELIX 7 DI GPS • HELIX 7 DI GPS G2 • HELIX 9 DI GPS • HELIX 10 DI GPS • HELIX 12 CHIRP DI GPS • 1159ci HD DI • 959ci HD DI • 859ci HD DI • 688ci DI, 678 DI • 386ci DI, 346c DI • PMAX 4 DI

 <p>XTM 9 WIDE DI 20 T</p>	710235-1	<p>Trolling Motor Mount Down Imaging/ DualBeam 75/45/ 25/16 Degree 200/455 kHz 455/800 kHz (DI), 20' cable with temperature sensor</p>	<ul style="list-style-type: none"> • HELIX 7 DI GPS • HELIX 7 DI GPS G2 • HELIX 9 DI GPS • HELIX 10 DI GPS • HELIX 12 CHIRP DI GPS • 1159ci HD DI • 959ci HD DI • 859ci HD DI
<p>TROLLING MOTOR TRANSDUCERS– Side Imaging</p>	<p>Item Number</p>	<p>Description</p>	<p>Compatible Units</p>
 <p>XTM 9 HW MSI 150 T</p>	710298-1	<p>Trolling Motor Mount MEGA Side Imaging MEGA Down Imaging Dual Spectrum CHIRP with temperature Sensor</p>	<ul style="list-style-type: none"> • HELIX 7 MSI GPS G3 • HELIX 7 MSI GPS G3N
 <p>XTM 9 HW MSI T</p>	710283-1	<p>Trolling Motor Mount MEGA Side Imaging+ MEGA Down Imaging+ Dual Spectrum CHIRP with 20' cable and temperature sensor</p>	<ul style="list-style-type: none"> • HELIX 8 MEGA SI+ GPS G3N • HELIX 9 MEGA SI+ GPS G3N • HELIX 10 MEGA SI+ GPS G3N • HELIX 12 MEGA SI+ GPS G3N
 <p>XTM 9 20 MSI T</p>	710263-1	<p>Trolling Motor Mount 1.2 Mhz/800 kHz/455 kHz MEGA SI, MEGA DI and DualBeam Plus 20' cable with temperature sensor</p>	<ul style="list-style-type: none"> • HELIX 9 MEGA SI GPS G2N • HELIX 10 MEGA SI GPS G2N • HELIX 12 MEGA SI GPS G2N



 <p>XTM 9 HDSI 180 T</p>	710205-1	Trolling Motor Mount Dual/HD Side Imaging 20/74/180 Degree 83/200/455/800kHz 20' cable and with temp	<ul style="list-style-type: none"> • HELIX 9 SI GPS • HELIX 10 SI GPS • HELIX 12 SI GPS • 1199ci HD SI, 999ci HD SI, 899ci HD SI 				
 <p>XTM 9 SI 180 T</p>	710204-1	Trolling Motor Mount Compact SI / DI and DualBeam 20/60/70 Degree 83/200/455/800kHz 20' cable and with temp	<ul style="list-style-type: none"> • HELIX 9 SI GPS • HELIX 7 SI GPS • HELIX 7 SI GPS G2 • HELIX 7 SI GPS G2N • HELIX 5 SI GPS • HELIX 5 SI GPS G2 • 398ci SI, 698ci HD SI, 899ci HD SI 				
<table border="1"> <thead> <tr> <th data-bbox="90 674 553 768">PORTABLE TRANSDUCERS</th> <th data-bbox="553 674 776 768">Item Number</th> <th data-bbox="776 674 1073 768">Description</th> <th data-bbox="1073 674 1534 768">Compatible Units</th> </tr> </thead> </table>				PORTABLE TRANSDUCERS	Item Number	Description	Compatible Units
PORTABLE TRANSDUCERS	Item Number	Description	Compatible Units				
 <p>XPT 9 HW T</p>	710278-1	Portable, suction cup mount, Dual Spectrum CHIRP transducer with Temperature sensor and 20' cable.	<ul style="list-style-type: none"> • HELIX 5 CHIRP G2 models • HELIX 7 CHIRP G2/G3 models • HELIX 7 G2N/G3N models • HELIX 8 G3N models • HELIX 9 G2N/G3N models • HELIX 10 G2N/G3N models • HELIX 12 G2N/G3N models • ICE HELIX CHIRP G2/G2N/G3/G3N models 				
 <p>XPT 9 20 T</p>	710161-1	Portable, suction cup mount, Dual Beam transducer with Temperature sensor and 20' cable.	<ul style="list-style-type: none"> • All 100 / 300 Series except DI models • All 500 Series except DI models • All 600 Series except DI models • All 800 Series except DI models • All 900 Series except DI models • All 1100 Series except DI models • All HELIX non-CHIRP models, except DI • HDR 650 				
<table border="1"> <thead> <tr> <th data-bbox="90 1524 553 1661">S.S. & BRONZE THRU HULL TRANSDUCERS – 2D Sonar</th> <th data-bbox="553 1524 776 1661">Item Number</th> <th data-bbox="776 1524 1073 1661">Description</th> <th data-bbox="1073 1524 1534 1661">Compatible Units</th> </tr> </thead> </table>				S.S. & BRONZE THRU HULL TRANSDUCERS – 2D Sonar	Item Number	Description	Compatible Units
S.S. & BRONZE THRU HULL TRANSDUCERS – 2D Sonar	Item Number	Description	Compatible Units				
 <p>XTH 9 20</p>	710166-1	Bronze thru-hull transducer with Dual Beam sonar, temp sensor and 20' cable. 20/60 Degree, 200/83kHz	<ul style="list-style-type: none"> • All 100 / 300 Series except DI models • All 500 Series except DI models • All 600 Series except DI models • All 800 Series except DI models • All 900 Series except DI models • All 1100 Series except DI models • All HELIX non-CHIRP models, except DI • HDR 650 				

S.S. & BRONZE THRU HULL TRANSDUCERS – Side Imaging	Item Number	Description	Compatible Units
 <p>SSTH 14 HW MSI+ T</p>	710302-1	Stainless Steel thru-hull transducer with MEGA Side Imaging+, MEGA Down Imaging+ and Dual Spectrum CHIRP sonar and includes built-in temperature sensor, fairing block, stainless steel mounting hardware and 20' cable,	<ul style="list-style-type: none"> • SOLIX 10/12/15 MSI+ GPS <ul style="list-style-type: none"> ◦ G2 models
PLASTIC THRU- HULL TRANSDUCERS – 2D Sonar	Item Number	Description	Compatible Units
 <p>XPTH 9 HW T</p>	710279-1	Plastic thru-hull transducer Dual Spectrum CHIRP, temperature Sensor and 20' cable	<ul style="list-style-type: none"> • HELIX 5 G2 (GPS models) • HELIX 7 G2/G3 models • HELIX 7 G2N/G3N models • HELIX 8 G3N models • HELIX 9 G2N/G3N models • HELIX 10 G2N/G3N models • HELIX 12 G2N/G3N models • ICE HELIX G2/G3/G3N models
 <p>XPTH 14 HW T</p>	710289-1	Plastic thru-hull transducer Dual Spectrum CHIRP, temperature Sensor and 20' cable	<ul style="list-style-type: none"> • SOLIX 10 Series - All Models • SOLIX 12 Series - All Models • SOLIX 15 Series - All Models
 <p>XTH 9 20 P</p>	710167-1	Plastic thru-hull Single/Dual Beam transducer with 20' cable. 20/60 Degree, 200/83kHz Transducer: 3.9" L x 2.5" W x 1.16" D Shaft: 1.0" diameter	<ul style="list-style-type: none"> • All HELIX non-CHIRP models, except DI models • All 300 Series except DI models • All 500 Series except DI models • All 600 Series except DI models • All 800 Series except DI models • All 900 Series except DI, 3D models • All 1100 Series except DI models







 <p>XTH 9 20 P</p>	710181-1	<p>Plastic flush mount thru the hull transducer. DualBeam, 20/60 degree, 200/83kHz</p>	<ul style="list-style-type: none"> • All HELIX non-CHIRP models, except DI models • All 300 Series except DI models • All 500 Series except DI models • All 600 Series except DI models • All 800 Series except DI models • All 900 Series except DI, 3D models • All 1100 Series except DI models
 <p>XTH 9 DB 74 P</p>	710185-1	<p>Plastic thru hull Dual Beam, 20/74 degrees. 200/50kHz, transducer with 20' cable 6.7" L x 3" W x 1.4" D (below boat hull). Shaft: 1" diameter. Cable Length: 30 Feet.</p>	<ul style="list-style-type: none"> • 1159ci HD XD Combo • 859ci HD XD Combo • 678c HD XD • 688ci HD XD Combo • 959ci HD XD Combo • All HELIX models except HELIX 7 SONAR G2, HELIX 7 SI GPS, HELIX 7 DI GPS, HELIX 7 SONAR GPS, HELIX 7 DI, HELIX 5 DI G2, HELIX 5 SI GPS, HELIX 5 DI GPS, HELIX 5 SONAR GPS, HELIX 5 DI, HELIX 5 SONAR
<p>PLASTIC THRU- HULL TRANSDUCERS – Side Imaging</p>	<p>Item Number</p>	<p>Description</p>	<p>Compatible Units</p>
 <p>XPTH 9 HW MSI T</p>	710284-1	<p>Plastic thru-hull transducer MEGA SIDE IMAGING+, MEGA Down Imaging+ Dual Spectrum CHIRP, temperature Sensor and 20' cable</p>	<ul style="list-style-type: none"> • HELIX 8 MEGA SI+ GPS G3N • HELIX 9 MEGA SI+ GPS G3N • HELIX 10 MEGA SI+ GPS G3N • HELIX 12 MEGA SI+ GPS G3N
 <p>XPTH 14 HW MSI T</p>	710294-1	<p>Plastic thru-hull transducer MEGA SIDE IMAGING+, MEGA Down Imaging+ Dual Spectrum CHIRP, temperature Sensor and 20' cable</p>	<ul style="list-style-type: none"> • SOLIX 10 MEGA SI+ GPS G2 • SOLIX 12 MEGA SI+ GPS G2 • SOLIX 15 MEGA SI+ GPS G2




 <p>XPTH 9 20 MSI T</p>	710264-1	Plastic Thru Hull MEGA SI / MEGA DI / DualBeam Transducer includes 1.2 Mhz/800 kHz/455 kHz with 20' cable and temp sensor	<ul style="list-style-type: none"> • HELIX 9 MEGA SI GPS G2N • HELIX 10 MEGA SI GPS G2N • HELIX 12 MEGA SI GPS G2N
 <p>XPTH 14 20 MSI T</p>	710267-1	Plastic thru hull MEGA SI / DI and DualBeam Plus transducer with temp sensor	<ul style="list-style-type: none"> • SOLIX 10 CHIRP MEGA SI GPS • SOLIX 12 CHIRP MEGA SI GPS • SOLIX 15 CHIRP MEGA SI GPS • ONIX Series* <p>*Only 455/800 kHz frequencies available for SI and DI</p>
ICE TRANSDUCERS- 2D Sonar	Item Number	Description	Compatible Units
 <p>XI 9 1521</p>	710273-1	Dual Spectrum CHIRP Ice Transducer with 8' cable. 130-250 kHz 15 - 21 Degree.	<ul style="list-style-type: none"> • All ICE HELIX CHIRP G2/G2N/G3/G3N models • All HELIX CHIRP G2/G2N/G3/G3N models in Ice Fishing Mode
 <p>XI 9 20</p>	710211-1	Dual Beam Ice transducer with 8' cable. 20/60 Degree, 200/83 kHz.	<ul style="list-style-type: none"> • All non-CHIRP HELIX units, except DI models • All 100 and 300 Series™ except DI • All 500, 600, 700, 800, 900, 1100 Series, except DI and 3D models
 <p>XI 9 19</p>	710215-1	Dual Beam Ice transducer with 8' cable. 9/19 Degree. 455/240kHz.	<ul style="list-style-type: none"> • ICE 35 • ICE 45 • ICE 55

TROLLING MOTOR TRANSDUCER KIT	Item Number	Description	Compatible Units
 <p data-bbox="188 558 466 590">AD MTM HW MDI</p>	740181-1	<p data-bbox="789 254 1045 579">MEGA DI+ Trolling Motor Transducer Adapter Bracket Rugged composite design conforms to the trolling motor for low profile fit. Adapts transom mount transducer for trolling motor use</p>	<p data-bbox="1084 191 1235 216">Transducers:</p> <ul data-bbox="1084 220 1321 344" style="list-style-type: none"> • XM 9 HW MDI T • XTM 9 HW MDI T • XM 14 HW MDIT • XTM 14 HW MDI T <p data-bbox="1084 386 1243 411">Fish Finders:</p> <ul data-bbox="1084 415 1461 663" style="list-style-type: none"> • HELIX 8 MEGA DI GPS G3N • HELIX 9 MEGA DI+ GPS G3N • HELIX 10 MEGA DI+ GPS G3N • HELIX 12 MEGA DI+ GPS G3N • SOLIX 10 G2 - All Models • SOLIX 12 G2 - All Models • SOLIX 15 G2 - All Models • AD MTM
 <p data-bbox="188 1110 466 1142">AD MTM HW MSI</p>	740182-1	<p data-bbox="789 806 1045 1131">MEGA SI+ Trolling Motor Transducer Adapter Bracket Rugged composite design conforms to the trolling motor for low profile fit. Adapts transom mount transducer for trolling motor use</p>	<p data-bbox="1084 741 1235 766">Transducers:</p> <ul data-bbox="1084 770 1321 894" style="list-style-type: none"> • XM 9 HW MSI T • XTM 9 HW MSI T • XM 14 HW MSI T • XTM 14 HW MSI T <p data-bbox="1084 936 1243 961">Fish Finders:</p> <ul data-bbox="1084 966 1461 1184" style="list-style-type: none"> • HELIX 8 MEGA SI+ GPS G3N • HELIX 9 MEGA SI+ GPS G3N • HELIX 10 MEGA SI+ GPS G3N • HELIX 12 MEGA SI+ GPS G3N • SOLIX 10 MEGA SI+ GPS G2 • SOLIX 12 MEGA SI+ GPS G2 • SOLIX 15 MEGA SI+ GPS G2
 <p data-bbox="256 1520 396 1551">AD MTM</p>	740159-1	<p data-bbox="789 1293 1045 1388">Rugged Trolling Motor Transducer Adapter Bracket</p>	<p data-bbox="1084 1199 1235 1224">Transducers:</p> <ul data-bbox="1084 1228 1279 1287" style="list-style-type: none"> • XM 9 20 MSI T • XM 14 20 MSI T <p data-bbox="1084 1329 1243 1354">Fish Finders:</p> <ul data-bbox="1084 1358 1528 1606" style="list-style-type: none"> • HELIX 9 CHIRP MEGA SI GPS G2N • HELIX 10 CHIRP MEGA SI GPS G2N • HELIX 12 CHIRP MEGA SI GPS G2N • SOLIX 10 SI • SOLIX 12 SI • SOLIX 15 SI
 <p data-bbox="245 1871 407 1902">AD XTM 9</p>	740087-1	<p data-bbox="789 1734 1045 1829">Trolling Motor Adapter for New XNT Transducer</p>	<p data-bbox="1084 1648 1235 1673">Transducers:</p> <ul data-bbox="1084 1680 1273 1965" style="list-style-type: none"> • XNT 9 20 • XNT 9 20 T • XNT 9 SI 180 T • XNT 9 DI T • XNT 9 28 T • XNT 9 HW T • XNT 14 20 T • XNT 14 DI T • XNT 9 QB 90 T


TRANSOM MOUNTING HARDWARE & ADAPTERS	Item Number	Description	Compatible Units
 <p>MHX XM HW</p>	740183-1	<p>MEGA Imaging+ Metal Mounting Bracket Durable and rugged metal construction Allows adjustment of transducer angle Ideal for transom-mount installations</p>	<p>Transducers:</p> <ul style="list-style-type: none"> • XM 9 HW MSI T • XM 9 HW MDI T • XM 9 20 MSI T • XM 14 HW MDI T • XM 14 HW MSIT • XM 14 20 MSI T • XM 14 74 MSIT
 <p>MHX MXNT</p>	740162-1	<p>Durable and rugged metal construction Impact-Release Mounting Bracket</p>	<p>Transducers:</p> <ul style="list-style-type: none"> • XNT 9 DI T • XNT 9 28 T • XNT 9 20 T • XNT 9 HW T • XNT 14 20 T • XNT 14 74 T • XNT 14 DI T
 <p>MHX HS</p>	740011-1	<p>HDWE - High Speed 200 KHZ Metal & Plastic</p>	<p>Transducers:</p> <ul style="list-style-type: none"> • XHS 9 DB 74 T • XHS 9 SI 160 T • XHS 9 HDSI 180T • XT 14 20 HDSI T • XT 14 74 HDSI T
 <p>MHX XNT</p>	740093-1	<p>HDWE - XNT with kick-up</p>	<p>Transducers:</p> <ul style="list-style-type: none"> • XNT 9 DI T • XNT 9 28 T • XNT 9 20 T • XNT 9 20 • XNT 9 HW T • XNT 14 20 T • XNT 14 74 T • XNT 14 DI T
PORTABLE MOUNTING HARDWARE	Item Number	Description	Compatible Units
 <p>MHX XNPT</p>	740090-1	<p>Transom transducer mounting hardware</p>	<p>Transducers:</p> <ul style="list-style-type: none"> • XNT 9 DI T • XNT 9 28 T • XNT 9 HW T • XNT 9 20 T • XNT 9 20 • XNT 14 20 T • XNT 14 74 T • XNT 14 DI T

IN-DASH MOUNTS	Item Number	Description	Compatible Units
 <p data-bbox="261 344 396 373">IDMK H5</p>	740142-1	<p data-bbox="800 243 1052 436">In-dash mounting kit for quick and easy in-dash installation. Includes gasket, made of durable, adhesive backing</p>	<ul data-bbox="1089 268 1317 298" style="list-style-type: none"> • All HELIX 5 Series
 <p data-bbox="261 653 396 682">IDMK H7</p>	740174-1	<p data-bbox="800 518 1052 669">In-dash mounting kit for quick and easy in-dash installation. Includes bracket and hardware</p>	<ul data-bbox="1089 548 1308 577" style="list-style-type: none"> • All HELIX 7 Series
 <p data-bbox="240 888 415 917">IDMK H89R</p>	740179-1	<p data-bbox="800 735 1052 886">In-dash mounting kit for quick and easy in-dash installation. Includes bracket, clamp and hardware</p>	<ul data-bbox="1105 726 1507 785" style="list-style-type: none"> • HELIX 8 G3N Series - All models • HELIX 9 G3N Series - All models
 <p data-bbox="240 1136 415 1165">IDMK H910R</p>	740155-1	<p data-bbox="800 1010 1052 1161">In-dash mounting kit for quick and easy in-dash installation. Includes bracket, clamp and hardware</p>	<ul data-bbox="1089 1039 1455 1098" style="list-style-type: none"> • All HELIX 9 Series, except G3N models
 <p data-bbox="245 1446 407 1476">IDMK H12R</p>	740175-1	<p data-bbox="800 1289 1052 1440">In-dash mounting kit for quick and easy in-dash installation. Includes bracket, clamp and hardware</p>	<ul data-bbox="1089 1318 1325 1348" style="list-style-type: none"> • All HELIX 12 Series
 <p data-bbox="256 1793 396 1822">IDMK S10</p>	740173-1	<p data-bbox="800 1558 1052 1709">In-dash mounting kit for quick and easy in-dash installation. Includes bracket and hardware</p>	<ul data-bbox="1089 1587 1435 1617" style="list-style-type: none"> • SOLIX 10 Series - All Models


 <p>IDMK S12</p>	740176-1	In-dash mounting kit for quick and easy in-dash installation. Includes bracket and hardware	<ul style="list-style-type: none"> • SOLIX 12 Series - All Models
 <p>IDMK S15</p>	740177-1	In-dash mounting kit for quick and easy in-dash installation. Includes bracket and hardware	<ul style="list-style-type: none"> • SOLIX 15 Series - All Models
MOUNTING HARDWARE	Item Number	Description	Compatible Units
 <p>GM S10</p>	740172-1	Replacement Mounting Bracket Kit <ul style="list-style-type: none"> • Includes attachment screws and knobs 	<ul style="list-style-type: none"> • SOLIX 10 Series - All Models
 <p>GM S12</p>	740164-1	Replacement Mounting Bracket Kit <ul style="list-style-type: none"> • Includes Attachment Screws and Knobs 	<ul style="list-style-type: none"> • SOLIX 12 Series - All Models
 <p>GM S15</p>	740165-1	Replacement Mounting Bracket Kit <ul style="list-style-type: none"> • Includes Attachment Screws and Knobs 	<ul style="list-style-type: none"> • SOLIX 15 Series - All Models
 <p>GM H5</p>	740143-1	Replacement Mounting Bracket Kit includes attachment screws and knobs	<ul style="list-style-type: none"> • All HELIX 5 Series




 GM H7	740146-1	Replacement Mounting Bracket Kit includes attachment screws and knobs	<ul style="list-style-type: none"> • All HELIX 7 Series
 GM H910	740149-1	Replacement Mounting Bracket Kit includes attachment screws and knobs	<ul style="list-style-type: none"> • All HELIX 8 Series • All HELIX 9 Series • All HELIX 10 Series
 GM H12	740151-1	Replacement Mounting Bracket Kit includes attachment screws and knobs	<ul style="list-style-type: none"> • All HELIX 12 Series

TEMPERATURE AND SPEED SENSORS	Item Number	Description	Compatible Units
-------------------------------	-------------	-------------	------------------






 TS W	730000-1	Transom Mount Speed/ Temp sensor	<ul style="list-style-type: none"> • ONIX 10 - TS W+ PC 12 ST • ONIX 8 - TS W+ PC 12 ST • SOLIX 12 TS W+ PC 12ST • SOLIX 15 TS W + PC 12 ST • 700 HD - TS W + AS TY • 600 Series TS W + ASTY • 500 Series, 800 Series, 900 Series, 1100 Series, • ALL HELIX Series
--	----------	----------------------------------	--


EXTENSION CABLES	Item Number	Description	Compatible Units
------------------	-------------	-------------	------------------




 EC M10	720096-1	Transducer extension cable 10 Feet, 7 Pin	<ul style="list-style-type: none"> • All transducers except for those used with the following fish finders: SOLIX, ION, ONIX and Fishin' Buddy • Compatible Transducers: XNT 9 HW T, XNT 9 HW MDI 75 T, XM 9 HW MDI T, XNT 9 HW MSI 150 T, XM 9 HW MSI T, XP 9 H, XP 9 HW T, XTM 9 HW T, XTM 9 HW MDI 75 T, XTM 9 HW MDI T, XTM 9 HW MSI 150T, XTM 9 HW MSI T, XPT 9 HW T, XPTH 9 HW T, XPTH 9 HW MSI T, XNT 9 20 T, XNT 9 20, XNT 9 28 T, XNT 9 28, XP 9 20 T, XP 9 20, XAP 9 20, XTM 9 20 T, XTM 9 20, XHS 9 HDSI 180 T, XNT 9 180 T, XNT 9 QB 90 T, XNT 9 DB 74 T, XTM 9 QB 90 T, XM 9 20 MSI T, XTM 9 20 MSI T, XPTH 9 20 MSI T
---	----------	--	--

 <p>EC M30</p>	<p>720096-2</p>	<p>Transducer extension cable 30 Feet, 7 Pin</p>	<ul style="list-style-type: none"> • All transducers except for those used with the following fish finders: SOLIX, ION, ONIX and Fishin' Buddy • Compatible Transducers: XNT 9 HW T, XNT 9 HW MDI 75 T, XM 9 HW MDI T, XNT 9 HW MSI 150 T, XM 9 HW MSI T, XP 9 H, XP 9 HW T, XTM 9 HW T, XTM 9 HW MDI 75 T, XTM 9 HW MDI T, XTM 9 HW MSI 150T, XTM 9 HW MSI T, XPT 9 HW T, XPTH 9 HW T, XPTH 9 HW MSI T, XNT 9 20 T, XNT 9 20, XNT 9 28 T, XNT 9 28, XP 9 20 T, XP 9 20, XAP 9 20, XTM 9 20 T, XTM 9 20, XHS 9 HDSI 180 T, XNT 9 180 T, XNT 9 QB 90 T, XNT 9 DB 74 T, XTM 9 QB 90 T, XM 9 20 MSI T, XTM 9 20 MSI T, XPTH 9 20 MSI T
 <p>EC M3 14W10</p>	<p>720106-1</p>	<p>10' Extension Cable for 14-pin transducers</p>	<ul style="list-style-type: none"> • Compatible with transducers for the following models: -MEGA 360 Imaging -Built-in MEGA Imaging on select Minn Kota trolling motors - All 14-pin transducers; including: XNT 14 HW T, XM 14 HW MDI T, XM 14 HW MSI T, XP 14 HW, XP 14 HW T, XTM 14 HW T, XTM 14 HW MDI T, SSTH 14 HW MSI+ T, XPTH 14 HW T, XPTH 14 HW MSI T, XNT 14 20 T, XM 14 20 MSI T, XP 14 20 T, XTM 14 20 T, XPTH 14 20 MSI T
 <p>EC M3 14W30</p>	<p>720106-2</p>	<p>30' Extension Cable for 14-pin transducers</p>	<ul style="list-style-type: none"> • Compatible with transducers for the following models: -MEGA 360 Imaging -Built-in MEGA Imaging on select Minn Kota trolling motors - All 14-pin transducers; including: XNT 14 HW T, XM 14 HW MDI T, XM 14 HW MSI T, XP 14 HW, XP 14 HW T, XTM 14 HW T, XTM 14 HW MDI T, SSTH 14 HW MSI+ T, XPTH 14 HW T, XPTH 14 HW MSI T, XNT 14 20 T, XM 14 20 MSI T, XP 14 20 T, XTM 14 20 T, XPTH 14 20 MSI T




POWER CABLES	Item Number	Description	Compatible Units
 <p data-bbox="277 470 375 506">HCCT</p>	740184-1	<p data-bbox="792 212 1057 443">HELIX Cable Connector Tray Connect multiple cable inputs with a single tray Simple installation for quick removal, storage and security</p>	<ul data-bbox="1089 212 1365 338" style="list-style-type: none"> • HELIX 8 - All models • HELIX 9 - All models • HELIX 10 - All models • HELIX 12 - All models
 <p data-bbox="277 743 375 779">PC 10</p>	720002-1	<p data-bbox="792 638 1008 701">Power cable - 6 feet long</p>	<ul data-bbox="1089 575 1463 800" style="list-style-type: none"> • Many Humminbird models produced after 1988; including • 300, 500, 700 Series (non-Side or Down Imaging models) • HELIX 5 & 7 Series (non-Side or Down Imaging models) • PMAX Series
 <p data-bbox="277 1121 375 1157">PC 11</p>	720057-1	<p data-bbox="792 995 1057 1058">Power cable w/choke- 6 feet long</p>	<ul data-bbox="1089 905 1479 1062" style="list-style-type: none"> • All 700 HD, 800, 900, 1100 Series models • All HELIX 5 and 7 Side Imaging and Down Imaging models • All HELIX 8, 9, 10, 12 Series
 <p data-bbox="191 1451 461 1486">PC HELIX 12V DC</p>	720105-1	<p data-bbox="808 1325 1040 1388">12V Cigarette Lighter power cord, 8 ft long</p>	<ul data-bbox="1089 1262 1446 1419" style="list-style-type: none"> • All HELIX models • All ICE HELIX models • All ICE Flashers models • All 300, 500, 700, 800, 900, 1100 models
 <p data-bbox="277 1814 375 1850">PC 12</p>	720085-1	<p data-bbox="824 1667 1024 1730">Power cable- 6 feet power cable</p>	<ul data-bbox="1089 1646 1284 1709" style="list-style-type: none"> • All SOLIX Series • All ONIX Series

TRANSDUCER ADAPTER CABLES	Item Number	Description	Compatible Units
 <p>9 M SIDB Y</p>	720101-1	<p>Transducer Y-cable allows both a Side Imaging and a 2D transducer to be connected to one Humminbird unit for high speed depth and sonar performance.</p>	<ul style="list-style-type: none"> • All Side Imaging and Down Imaging units in the following series: 300, 500, 700, 800, 900, 1100, HELIX series *Compatible with models that utilize 455kHz/800kHz, MEGA Imaging and MEGA Imaging+ frequencies
 <p>9 M SILR Y</p>	720102-1	<p>Y-cable allows for installation of separate left and right Side Imaging transducers to be connected to one Humminbird unit for a combined Side Imaging picture</p>	<ul style="list-style-type: none"> • All Side Imaging and Down Imaging units in the following series: 300, 500, 700, 800, 900, 1100, HELIX series *Compatible with models that utilize 455kHz/800kHz, MEGA Imaging and MEGA Imaging+ frequencies
 <p>14 M SIDB Y</p>	720103-1	<p>Transducer Y-cable allows both a Side Imaging and a 2D transducer to be connected to one Humminbird unit for high speed depth and sonar performance.</p>	<ul style="list-style-type: none"> • All Side Imaging and Down Imaging units in the following series: SOLIX, ONIX and ION *Compatible with models that utilize 455kHz/800kHz, MEGA Imaging and MEGA Imaging+ frequencies
 <p>14 M SILR Y</p>	720104-1	<p>Y-cable allows for installation of separate left and right Side Imaging transducers to be connected to one Humminbird unit for a combined Side Imaging picture</p>	<ul style="list-style-type: none"> • All Side Imaging and Down Imaging units in the following series: 300, 500, 700, 800, 900, 1100, HELIX *Compatible with models that utilize 455kHz/800kHz, MEGA Imaging and MEGA Imaging+ frequencies
 <p>9 M360 2DDI Y</p>	720107-1	<p>Combines MEGA 360 Imaging transducer and 7-pin Dual Spectrum/MEGA Imaging+ transducers into one 7-pin transducer plug for connection to the same, compatible HELIX fish finder.</p>	<ul style="list-style-type: none"> • HELIX G3N models with MEGA Imaging+ • For use when connecting a MEGA 360 Imaging transducer to a single compatible HELIX fish finder, in conjunction with an external transducer (Dual Spectrum CHIRP or DI & Dual Spectrum CHIRP transducer)




 <p>14 M360 2DDI Y</p>	720108-1	Combines MEGA 360 Imaging transducer and 14-pin Dual Spectrum / MEGA Imaging+ transducers (including Built-in MEGA Imaging) into one 14-pin plug for connection to the same, compatible control head. 30" on Dual Spectrum CHIRP side of cable and 10' cable on the MEGA 360 side	<ul style="list-style-type: none"> • All SOLIX 10/12/15 G2 models • For use when connecting a MEGA 360 Imaging transducer to a compatible SOLIX or HELIX fish finder, in conjunction with a Built-in MEGA Imaging transducer or external 14-pin 2D /MDI transducer.
---	----------	---	---

ETHERNET CABLES	Item Number	Description	Compatible Units
 <p>AC EC 5E</p>	720073-6	Ethernet Cable – 5ft Female-Female: *May require use of AS EC QDE depending on Compatible unit. See AS EC QDE for details	<ul style="list-style-type: none"> • All SOLIX, ION, ONIX The below models also require (1) AS EC QDE to use this product: <ul style="list-style-type: none"> • 1199ci HD SI, 1159ci HD DI, 1159ci HD • 999ci HD, 959ci HD DI, 959ci HD • 899ci HD, 859ci HD DI, 859ci HD • 798ci HD • HELIX 9, 10, 12 Gen-1 models • All HELIX G2N and newer models
 <p>AS EC 10E</p>	720073-2	Ethernet Cable – 10 ft Female-Female: *May require use of AS EC QDE depending on Compatible unit. See AS EC QDE for details	<ul style="list-style-type: none"> • All SOLIX, ION, ONIX The below models also require (1) AS EC QDE to use this product: <ul style="list-style-type: none"> • 1199ci HD SI, 1159ci HD DI, 1159ci HD • 999ci HD, 959ci HD DI, 959ci HD • 899ci HD, 859ci HD DI, 859ci HD • 798ci HD • HELIX 9, 10, 12 Gen-1 models • All HELIX G2N and newer models
 <p>AS EC 15E</p>	720073-5	Ethernet Cable - 15 ft Female-Female: *May require use of AS EC QDE depending on Compatible unit. See AS EC QDE for details	<ul style="list-style-type: none"> • All SOLIX, ION, ONIX The below models also require (1) AS EC QDE to use this product: <ul style="list-style-type: none"> • 1199ci HD SI, 1159ci HD DI, 1159ci HD • 999ci HD, 959ci HD DI, 959ci HD • 899ci HD, 859ci HD DI, 859ci HD • 798ci HD • HELIX 9, 10, 12 Gen-1 models • All HELIX G2N and newer models

 <p>AS EC 20E</p>	<p>720073-3</p>	<p>Ethernet Cable – 20 ft Female-Female:</p> <p>*May require use of AS EC QDE depending on Compatible unit.</p> <p>See AS EC QDE for details</p>	<ul style="list-style-type: none"> • All SOLIX, ION, ONIX <p>The below models also require (1) AS EC QDE to use this product:</p> <ul style="list-style-type: none"> • 1199ci HD SI, 1159ci HD DI, 1159ci HD • 999ci HD, 959ci HD DI, 959ci HD • 899ci HD, 859ci HD DI, 859ci HD • 798ci HD • HELIX 9, 10, 12 Gen-1 models • All HELIX G2N and newer models
 <p>AS EC 30E</p>	<p>720073-4</p>	<p>Ethernet Cable - 30 ft Female-Female:</p> <p>*May require use of AS EC QDE depending on Compatible unit.</p> <p>See AS EC QDE for details</p>	<ul style="list-style-type: none"> • All SOLIX, ION, ONIX <p>The below models also require (1) AS EC QDE to use this product:</p> <ul style="list-style-type: none"> • 1199ci HD SI, 1159ci HD DI, 1159ci HD • 999ci HD, 959ci HD DI, 959ci HD • 899ci HD, 859ci HD DI, 859ci HD • 798ci HD • HELIX 9, 10, 12 Gen-1 models • All HELIX G2N and newer models
 <p>AS ECX 30E</p>	<p>760025-1</p>	<p>Ethernet Extension Cable Female-Male:</p> <p>The Ethernet Extension Cable is a 30' cable that allows you to extend the length of your ethernet cables.</p>	<p>Requires at least one Ethernet cable: AS EC5E AS EC10E, AS EC15E, AS EC20E, AS EC30E</p> <ul style="list-style-type: none"> • SOLIX, ION, ONIX <p>These models also require (1) AS EC QDE to use this product:</p> <ul style="list-style-type: none"> • 1199ci HD SI, 1159ci HD DI, 1159ci HD • 999ci HD, 959ci HD DI, 959ci HD • 899ci HD, 859ci HD DI, 859ci HD • 798ci HD • HELIX 9, 10, 12 Gen-1 models • All HELIX G2N and newer models
 <p>AS EC QDE</p>	<p>720074-1</p>	<p>Ethernet Adapter Cable converts from metal screw-on connector quick-disconnect, press-fit connector.</p>	<ul style="list-style-type: none"> • The below models also require (1) AS EC QDE to connect to complete an Ethernet connection: • 1199ci HD SI, 1159ci HD DI, 1159ci HD • 999ci HD, 959ci HD DI, 959ci HD • 899ci HD, 859ci HD DI, 859ci HD • 798ci HD • HELIX 9, 10, 12 Gen-1 models • All HELIX G2N and newer models

 <p>AS ETH 5PXG</p>	<p>408450-1</p>	<p>Use this 5-Port Ethernet Switch to network multiple Humminbird units, radar, Minn Kota trolling motors. Ethernet cable(s) are required depending on the number of devices you plan to add to this switch.</p>	<ul style="list-style-type: none"> • All SOLIX, ION, ONIX <p>The below models also require (1) AS EC QDE to use this item:</p> <ul style="list-style-type: none"> • 1199ci HD SI, 1159ci HD DI, 1159ci HD • 999ci HD, 959ci HD DI, 959ci HD • 899ci HD, 859ci HD DI, 859ci HD • 798ci HD, 788ci HD DI, 788ci HD • HELIX 9, 10, 12 Gen-1 models • All HELIX G2N and newer models
 <p>DUAL HELIX STARTER KIT HWAL</p>	<p>760060-1</p>	<p>Everything needed to network two Ethernet-equipped, HELIX models on your aluminum boat. (1) XNT 9 HW T Transom Mount Dual Spectrum HW CHIRP Transducer and metal mounting hardware, (1) AS EC 20E Ethernet Cable, (2) AS EC QDE Ethernet Adapters, (1) MKR-MDI-1 Built-In MEGA Down Imaging Trolling Motor Adapter, (1) 9 M SIDB Y Transducer Y- Cable</p>	<ul style="list-style-type: none"> • All HELIX 8 / 9 / 10 / 12 G3N Series models
 <p>DUAL HELIX STARTER KIT HWFG</p>	<p>760061-1</p>	<p>Everything needed to network two Ethernet-equipped, HELIX models on your fiberglass boat. (1) XP 9 HW T In-Hull Mount Dual Spectrum HW CHIRP Transducer and epoxy, (1) AS EC 20E Ethernet Cable, (2) AS EC QDE Ethernet Adapters, (1) MKR-MDI-1 Built-In MEGA Down Imaging Trolling Motor Adapter, (1) 9 M SIDB Y Transducer Y-Cable.</p>	<ul style="list-style-type: none"> • All HELIX 8 / 9 / 10 / 12 G3N Series models

MEGA 360 IMAGING	Item Number	Description	Compatible Units
 <p data-bbox="139 709 521 741">MEGA 360 Imaging-Ultrex</p>	411250-1	<p data-bbox="792 174 1057 363">MEGA 360 Imaging transducer, compatible with ULTREX trolling motors, provides 125' of MEGA Imaging detail all around your boat.</p> <p data-bbox="816 405 1032 464"><u>RECOMMENDED ACCESSORIES:</u></p> <p data-bbox="800 474 1049 533">HELIX: • AS GPS HS (Part# 408400-1)</p> <p data-bbox="800 543 1049 602">SOLIX: • AS GPS HS (Part#408400-1)</p> <p data-bbox="824 613 1024 672">• AS GPS NMEA (Part# 720080-1)</p> <p data-bbox="808 682 1040 701">Transducer Y Cable:</p> <p data-bbox="824 711 1024 770">• 14 M360 2DDI Y (Part# 720108-1)</p> <p data-bbox="906 781 943 800">OR</p> <p data-bbox="865 810 1057 869">• 9 M360 2DDI Y (Part# 720107-1)</p>	<ul data-bbox="1089 216 1523 422" style="list-style-type: none"> • All HELIX 8-12 G3N models with MEGA Imaging+ • All SOLIX G2 models with MEGA Imaging+ • Designed for use with MINN KOTA® Ultrex trolling motors
 <p data-bbox="102 1335 537 1367">MEGA 360 Imaging – Fortrex</p>	411260-1	<p data-bbox="792 947 1057 1178">MEGA 360 Imaging transducer, compatible with FORTREX and MAXXUM trolling motors, provides 125' of MEGA Imaging detail all around your boat.</p> <p data-bbox="816 1220 1032 1278"><u>RECOMMENDED ACCESSORIES:</u></p> <p data-bbox="800 1289 1049 1348">HELIX: • AS GPS HS (Part# 408400-1)</p> <p data-bbox="800 1358 1049 1417">SOLIX: • AS GPS HS (Part#408400-1)</p> <p data-bbox="824 1428 1024 1486">• AS GPS NMEA (Part# 720080-1)</p> <p data-bbox="808 1497 1040 1516">Transducer Y Cable:</p> <p data-bbox="824 1526 1024 1585">• 14 M360 2DDI Y (Part# 720108-1)</p> <p data-bbox="906 1596 943 1614">OR</p> <p data-bbox="824 1625 1008 1684">• 9 M360 2DDI Y (Part# 720107-1)</p>	<ul data-bbox="1089 957 1523 1163" style="list-style-type: none"> • All HELIX 8-12 G3N models with MEGA Imaging+ • All SOLIX G2 models with MEGA Imaging+ • Designed for use with MINN KOTA® Fortrex and Maxxum Trolling Motors

 <p>MEGA 360 Imaging - Universal</p>	<p>411390-1</p>	<p>MEGA 360 Imaging transducer, with universal boat mount, provides 125' of MEGA Imaging detail all around your boat.</p> <p><u>RECOMMENDED ACCESSORIES:</u> HELIX: • AS GPS HS (Part# 408400-1) SOLIX: • AS GPS HS (Part#408400-1) • AS GPS NMEA (Part# 720080-1) Transducer Y Cable: • 14 M360 2DDI Y (Part# 720108-1) OR • 9 M360 2DDI Y (Part# 720107-1)</p>	<ul style="list-style-type: none"> • All HELIX 8-12 G3N models with MEGA Imaging+ • All SOLIX G2 models with MEGA Imaging+ • Universal mount is configurable to almost any boat with adjustable GiegerTec Marine mount.
SONAR MODULES			
Item Number	Description	Compatible Units	
 <p>SM3000</p>	<p>408040-1</p>	<p>MFD Black Box Ethernet Sonar Sonar module-Speed & temp, Ethernet, 2D digital sonar, SI, DI and 2D CHIRP</p>	<ul style="list-style-type: none"> • ION and ONIX Series • XD M260 1K, XD R99 2K, XD B260 1K, XD B164 1K, XD SSW50, XD SSW200, XD 600P • All SOLIX Series
ADVANCED FISHING SYSTEMS			
Item Number	Description	Compatible Units	
 <p>AS ETH NMEA2K</p>	<p>408390-1</p>	<p>Waterproof black box, connects via Ethernet Connects to established NMEA 2000® network. Intuitive user interface features data boxes and pre-programmed instrument views</p>	<p>These models also require (1) AS EC QDE to use this product:</p> <ul style="list-style-type: none"> • 1199ci HD SI, 1159ci HD DI, 1159ci HD • 999ci HD, 959ci HD DI, 959ci HD • 899ci HD, 859ci HD DI, 859ci HD • 798ci HD • HELIX 9, 10, 12 Gen-1 models • All HELIX G2N and G3N models

 <p>AS HHGPS</p>	<p>700030-1</p>	<p>Handheld GPS Connection Kit includes: NMEA connection cable, Y cable and detailed instructions. This kit requires the handheld GPS manufacturers NMEA data cable to complete the connection to your handheld GPS.</p>	<ul style="list-style-type: none"> • All 700 Series • All 800 Series • All 900 Series • All 1100 Series
 <p>AS T Y</p>	<p>720075-1</p>	<p>This Y cable is required for optional temp sensor to connect to Select Humminbird Series product.</p>	<ul style="list-style-type: none"> • 600 series • 700 series • 800 series • 900 series • 1100 series • All HELIX models
 <p>AS GPS NMEA</p>	<p>720080-1</p>	<p>Adapter Cable to connect with optional external GPS receiver AS GRP or AS GPS HS and 1 additional NMEA 0183 communication</p>	<ul style="list-style-type: none"> • All SOLIX Series • All ONIX Series
 <p>AS GRP</p>	<p>408920-1</p>	<p>Precision GPS/WAAS receiver provides fast position fixes accurate within 2.5 meters.</p>	<ul style="list-style-type: none"> • All HELIX 7 G2N/G3N Series • All HELIX 8 / 9 / 10 / 12 Series models <p>Models require (1) AS GPS NMEA</p> <ul style="list-style-type: none"> • All ONIX Series* • All SOLIX Series*

 <p>AS GPS HS</p>	<p>408400-1</p>	<p>Precision GPS/WAAS receiver provides fast position fixes accurate within 2.5 meters and provides constant vessel heading with internal heading sensor compass</p>	<ul style="list-style-type: none"> • All HELIX 7 G2N/G3N Series • All HELIX 8 / 9 / 10 / 12 Series models • 859ci HD Combo, 859ci HD DI Combo, 859ci HD XD Combo, 899ci HD SI Combo • 959ci HD Combo, 959ci HD DI Combo, 959ci HD XD Combo, 999ci HD SI Combo • 1159ci HD Combo, 1159ci HDDI Combo, 1159ci HD XD Combo, 1199ci HD SI Combo <p>Models require (1) AS GPS NMEA</p> <ul style="list-style-type: none"> • All ONIX Series* • All SOLIX Series* <p>Optional Accessory for use with</p> <ul style="list-style-type: none"> • MEGA 360 Imaging – all models • AS 360SSI • AS 360 TM
 <p>RC 2</p>	<p>410180-1</p>	<p>Wireless remote for compatible Humminbird fish finders. Mark waypoints, adjust zoom levels, sensitivity, custom views and more.</p>	<ul style="list-style-type: none"> • All HELIX G2N & G3N Series • All SOLIX Series
UNIT COVERS	Item Number	Description	Compatible Units
 <p>UCPM 4</p>	<p>780033-1</p>	<p>Protective Cover protects lens during storage</p>	<ul style="list-style-type: none"> • PiranhaMAX 4 • PiranhaMAX 4 DI • Fishin Buddy MAX • Fishin Buddy MAX DI
 <p>UC H5</p>	<p>780028-1</p>	<p>Protective cover protects lens during storage. Durable, easy-on neoprene design</p>	<ul style="list-style-type: none"> • All HELIX 5 Series

 <p>UC H7</p>	780029-1	<p>Protective cover protects lens during storage. Durable, easy-on neoprene design</p>	<ul style="list-style-type: none"> • All HELIX 7 Series
 <p>UC H7 PR</p>	780036-1	<p>Protective cover protects lens during storage. Durable, easy-on rubberized design</p>	<ul style="list-style-type: none"> • HELIX 7 - all models
 <p>UC H89</p>	780038-1	<p>Protective cover protects lens during storage. Durable, easy-on rubberized design</p>	<ul style="list-style-type: none"> • HELIX 8 G3N models • HELIX 9 G3N models
 <p>UC H910</p>	780030-1	<p>Protective cover protects lens during storage. Durable, easy-on rubberized design</p>	<ul style="list-style-type: none"> • HELIX 9 Series <ul style="list-style-type: none"> ◦ Gen-1 and G2N models • All Helix 10 Series
 <p>UC H12</p>	780031-1	<p>Protective cover protects lens during storage. Durable, easy-on rubberized design</p>	<ul style="list-style-type: none"> • All HELIX 12 Series
 <p>UC S10</p>	780037-1	<p>Protective cover protects lens during storage. Durable, easy-on rubberized design</p>	<ul style="list-style-type: none"> • All SOLIX 10 Series
 <p>UC S12</p>	780034-1	<p>Protective cover protects lens during storage. Durable, easy-on rubberized design</p>	<ul style="list-style-type: none"> • All SOLIX 12 Series

 <p>UC S15</p>	780035-1	Protective cover protects lens during storage. Durable, easy-on rubberized design	<ul style="list-style-type: none"> • All SOLIX 15 Series
PORTABLE CONFIGURATIONS	Item Number	Description	Compatible Units
 <p>9AH BK</p>	770030-1	Portable 9 Ah Battery and Charger	<ul style="list-style-type: none"> • All ICE Series • All HELIX Series • PiranhaMAX Series • 300 Series • 500 Series • 600 Series • 700 Series
 <p>PTC U2</p>	740157-1	Soft Portable Case (includes gel-cell battery and charger)	<ul style="list-style-type: none"> • All 100 Series • All 300 Series • All 500 Series • All 600 Series • All 700 Series • HELIX 5 Series • HELIX 7 Series
 <p>PTC UNB2</p>	740157-1NB	Soft Portable Case without battery (unit not included)	<ul style="list-style-type: none"> • All 100 Series • All 300 Series • All 500 Series • All 600 Series • All 700 Series • HELIX 5 Series • HELIX 7 Series
ICE ACCESSORIES	Item Number	Description	Compatible Units
 <p>ICE PTC CHIRP H57 FB</p>	740178-1NB	ICE conversion kit for HELIX CHIRP models. Includes Dual Spectrum CHIRP Ice transducer / float, mounting hardware, soft side bag and power cable. Battery and charger NOT included	<ul style="list-style-type: none"> • All HELIX 5 G2 & HELIX 7 G2, G2N, G3 and G3N models with CHIRP • All ICE HELIX G2/G2N/G3/G3N Series models

 <p>ICE PTC CHIRP H8910</p>	740185-NB	ICE conversion kit for HELIX CHIRP models. Includes Dual Spectrum CHIRP Ice transducer / float, mounting hardware, and power cable. Battery and charger NOT included	<ul style="list-style-type: none"> • All HELIX 8 / 9 / 10 models with CHIRP sonar <ul style="list-style-type: none"> ◦ G2N/G3N series
 <p>ICE PTC UNB2</p>	740158-1NB	ICE conversion kit for HELIX models without CHIRP sonar. Includes Dual Beam ice transducer / float, mounting hardware, soft side bag and power cable. Battery and charger NOT included.	<ul style="list-style-type: none"> • HELIX 5 SONAR • HELIX 5 SONAR GPS • HELIX 5 SONAR G2 • HELIX 7 SONAR • HELIX 7 SONAR GPS • HELIX 7 SONAR G2
 <p>MHX ICE</p>	740105-1	Mounting Hardware – Ice transducer and cable wrap	<ul style="list-style-type: none"> • ICE HELIX – All models
 <p>CC ICE</p>	780015-1	Soft Sided Bag for ICE Flashers	<ul style="list-style-type: none"> • ICE 35, ICE 45, ICE 55
AUTOPILOT AND ACCESSORIES			
 <p>SC 110 AP Kit</p>	700052-1	Kit includes Autopilot 3.5" color TFT display, Course Computer with Fluxgate Compass, Rudder Reedback Unit and Rate Gyro with 30m cable. Rotary knob and push button controls.	All Autopilot products are stand alone. They do not need a HB product to work

 <p>SC 110 AP Kit w/o FB</p>	700053-1	Kit includes Autopilot 3.5" color TFT display, Course Computer with Fluxgate Compass and Rate Gyro, and 30m cable. Rotary knob and push button controls.	All Autopilot products are stand alone. They do not need a HB product to work
 <p>SC 110, display only</p>	409100-1	3.5" color TFT display with rotary knob and push button controls.	<ul style="list-style-type: none"> • SC 110 AP Kit w/o FB
 <p>SCP 110 Course Computer</p>	408180-1	High speed, highly reliable SCP 110 course computer. It optimizes rudder movement by working with the GPS speed, Fluxgate Compass and Rate Gyro	<ul style="list-style-type: none"> • SC 110 AP Kit • SC 110 AP Kit w/o FB • SC 110 Display Only
 <p>FB 30</p>	408150-1	This brushless RFU features a unique, linear variable transformer - proving decades of reliable performance	<ul style="list-style-type: none"> • SC 110 AP Kit • SC 110 AP Kit w/o FB • SC 110 Display Only
 <p>FXC 110</p>	408210-1	This reliable electronic compass maintains your course based on magnetic heading reference. Automatic Self-Compensation, Ensures Relevant Magnetic Reference, Durable Construction	<ul style="list-style-type: none"> • SC 110 AP Kit • SC 110 AP Kit w/o FB • SC 110 Display Only
 <p>HHRP 11-12</p>	408340-1	Built with the finest components, Humminbird & reg pumps feature a full range of flow rates, pressure ratings and oil tank capacities. 1.0 cubic in per second, 12 VDC	<ul style="list-style-type: none"> • SC 110 AP Kit • SC 110 AP Kit w/o FB • SC 110 Display Only
 <p>HHRP 17-12</p>	408350-1	Built with the finest components, Humminbird & reg pumps feature a full range of flow rates, pressure ratings and oil tank capacities. 1.6 cubic in per second, 12 VDC	<ul style="list-style-type: none"> • SC 110 AP Kit • SC 110 AP Kit w/o FB • SC 110 Display Only




SCP Cable 30

720077-1

30 meter cable for the FB 30 and FXC 110 (included in Autopilot Kit SKU)

- SC 110 AP Kit
- SC 110 AP Kit w/o FB
- SC 110 Display Only
- FB 30
- FXC 110

RADAR	Item Number	Description	Compatible Units
 <p data-bbox="267 804 375 835">HB2124</p>	<p data-bbox="613 674 716 705">750013-1</p>	<p data-bbox="784 478 1065 1066">Humminbird CHIRP Radar features CHIRP pulse compression. It delivers superior RADAR imaging on both long and extremely short ranges. This translates to better situational awareness in low-visibility conditions and helps identify birds and floating obstacles for clues to where gamefish are located. Track weather and vessels with amazing definition.</p>	<ul style="list-style-type: none"> • All HELIX 7 G2N/G3N models • All HELIX 8 Series • All HELIX 9 Series • All HELIX 10 Series • All HELIX 12 Series • All ION Series • All ONIX Series • All SOLIX Series