




INSPECTION CERTIFICATE

| | | | | | | | | | | | | | | | |
|--|----------------------|----------------------|--|----------------|----------------------|---|----------------|----------------|------------------|--|-----------------|----------------|----------------|-----------------|------------|
| Steel Grade : | SUS 316L(SL) | Size 3.00 mm. | Certificate No. : ST2104300 | | Date : 22 April 2021 | | | | | | | | | | |
| Order No. : | SO-2012105 | | Customer Name : BODYSTEEL AND SILVER CO., LTD. Country : THAILAND | | | | | | | | | | | | |
| Description : | Stainless Steel Wire | | | | | | | | | | | | | | |
| CHEMICAL COMPOSITION (%) | | | | | | | | | | | | | | | |
| Inspection Items | | C | Si | Mn | P | S | Ni | Cr | Mo | Cu | N | Co | | | |
| Standard | | Max Min | 0.030 - | 1.00 - | 2.00 - | 0.045 - | 0.030 - | 14.00 10.00 | 18.00 16.00 | 3.00 2.00 | - - | 0.1000 - | - - | | |
| Heat No. | 193617 | | 0.016 | 0.52 | 1.35 | 0.030 | 0.001 | 10.16 | 17.30 | 2.10 | 0.27 | 0.0130 | - | | |
| Standard JIS G 4309 | | Diameter (mm) | Tensile Strength (kgf/mm2) | | Elongation % | HV (Vicker) | Length (mm) | | | | | | | | |
| Standard | | Max Min | 3.00+0.02 -0.02 | | 79 53 | - 30 | - - | | | | | | | | |
| No. | Diameter (mm) | Tensile (kgf/mm2) | Elongation % | HV (Vicker) | Weigh (kgs) | Packing Date | Appearance | No. | Diameter (mm) | Tensile (kgf/mm2) | Elongation % | HV (Vicker) | Weigh (kgs) | Packing Date | Appearance |
| 1 | 3.160 | 66.91 | 31.00 | - | 209.73 | - | OK. | | | | | | | | |
| | | | | TOTAL | 209.73 | | | | | | | | | | |
| Inspection by  | | | | | | Checked  | | | | Approved by  | | | | | |