



SECTION 1:

Identification of the substance/mixture and of the company/undertaking



1.1 PRODUCT IDENTIFIER

PRODUCT NAME:
Diva

PRODUCT CODE:
GPIO46

1.2 RELEVANT IDENTIFIES USES OF THE SUBSTANCE OR MIXTURE AND USES ADVISED AGAINST

USE OF SUBSTANCE / MIXTURE:

Light curable resin / UV gel. Only for professional use.

1.3 DETAILS OF THE SUPPLIER OF THE SAFETY DATA SHEET

COMPANY NAME:

By Ström AB
Tillgängligheten 3B
417 10 Göteborg
Sweden

EMAIL:

contact@bystrom.beauty

1.4 EMERGENCY TELEPHONE NUMBER

SECTION: 2

Hazards identification



2.1 CLASSIFICATION OF THE SUBSTANCE OR MIXTURE

CLASSIFICATION UNDER CLP:

Aquatic Chronic 3: H412; Eye Irrit. 2: H319;
Skin Irrit. 2: H315; Skin Sens. 1A: H317

MOST IMPORTANT ADVERSE EFFECTS:

Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. Harmful to aquatic life with long lasting effects.

2.2 LABEL ELEMENTS

LABEL ELEMENTS:

HAZARD STATEMENTS:


H315: Causes skin irritation.

H317: May cause an allergic skin reaction.

H319: Causes serious eye irritation.

H412: Harmful to aquatic life with long lasting effects.

HAZARD PICTOGRAMS:

GHS07: Exclamation mark 

SIGNAL WORDS:

Warning

PRECAUTIONARY STATEMENTS:

P261: Avoid breathing dust/fume/gas/mist/vapours/spray.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P302+P352: IF ON SKIN: Wash with plenty of water.

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P321: Specific treatment (see supplemental first aid instruction on this label)

P362+P364: Take off contaminated clothing and wash it before reuse.

2.3 OTHER HAZARDS

PBT:

This product is not identified as a PBT/vPvB substance.

SECTION: 3

Composition/information on ingredients



3.1 MIXTURES

HAZARDOUS INGREDIENTS:

EINECS	CAS	PBT / WEL	CLP Classification	Percent
POLYETHYLENGLYCOL20ODIMETHACRYLATE				
-	25852-47-5	-	-	5-25%
ALIPHATIC URETHANE ACRYLATE				
-	-	-	Skin Sens. 1A: H317	5-25%
ALIPHATIC URETHANE DIACRYLATE				
-	-	-	Skin Irrit. 2: H315; Eye Irrit. 2: H319	5-25%
ACRYLIC RESIN				
-	264888-21-5	-	Skin Sens. 1A: H317; Aquatic Chronic 4: H413	5-25%
TRICYCLODECANDIMETHANOLDIACRYLAT				
255-901-3	42594-17-2	-	Aquatic Chronic 2: H411; Skin Sens. 1B: H317	5-25%
ETHOXYLATED TRIMETHYLOLPROPANE TRIACRYLATE - REACH registered number(s): 01-2119489900-30-0004				
500-066-5	28961-43-5	-	Eye Irrit. 2: H319; Skin Sens. 1: H317	1-5%
PEG-4-DIMETHACRYLATE				
-	-	-	Skin Irrit. 2: H315; Eye Irrit. 2: H319	1-5%
HDMAP				
231-272-0	7473-98-5	-	Acute Tox. 4: H302	1-5%
TPO-L				
282-810-6	84434-11-7	-	Aquatic Chronic 3: H412	1-5%
PEG-DIACRYLATE				
-	26570-48-9	-	Skin Irrit. 2: H315; Eye Dam. 1: H318; Skin Sens. 1: H317	1-5%
METHYL TOLUENE-4-SULPHONATE				
201-283-5	80-48-8	-	Acute Tox. 4: H302; Skin Irrit. 2: H315; Eye Irrit. 2: H319; Skin Sens. 1B: H317	0.1-1%
2-ETHYLHEXYL ACRYLATE				
203-080-7	103-11-7	-	STOT SE 3: H335; Skin Irrit. 2: H315; Skin Sens. 1: H317	0.1-1%

SECTION: 4

First aid measures



4.1 DESCRIPTION OF FIRST AID MEASURES

SKIN CONTACT:

Remove all contaminated clothes and footwear immediately unless stuck to skin.

Wash immediately with plenty of soap and water.

EYE CONTACT:

Bathe the eye with running water for 15 minutes.
Consult a doctor.

INGESTION:

Wash out mouth with water.

Consult a doctor.

INHALATION:

Remove casualty from exposure ensuring one's own safety whilst doing so.

Consult a doctor.

4.2 MOST IMPORTANT SYMPTOMS AND EFFECTS, BOTH ACUTE AND DELAYED

SKIN CONTACT:

There may be irritation and redness at the site of contact.

EYE CONTACT:

There may be irritation and redness.

The eyes may water profusely.

INGESTION:

There may be soreness and redness of the mouth and throat.

INHALATION:

There may be irritation of the throat with a feeling of tightness in the chest.

Exposure may cause coughing or wheezing.

DELAYED / IMMEDIATE EFFECTS:

Immediate effects can be expected after short-term exposure.

4.3 INDICATION OF ANY IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENT NEEDED

IMMEDIATE / SPECIAL TREATMENT:

Eye bathing equipment should be available on the premises.

SECTION: 5

Fire-fighting measures



5.1 EXTINGUISHING MEDIA

EXTINGUISHING MEDIA:

Suitable extinguishing media for the surrounding fire should be used.

5.2 SPECIAL HAZARDS ARISING FROM THE SUBSTANCE OR MIXTURE

EXPOSURE HAZARDS:

In combustion emits toxic fumes.

5.3 ADVICE FOR FIRE-FIGHTERS

ADVICE FOR FIRE-FIGHTERS:

Wear self-contained breathing apparatus.

Wear protective clothing to prevent contact with skin and eyes.

SECTION: 6

Accidental release measures



6.1 PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT AND EMERGENCY PROCEDURES

PERSONAL PRECAUTIONS:

Refer to section 8 of SDS for personal protection details.

If outside do not approach from downwind.

If outside keep bystanders upwind and away from danger point.

Mark out the contaminated area with signs and prevent access to unauthorised personnel.

Do not create dust.

6.2 ENVIRONMENTAL PRECAUTIONS

ENVIRONMENTAL PRECAUTIONS:

Do not discharge into drains or rivers

6.3 METHODS AND MATERIAL FOR CONTAINMENT AND CLEANING UP

CLEAN-UP PROCEDURES:

Transfer to a closable, labelled salvage container for disposal by an appropriate method.

6.4 REFERENCE TO OTHER SECTIONS

REFERENCE TO OTHER SECTIONS:

Refer to section 8 of SDS.

SECTION: 7

Handling and storage



7.1 PRECAUTIONS FOR SAFE HANDLING

HANDLING REQUIREMENTS:

- Avoid direct contact with the substance.
- Ensure there is sufficient ventilation of the area.
- Do not handle in a confined space.
- Avoid the formation or spread of dust in the air.

7.2 CONDITIONS FOR SAFE STORAGE, INCLUDING ANY INCOMPATIBILITIES

STORAGE CONDITIONS:

Store in a cool, well ventilated area. Keep container tightly closed.

7.3 SPECIFIC END USE(S)

SPECIFIC END USE(S):

No data available.

SECTION: 8

Exposure controls/personal protection



8.1 CONTROL PARAMETERS

HAZARDOUS INGREDIENTS:

2-ETHYLHEXYL ACRYLATE

WORKPLACE EXPOSURE LIMITS:

RESPIRABLE DUST

STATE	8 HOUR TWA	15 MIN. STEL	8 HOUR TWA	15 MIN. STEL
UK	82 mg/m ³	82 mg/m ³	-	-

DNEL/PNEC VALUES

DNEL / PNEC

No data available.

8.2 EXPOSURE CONTROLS

ENGINEERING MEASURES:

Ensure there is sufficient ventilation of the area.

RESPIRATORY PROTECTION:

Self-contained breathing apparatus must be available in case of emergency.

Respiratory protective device with particle filter.

HAND PROTECTION:

Protective gloves.

EYE PROTECTION:

Safety glasses.

Ensure eye bath is to hand.

SKIN PROTECTION:

Protective clothing.

SECTION: 9

Physical and chemical properties

**9.1 INFORMATION ON BASIC PHYSICAL AND CHEMICAL PROPERTIES**

STATE: Paste	SOLUBILITY IN WATER: Insoluble
COLOUR: Red	ALSO SOLUBLE IN: Most organic solvents.
ODOUR: Characteristic odour	VISCOSITY: Viscous
EVAPORATION RATE: Negligible	RELATIVE DENSITY: > 1,0
OXIDISING: Non-oxidising (by EC criteria)	

9.2 OTHER INFORMATION

OTHER INFORMATION:
No data available.

SECTION: 10

Stability and reactivity

**10.1 REACTIVITY**

REACTIVITY:
Stable under recommended transport or storage conditions.

10.2 CHEMICAL STABILITY

CHEMICAL STABILITY:
Stable under normal conditions.

10.3 POSSIBILITY OF HAZARDOUS REACTIONS

HAZARDOUS REACTIONS:
Hazardous reactions will not occur under normal transport or storage conditions.
Decomposition may occur on exposure to conditions or materials listed below.

10.4 CONDITIONS TO AVOID

CONDITIONS TO AVOID:
Heat.

10.5 INCOMPATIBLE MATERIALS

MATERIALS TO AVOID:
Strong oxidising agents.
Strong acids.

10.6 HAZARDOUS DECOMPOSITION PRODUCTS

HAZ. DECOMP. PRODUCTS:
In combustion emits toxic fumes.

SECTION: II

Toxicological information

**II.1 INFORMATION ON TOXICOLOGICAL EFFECTS**

HAZARDOUS INGREDIENTS: 2-ETHYLHEXYL ACRYLATE

IPR	RAT	LD50	1 670	mg/kg
ORL	MUS	LD50	4 400	mg/kg
ORL	RAT	LD50	6 500	µl/kg

RELEVANT HAZARDS FOR PRODUCT:

HAZARD	ROUTE	BASIS
Skin corrosion/irritation	DRM	Hazardous: calculated
Serious eye damage/irritation	OPT	Hazardous: calculated
Respiratory/skin sensitisation	-	Hazardous: calculated

SYMPTOMS / ROUTES OF EXPOSURE

SKIN CONTACT:

There may be irritation and redness at the site of contact.

EYE CONTACT:

There may be irritation and redness. The eyes may water profusely.

INGESTION:

There may be soreness and redness of the mouth and throat.

INHALATION:

There may be irritation of the throat with a feeling of tightness in the chest.

Exposure may cause coughing or wheezing.

DELAYED / IMMEDIATE EFFECTS:

Immediate effects can be expected after short-term exposure.

SECTION: I2

Ecological information

**I2.1 TOXICITY**

ECOTOXICITY VALUES:

No data available.

I2.2 PERSISTENCE AND DEGRADABILITY

PERSISTENCE AND DEGRADABILITY:

Biodegradable.

I2.3 BIOACCUMULATIVE POTENTIAL

BIOACCUMULATIVE POTENTIAL:

No bioaccumulation potential.

I2.4 MOBILITY IN SOIL**I2.5 RESULTS OF PBT AND VPVB ASSESSMENT**

PBT IDENTIFICATION:

This product is not identified as a PBT/vPvB substance.

I2.6 OTHER ADVERSE EFFECTS

OTHER ADVERSE EFFECTS:

Negligible ecotoxicity.

SECTION: 13

Disposal considerations

**13.1 WASTE TREATMENT METHODS**

DISPOSAL OPERATIONS:

Transfer to a suitable container and arrange for collection by specialised disposal company.

DISPOSAL OF PACKAGING:

Dispose of as normal industrial waste.

NB:

The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

SECTION: 14

Transport information



TRANSPORT CLASS:

This product does not require a classification for transport.

SECTION: 15

Regulatory information

**15.1 SAFETY, HEALTH AND ENVIRONMENTAL REGULATIONS/LEGISLATION SPECIFIC FOR THE SUBSTANCE OR MIXTURE**

SPECIFIC REGULATIONS:

Not applicable.

15.2 CHEMICAL SAFETY ASSESSMENT

CHEMICAL SAFETY ASSESSMENT:

A chemical safety assessment has not been carried out for the substance or the mixture by the supplier.

SECTION: 16

Other information

**OTHER INFORMATION**

OTHER INFORMATION:

According to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

* indicates text in the SDS which has changed since the last revision.

PHRASES USED IN 5.2 AND 5.3:

H302: Harmful if swallowed.

H315: Causes skin irritation.

H317: May cause an allergic skin reaction.

H318: Causes serious eye damage.

H319: Causes serious eye irritation.

H335: May cause respiratory irritation.

H411: Toxic to aquatic life with long lasting effects.

H412: Harmful to aquatic life with long lasting effects.

H413: May cause long lasting harmful effects to aquatic life

LEGAL DISCLAIMER:

The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide.

This company shall not be held liable for any damage resulting from handling or from contact with the above product.