

Data Sheet

15XP-A Digital Multimeter



A compact digital multimeter for electronics and test applications

The 15XP-A is the right choice for electronics engineers, technicians and field service.

- Autoranging display for faster measurements
- TTL logic test for digital circuits
- Integrated tilt stand for easy bench use
- Diode test for component level troubleshooting
- Data Hold freezes display to “hold” measurement reading
- 750 V ac/1000 V dc—highest voltage rating in this size of meter

Specifications

Function	Range	Accuracy
Voltage		
DC Volts		
Ranges	200 mV, 2 V, 20 V, 200 V, 1000 V	± (0.5 % rdg + 1 dgt)
AC Volts (45 Hz to 500 Hz)		
Ranges	200 mV (45 Hz to 100 Hz) 2 V, 20 V, 200 V, 750 V	± (1.5 % rdg + 5 dgts) ± (1.5 % rdg + 5 dgts)
Resolution	100 μ V	
Input Impedance	400 mV: > 100 M Ω ; 4 V: 10 M Ω ; 40 V to 1000 V: 9.1 M Ω	
Overload Protection	1000 V dc or 750 V ac rms	
Current		
DC Current		
Ranges	200 μ A, 2000 μ A, 20 mA, 200 mA 2 A	± (1.0 % rdg + 2 dgt) ± (2.0 % rdg + 3 dgts)
AC Current (45 Hz to 500 Hz)		
Ranges	200 μ A, 2000 μ A, 20 mA, 200 mA 2 A	± (1.5 % rdg + 5 dgts) ± (2.5 % rdg + 5 dgts)
Resolution	0.1 μ A	
Input Protection	2 A/1000 V fast blow ceramic fuse 6.3 mm x 32 mm on A input	
Burden Voltage	500 mV max. (2 V max. on 2 mA, 200 mA ranges)	
Resistance		
	200 Ω , 2 k Ω , 20 k Ω , 200 k Ω , 2 M Ω 2000 M Ω	± (1.0 % rdg + 4 dgts) ± {5.0 % (rdg -10 dgts) + 20 dgt}
Resolution	100 m Ω	
Open Circuit Voltage	-0.45 V dc typical, (-1.2 V dc on 200 Ω range)	
Overload Protection	1000 V dc or 750 V ac rms	
Continuity		
Audible Indication	Less than 25 Ω	
Response Time	100 ms	
Overload Protection	1000 V dc or 750 V ac rms	
Diode Test		
Test Current	1.2 mA (approximate)	± (1.5 % rdg + 3 dgts)
Resolution	1 mV	
Open Circuit Voltage	3.0 dc typical	
Overload Protection	1000 V dc or 750 V ac rms	



Specifications *cont.*

Function	Range	Accuracy
Logic Test	TTL	
Thresholds Logic 1 (Hi)	2.8 V ± 0.8 V	
Thresholds Logic 0 (Lo)	0.8 V ± 0.5 V	
Test Voltage	TTL 5 VDC	
Frequency Range	20 MHz	
Pulse Width	25 ns min	
Duty Cycle Limits	> 30 % and < 70 %	
Indication	40 ms beep at Logic 0 (Lo)	
Overload Protection	1000 VDC or 750 VAC rms	
Non-Contact Voltage Indicator		
Sense voltage 70 V to 600 V ac (50 Hz to 60 Hz) beeper chirps and big bright red LED comes on, works on all ranges		

General Specifications

Display	3-1/2 digit liquid crystal display (LCD) with a maximum reading of 1999
Polarity	Automatic, positive implied, negative polarity indication
Overrange	(OL) or (-OL) is displayed
Zero	Automatic
Low Battery Indication	The " " is displayed when the battery voltage drops below the operating level
Auto Power Off	Approx. 10 minutes
Measurement Rate	2 times per second, nominal
Operating Environment	0 °C to 50 °C at < 70 % R.H.
Storage Temperature	-20 °C to 60 °C, 0 to 80 % R.H. with battery removed from meter
Accuracy	Stated accuracy at 23 °C ± 5 °C, < 75 % relative humidity
Temperature Coefficient	0.1 x (specified accuracy) per °C (0 °C to 18 °C, 28 °C to 50 °C)
Altitude	2000 m
Power	Single standard 9 volt battery, NEDA 1604, JIS 006P, IEC 6F22
Battery Life	200 hours typical with carbon-zinc
Dimensions (H x W x D)	155 mm x 72 mm x 32 mm
Weight	Approx. 210 g including battery
Warranty	One-year

No waiting.

No shipping charges.



No hassle warranty

Our commitment to high-quality products and customer service is demonstrated by our industry exclusive "No Hassle" warranty. In the unlikely event that a Amprobe test tool requires warranty service, any of our local dealers are authorized to replace it, on the spot.

(note: €500 MSLP limit)

Included Accessories

Pair of test leads (TL245), fuse 2 A/ 1000 V (P/N FP200), 9 V battery (installed), Magne-Grip™ Holster with magnetic hanging strap (H2-XR) and users manual.

Optional Accessories

VC30 Carrying Case
DL243C Test Lead Kit



Amprobe® Test Tools
website: www.Amprobe.com
email: info@amprobe.com
6920 Seaway Blvd.
Everett, WA 98203
tel: 877-AMPROBE

Beha-Amprobe GmbH
In den Engematten 14
79286 Glottertal, Germany
www.Amprobe.eu
info@amprobe.eu

©2006 Amprobe Test Tools. All rights reserved.
Printed in U.S.A.
12/2006 Pub_ID 11302-eng