

WALLBOX FOR ELECTRIC VEHICLE CHARGING

AWB1P32AT2 TYPE 2 32A 1-Phase -2, 3 to 7,4 KW Capacity



SPECIFICATIONS:

	AWB1P32AT1/ AWB1P32AT2	AWB3P32AT2	AWB1P32AT2NC	AWB3P32AT2NC
AC power:	1P+N+PE	3P+N+PE	1P+N+PE	3P+N+PE
Power supply Voltage:	AC230~±10%	AC400~±10%	AC230~±10%	AC400~±10%
Rated current:	10-32A	10-32A	10-32A	10-32A
Frequency:	50-60Hz	50-60Hz	50-60Hz	50-60Hz
Cable length:	5m	5m		
Sockets/plugs:	type1/type2	type2	type2	type2
Weight:	4.9kg	5.9kg	2.8kg	3.0kg
IP grade:	IP55/44	IP55/44	IP55/44	IP55/44
Working temperature:	-40°C ~ 45°C	-40°C ~ 45°C	-40°C ~ 45°C	-40°C ~ 45°C
Cooling way:	natural cooling	natural cooling	natural cooling	natural cooling
RCCB:	Type B	Type B	Type B	Type B

DISTRIBUTED BY:

BLP EV SYSTEMS APS - EDITHS ALLÉ 8, 5250 ODENSE SV, DENMARK