

CHARACTERISTICS

- \cdot Glove with double latex coating and tricot cuff
- \cdot Nylon liner (15 gauge) and a "terry" acrylic lining (10 gauge)
- Extremely supple glove with good fingertip sensitivity and seamless liner for optimal comfort
- The combination of the smooth latex coating and the latex "Sandy Finish" on the palm and fingers offers superior grip under wet and dry conditions
- $\boldsymbol{\cdot}$ The full double latex coating makes the glove liquid tight
- The warm acrylic lining makes the glove excellently suited for activities in cold environments
- $\boldsymbol{\cdot}$ The fully coated thumb makes the glove even more durable
- Antibacterial and antiviral treatment with the Premium SilverClear®.
 SilverClear® is an extremely effective antimicrobial, antibacterial and odour-resistant solution to treat e.g. gloves
- Their dark colour makes these gloves excellently suitable for use in environments with a certain level of contamination
- · Approved for processing dry foodstuffs
- Free from harmful substances in accordance with OEKO-TEX® Standard 100

Article number: 1.51.870.00

SUITABLE FOR ACTIVITIES IN E.G.

- · Building and construction
- · Cold-storage facilities
- · Wet working conditions
- · Maintenance of public works
- · Transport & logistics
- · Civil and hydraulic engineering
- · Agriculture
- \cdot Food processing

COLOUR

Black/blue

SIZES

7/S to 11/XXL incl.

PACKAGING

- · 1 pair per polybag
- · 12 pairs per bundle
- · 72 pairs per outer box











EN ISO 21420:2020



PRODUCT INFORMATION

SIZE	ARTICLE NO.	EAN CODE 1 PAIR (POLYBAG)	EAN CODE 12 PAIRS (BUNDLE)	EAN CODE 144 PAIRS (OUTER BOX)
7/S	1.51.870.07	8718249066863	8718249066870	8718249066887
8/M	1.51.870.08	8718249066894	8718249066900	8718249066917
9/L	1.51.870.09	8718249066924	8718249066931	8718249066948
10/XL	1.51.870.10	8718249066955	8718249066962	8718249066979
11/XXL	1.51.870.11	8718249066986	8718249066993	8718249067006

COLOUR BINDING/OVERLOCKING

Sizes	7/S	8/M	9/L	10/XL	11/XXL
Colour binding/overlocking	yellow	green	blue	grey	black

CLARIFICATION OF PICTOGRAMS

EN388:2016



3231X

EN511:2006



EN407:2004



EN388:2016 Protection against mechanical hazards



- B = Cut resistance (0-5)
- C = Tear resistance (0-4)
- D = Puncture resistance (0-4)
- E = Cut resistance (in accordance with EN ISO 13977 (A to F)
- F = Impact resistance (optional) (P = Passed)

EN511:2006 Protection against cold



abcdef

- A = Radiative cooling (0-4)
- B = Contact cold (0-4)
- C = Watertightness (0-1)

EN407:2004



A = Flammability (0-4)

Heat resistance

- B = Contact heat (0-4)
- C = Convection heat (0-4)
- D = Radiation heat (0-4)
- E = Small droplets of molten metal (0-4)
- F = Large quantities of molten metal (0-4)

Note: X = untested or not applicable

STORAGE CONDITIONS

The gloves should be kept in a clean, cool and dry place and not kept compressed in their original packaging. Do not expose the gloves to direct sunlight. Make sure that the packaging and the gloves are not damaged during shipping.

TESTING INSTITUTE

CTC (Notified Body no. 0075), 4 Rue Hermann Frenkel 69367 Lyon, Cedex 07, France.

DECLARATION OF CONFORMITY

For a copy of the declaration of conformity, we refer you to the following link: www.oxxa-safety.com/doc

YOUR SUPPLIER:

RELATED PRODUCTS



X-PRO-DRY Art. no. 1.51.30<u>0.00</u>