

Safety data sheet

Page: 1/13

BASF 3D Printing Safety data sheet according to UN GHS 4th rev.

Date / Revised: 22.12.2022 Version: 2.1

Product: Ultrafuse® 17-4 PH metal filament

(ID no. 11134863/SDS_GEN_00/EN)

Date of print 09.01.2023

1. Identification

Product identifier

Ultrafuse® 17-4 PH metal filament

Recommended use: 3D Printing

Details of the supplier of the safety data sheet

Company:
BASF 3D Printing Solutions B.V.
Eerste Bokslootweg 17
7821 AT Emmen, Netherlands

Telephone: + 31 591 820 389

E-mail address: sales@basf-3dps.com

Emergency telephone number

International emergency number: Telephone: +49 180 2273-112

2. Hazards Identification

Classification of the substance or mixture

According to UN GHS criteria

Aquatic Chronic 3

For the classifications not written out in full in this section the full text can be found in section 16.

Label elements

Date / Revised: 22.12.2022 Version: 2.1

Product: Ultrafuse® 17-4 PH metal filament

(ID no. 11134863/SDS_GEN_00/EN)

Date of print 09.01.2023

Globally Harmonized System (GHS)

Hazard Statement:

H412 Harmful to aquatic life with long lasting effects.

Precautionary Statements (Prevention):

P273 Avoid release to the environment.

Precautionary Statements (Disposal):

P501 Dispose of contents and container to hazardous or special waste

collection point.

Labeling of special preparations (GHS):

May produce an allergic reaction. Contains: Nickel, Cobalt

Other hazards

According to UN GHS criteria

If applicable information is provided in this section on other hazards which do not result in classification but which may contribute to the overall hazards of the substance or mixture.

Upon thermal and/or chemical treatment the product can release hazardous substances.

Upon mechanical treatment like e.g. cutting, grinding and/or polishing the product can release hazardous substances.

Fine dust produced by abrasion can form explosive mixtures with air.

3. Composition/Information on Ingredients

Substances

Not applicable

Mixtures

Chemical nature

polymer blend based on: Alloy, metal powder encapsulated, in a polymer matrix

<u>Hazardous ingredients (GHS)</u> According to UN GHS criteria

Nickel

Content (W/W): >= 3 % - < 5 % Skin Sens. 1 CAS Number: 7440-02-0 Carc. 2 EC-Number: 231-111-4 STOT RE 1

H317, H351, H372

Date / Revised: 22.12.2022 Version: 2.1

Product: Ultrafuse® 17-4 PH metal filament

(ID no. 11134863/SDS_GEN_00/EN)

Date of print 09.01.2023

Cobalt

Content (W/W): > 0 % - < 0,1 % Acute Tox. 4 (oral) CAS Number: 7440-48-4 Resp. Sens. 1 EC-Number: 231-158-0 Skin Sens. 1

Carc. 1B (by inhalation)

Muta. 2

Repr. 1B (fertility) Aquatic Chronic 4 Repr. 2 (unborn child)

H302, H334, H317, H341, H350, H360, H413

Ethylenebis(oxyethylene) bis[3-(5-tert-butyl-4-hydroxy-m-tolyl)propionate]

Content (W/W): > 0 % - < 0,1 % Aquatic Chronic 1 CAS Number: 36443-68-2 M-factor chronic: 10

EC-Number: 253-039-2 H410

For the classifications not written out in full in this section the full text can be found in section 16.

4. First-Aid Measures

Description of first aid measures

Remove contaminated clothing.

If inhaled:

Remove the affected individual into fresh air and keep the person calm. If symptoms persist, seek medical advice.

On skin contact:

Wash thoroughly with soap and water If irritation develops, seek medical attention. Burns caused by molten material require hospital treatment.

On contact with eyes:

Wash affected eyes for at least 15 minutes under running water with eyelids held open. If irritation develops, seek medical attention.

On ingestion:

Rinse mouth and then drink 200-300 ml of water. Seek medical attention.

Most important symptoms and effects, both acute and delayed

Symptoms: (Further) symptoms and / or effects are not known so far

Hazards: No hazard is expected under intended use and appropriate handling.

Indication of any immediate medical attention and special treatment needed

Treatment: Treat according to symptoms (decontamination, vital functions), no known specific antidote.

Date / Revised: 22.12.2022 Version: 2.1

Product: Ultrafuse® 17-4 PH metal filament

(ID no. 11134863/SDS_GEN_00/EN)

Date of print 09.01.2023

5. Fire-Fighting Measures

Extinguishing media

Suitable extinguishing media:

water spray, foam, dry powder, carbon dioxide

Additional information:

Water spray for suppression (heat dissipation) of incipient fires as long as the product has not yet ignited.

Special hazards arising from the substance or mixture

Formaldehyde, carbon oxides

The substances/groups of substances mentioned can be released in case of fire.

Advice for fire-fighters

Special protective equipment:

Wear a self-contained breathing apparatus.

Further information:

The degree of risk is governed by the burning substance and the fire conditions. Dispose of fire debris and contaminated extinguishing water in accordance with official regulations.

6. Accidental Release Measures

Avoid the formation and build-up of dust - danger of dust explosion. Dust in sufficient concentration can result in an explosive mixture in air. Handle to minimize dusting and eliminate open flame and other sources of ignition.

Personal precautions, protective equipment and emergency procedures

Handle in accordance with good industrial hygiene and safety practice. Avoid dust formation.

Environmental precautions

Discharge into the environment must be avoided.

Methods and material for containment and cleaning up

For small amounts: Sweep/shovel up. For large amounts: Sweep/shovel up.

Dispose of absorbed material in accordance with regulations. Avoid raising dust.

7. Handling and Storage

Precautions for safe handling

Avoid inhalation of dusts/mists/vapours. Ensure adequate ventilation. Provide suitable exhaust ventilation at the drying process and in the area surrounding the melt outlet of processing machines. Keep away from sources of ignition - No smoking. Take precautionary measures against static discharges. Avoid the formation and deposition of dust. Upon mechanical load the product can release sensitizing substances.

Further information is given in the user guidelines for the product.

Protection against fire and explosion:

Date / Revised: 22.12.2022 Version: 2.1

Product: Ultrafuse® 17-4 PH metal filament

(ID no. 11134863/SDS_GEN_00/EN)

Date of print 09.01.2023

The product is not an oxidizer, not self-combustible and not explosive. Avoid dust formation. Accumulation of fine dust may entail the risk of a dust explosion in the presence of air.

Conditions for safe storage, including any incompatibilities

Segregate from acids.

Suitable materials for containers: High density polyethylene (HDPE), Low density polyethylene (LDPE), Paper/Fibreboard

Further information on storage conditions: Avoid deposition of dust. Avoid extreme heat.

Storage stability:

Protect against moisture.

Specific end use(s)

For the relevant identified use(s) listed in Section 1 the advice mentioned in this section 7 is to be observed.

8. Exposure Controls/Personal Protection

Control parameters

Components with occupational exposure limits

50-00-0: Formaldehyde

7439-89-6: Iron

7440-02-0: Nickel

7440-47-3: Chromium

7440-48-4: Cobalt

7440-50-8: Copper

7440-48-4: Cobalt

Exposure controls

Personal protective equipment

Respiratory protection:

Breathing protection if breathable aerosols/dust are formed. Wear respiratory protection if ventilation is inadequate. Particle filter with medium efficiency for solid and liquid particles (e.g. EN 143 or 149, Type P2 or FFP2)

Hand protection:

Use additional heat protection gloves when handling hot molten masses (EN 407), e.g. of textile or leather.

Eve protection:

Safety glasses with side-shields (frame goggles) (e.g. EN 166)

Body protection:

Body protection must be chosen depending on activity and possible exposure, e.g. apron, protecting boots, chemical-protection suit (according to EN 14605 in case of splashes or EN ISO 13982 in case of dust).

General safety and hygiene measures

Date / Revised: 22.12.2022 Version: 2.1

Product: Ultrafuse® 17-4 PH metal filament

(ID no. 11134863/SDS_GEN_00/EN)

Date of print 09.01.2023

Wearing of closed work clothing is recommended. Ensure adequate ventilation. No eating, drinking, smoking or tobacco use at the place of work. Store work clothing separately. Hands and/or face should be washed before breaks and at the end of the shift.

9. Physical and Chemical Properties

Information on basic physical and chemical properties

Form: filament Colour: grev Odour: odourless

Odour threshold:

not applicable, odour not perceivable

pH value:

not applicable, substance/mixture is

non-soluble (in water)

Melting point:

not determined

Boiling point:

not applicable

Flash point:

Flammability:

not applicable, the product is a solid

Evaporation rate:

The product is a non-volatile solid. Not a flammable solid according to UN transport regulations division 4.1

and GHS chapter 2.7.

Lower explosion limit:

For solids not relevant for classification and labelling.

Upper explosion limit:

For solids not relevant for classification and labelling.

Ignition temperature:

not applicable

Vapour pressure:

not determined

Density:

(20 °C)

not determined

Relative vapour density (air):

The product is a non-volatile solid.

Solubility in water: insoluble

Partitioning coefficient n-octanol/water (log Kow):

not applicable for mixtures

Self ignition: not self-igniting

Thermal decomposition: No decomposition if stored and handled as prescribed/indicated.

Prolonged thermal loading can result in products of degradation being

aiven off.

Viscosity, kinematic:

not applicable, the product is a solid

Date / Revised: 22.12.2022 Version: 2.1

Product: Ultrafuse® 17-4 PH metal filament

(ID no. 11134863/SDS_GEN_00/EN)

Date of print 09.01.2023

Explosion hazard: Product is not explosive, however a

dust explosion could result from an

air / dust mixture.

Fire promoting properties: not fire-propagating

Other information

Self heating ability: It is not a substance capable of

spontaneous heating.

Bulk density:

not determined

Hygroscopy: Non-hygroscopic

Other Information:

If necessary, information on other physical and chemical parameters is indicated in this section.

10. Stability and Reactivity

Reactivity

No hazardous reactions if stored and handled as prescribed/indicated.

Corrosion to metals: No corrosive effect on metal.

Reactions with Reaction with: air

water/air:

Flammable gases: no Toxic gases: no Corrosive gases: no Smoke or fog: no Peroxides: no

Reaction with: water
Flammable gases: no
Toxic gases: no
Corrosive gases: no
Smoke or fog: no
Peroxides: no

Formation of Remarks: Forms no flammable gases in the

flammable gases: presence of water.

Chemical stability

The product is stable if stored and handled as prescribed/indicated.

Possibility of hazardous reactions

Strong exothermic reaction with acids. May decompose violently. The product is stable if stored and handled as prescribed/indicated.

Conditions to avoid

Avoid all sources of ignition: heat, sparks, open flame. Avoid dust formation.

Incompatible materials

Date / Revised: 22.12.2022 Version: 2.1

Product: Ultrafuse® 17-4 PH metal filament

(ID no. 11134863/SDS_GEN_00/EN)

Date of print 09.01.2023

Substances to avoid:

oxidizing agents, inorganic acids, plastics containing halogenated flame retardants

Hazardous decomposition products

Possible thermal decomposition products:

Formaldehyde, Carbon monoxide

At prolonged and/or strong thermal stressing above the decomposition temperature dangerous decomposition products can be formed.

11. Toxicological Information

Information on toxicological effects

Acute toxicity

Assessment of acute toxicity:

Based on available data, the classification criteria are not met. Contact with molten product may cause thermal burns.

Information on: Cobalt

Assessment of acute toxicity:

Of moderate toxicity after single ingestion. The inhalation of dusts represents a severe acute hazard. Virtually nontoxic after a single skin contact.

Irritation

Assessment of irritating effects:

May cause mechanical irritation.

Respiratory/Skin sensitization

Assessment of sensitization:

Based on available data, the classification criteria are not met. Study not necessary due to exposure considerations.

Information on: Cobalt Assessment of sensitization:

May cause sensitization by inhalation. May cause sensitization by skin contact.

Information on: Nickel Assessment of sensitization:

Sensitization after skin contact possible.

Germ cell mutagenicity

Assessment of mutagenicity:

Based on available data, the classification criteria are not met.

Carcinogenicity

Assessment of carcinogenicity:

Date / Revised: 22.12.2022 Version: 2.1

Product: Ultrafuse® 17-4 PH metal filament

(ID no. 11134863/SDS_GEN_00/EN)

Date of print 09.01.2023

Based on available data, the classification criteria are not met. Study not necessary due to exposure considerations.

Information on: Nickel

Assessment of carcinogenicity:

The results of various animal studies gave no indication of a carcinogenic effect. IARC (International Agency for Research on Cancer) has classified this substance as group 2B (The agent is possibly carcinogenic to humans).

Information on: Cobalt

Assessment of carcinogenicity:

In long-term studies in rats and mice in which the substance was given by inhalation, a carcinogenic effect was observed. IARC (International Agency for Research on Cancer) has classified this substance as group 2B (The agent is possibly carcinogenic to humans).

Reproductive toxicity

Assessment of reproduction toxicity:

Based on available data, the classification criteria are not met.

Information on: Cobalt

Assessment of reproduction toxicity:

The results of animal studies suggest a fertility impairing effect.

Developmental toxicity

Assessment of teratogenicity:

Based on available data, the classification criteria are not met.

Information on: Cobalt

Assessment of teratogenicity:

Indications of possible developmental toxicity/teratogenicity were seen in animal studies. The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

.....

Specific target organ toxicity (single exposure)

Remarks: Based on available data, the classification criteria are not met.

Repeated dose toxicity and Specific target organ toxicity (repeated exposure)

Assessment of repeated dose toxicity:

Based on our experience and the information available, no adverse health effects are expected if handled as recommended with suitable precautions for designated uses.

Information on: Nickel

Assessment of repeated dose toxicity:

The substance may cause damage to the lung after repeated inhalation.

Aspiration hazard

Date / Revised: 22.12.2022 Version: 2.1

Product: Ultrafuse® 17-4 PH metal filament

(ID no. 11134863/SDS_GEN_00/EN)

Date of print 09.01.2023

not applicable

12. Ecological Information

Toxicity

Assessment of aquatic toxicity:

Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment. The product has not been tested. The statement has been derived from the properties of the individual components.

Information on: Ethylenebis(oxyethylene) bis[3-(5-tert-butyl-4-hydroxy-m-tolyl)propionate] Assessment of aquatic toxicity:

There is a high probability that the product is not acutely harmful to aquatic organisms. The inhibition of the degradation activity of activated sludge is not anticipated when introduced to biological treatment plants in appropriate low concentrations.

. . . .

Persistence and degradability

Assessment biodegradation and elimination (H2O):

The product is not very soluble in water and can thus be removed from water mechanically in suitable effluent treatment plants.

Bioaccumulative potential

Assessment bioaccumulation potential:

The product has not been tested.

Bioaccumulation potential:

The product has not been tested. Because of the product's consistency and low water solubility, bioavailability is improbable.

Mobility in soil

Assessment transport between environmental compartments: Adsorption in soil: Adsorption to solid soil phase is possible.

Results of PBT and vPvB assessment

According to Annex XIII of Regulation (EC) No.1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH): The product does not contain a substance fulfilling the PBT (persistent/bioaccumulative/toxic) criteria.

Other adverse effects

The product does not contain substances that are listed in Regulation (EC) 1005/2009 on substances that deplete the ozone layer.

Additional information

Add. remarks environm. fate & pathway:

Date / Revised: 22.12.2022 Version: 2.1

Product: Ultrafuse® 17-4 PH metal filament

(ID no. 11134863/SDS_GEN_00/EN)

Date of print 09.01.2023

The product has not been tested. The statements on environmental fate and pathway have been derived from the properties of the individual components.

Other ecotoxicological advice:

The product has not been tested. The statements on ecotoxicology have been derived from the properties of the individual components.

13. Disposal Considerations

Waste treatment methods

Dispose of in accordance with national, state and local regulations.

Contact specialized companies about recycling.

Contaminated packaging:

Dispose of in accordance with national, state and local regulations.

Contaminated packaging should be emptied as far as possible and disposed of in the same manner as the substance/product.

14. Transport Information

Land transport

ADR

Not classified as a dangerous good under transport regulations

UN number or ID number: Not applicable Not applicable UN proper shipping name: Not applicable Transport hazard class(es): Packing group: Not applicable Environmental hazards: Not applicable None known Special precautions for

user

RID

Not classified as a dangerous good under transport regulations

UN number or ID number: Not applicable Not applicable UN proper shipping name: Not applicable Transport hazard class(es): Packing group: Not applicable Environmental hazards:

Special precautions for

user

Not applicable None known

Inland waterway transport

ADN

Not classified as a dangerous good under transport regulations

UN number or ID number: Not applicable UN proper shipping name: Not applicable

Date / Revised: 22.12.2022 Version: 2.1

Product: Ultrafuse® 17-4 PH metal filament

(ID no. 11134863/SDS_GEN_00/EN)

Date of print 09.01.2023

Transport hazard class(es): Not applicable Packing group: Not applicable Environmental hazards: Not applicable Special precautions for None known

user:

Transport in inland waterway vessel

Not evaluated

Sea transport

IMDG

Not classified as a dangerous good under transport regulations

UN number or ID number:
UN proper shipping name:
Transport hazard class(es):
Packing group:
Environmental hazards:
Special precautions for

Not applicable
Not applicable
Not applicable
Not applicable
Not applicable

user

Air transport

IATA/ICAO

Not classified as a dangerous good under transport regulations

UN number or ID number
UN proper shipping name:
Transport hazard class(es):
Packing group:
Environmental hazards:
Special precautions for

Not applicable

user

Maritime transport in bulk according to IMO instruments

Maritime transport in bulk is not intended.

15. Regulatory Information

Safety, health and environmental regulations/legislation specific for the substance or mixture

If other regulatory information applies that is not already provided elsewhere in this safety data sheet, then it is described in this subsection.

Date / Revised: 22.12.2022 Version: 2.1

Product: Ultrafuse® 17-4 PH metal filament

(ID no. 11134863/SDS_GEN_00/EN)

Date of print 09.01.2023

16. Other Information

Any other intended applications should be discussed with the manufacturer.

Full text of classifications, hazard symbols and hazard statements, if mentioned in section 2 or 3:

Aquatic Chronic Hazardous to the aquatic environment - chronic

Skin Sens. Skin sensitization Carc. Carcinogenicity

STOT RE Specific target organ toxicity — repeated exposure

Acute Tox. Acute toxicity

Resp. Sens. Respiratory sensitization
Muta. Germ cell mutagenicity
Repr. Reproductive toxicity

H317 May cause an allergic skin reaction.
H351 Suspected of causing cancer.

H372 Causes damage to organs through prolonged or repeated exposure.

H302 Harmful if swallowed.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H341 Suspected of causing genetic defects. H350 May cause cancer by inhalation.

H360 May damage fertility. Suspected of damaging the unborn child.

H413 May cause long lasting harmful effects to aquatic life.
H410 Very toxic to aquatic life with long lasting effects.

The data contained in this safety data sheet are based on our current knowledge and experience and describe the product only with regard to safety requirements. This safety data sheet is neither a Certificate of Analysis (CoA) nor technical data sheet and shall not be mistaken for a specification agreement. Identified uses in this safety data sheet do neither represent an agreement on the corresponding contractual quality of the substance/mixture nor a contractually designated use. It is the responsibility of the recipient of the product to ensure any proprietary rights and existing laws and legislation are observed.

Vertical lines in the left hand margin indicate an amendment from the previous version.