

iStorage®

DATASHUR® PRO²



The ultimate in secure USB flash drive technology

KEY FEATURES

Our highest capacity

PIN authenticated, hardware encrypted USB flash drive with capacities up to 512GB.

OS & platform independent

With no software required. Cross-platform compatible with: MS Windows, macOS, Linux, Android, Chrome, Thin Clients, Zero Clients, Embedded Systems, Citrix, VMware, DVR's, Medical Equipment, Printers, Scanners, CCTV. In fact, it will work on any device with a USB port!

Government validations

FIPS 140-2 Level 3, NCSC CPA, NLNCSA BSPA & NATO Restricted validations (pending Q3 2019)

FIPS 140-2 Level 3 compliant Tamper proof & evident design

All critical components are covered by a layer of super tough epoxy resin, which is virtually impossible to remove without causing permanent damage to the critical components. If breached, the tamper evident design of the datAshur PRO² will provide visible evidence that tampering has occurred.

Superspeed USB 3.2 (Generation 1x1)

Backwards compatible with older USB ports.

Inactivity Auto-lock

Configurable to lock after a predetermined period of inactivity. datAshur PRO² also automatically locks when unplugged from the host device or when power to the USB port is turned off.

Configure as Removeable Media or Fixed Disk

Depending on the OS environment and application scenario the datAshur PRO² can be configured as either Removeable Media or Fixed Disk to meet the User's needs.

Read only (write protect) - Dual Mode

Both Admin and User can configure the datAshur PRO² as a read only (write protect) device. If configured by the Admin, the device cannot be modified or disabled by the User allowing the Admin to pre-provision a device with pre-loaded content as read-only for the User.

User PIN enrolment

Admin can set a restriction policy for the User PIN. This includes setting the minimum length of the PIN, as well as requiring the input of one or more 'Special Character' if needed.

The 'Special Character' functions as 'SHIFT () + digit'

On-device Crypto-chip

Offering 100% real-time military grade AES-XTS 256-bit Hardware Encryption with FIPS PUB 197 validated encryption algorithm

Uniquely incorporates Common Criteria EAL4+ ready secure microprocessor

Offers ultimate security against hackers, detecting and responding to tampering with features such as:

- *Dedicated hardware for protection against SPA/DPA/SEMA, DEMA attacks*
- *Advanced protection against physical attacks, including Active Shield, Enhance Protection Object, CStack checker, Slope Detector and Parity Errors*
- *Environmental Protection Systems protecting against voltage monitor, frequency monitor, temperature monitor and light protection*
- *Secure Memory Management/Access Protection*

IP58 certified

Dust and water resistant. Includes hard anodized and ruggedised extruded aluminium protective sleeve.

Polymer coated, wear resistant on-board alphanumeric keypad

The datAshur PRO² is authenticated (unlocked) and all functions are performed using the onboard keypad and with zero host involvement, the device is not vulnerable to key-loggers and/or brute force attacks.

The datAshur PRO² keypad is coated with a layer of wear resistant polymer for added protection.

User & Admin PIN authenticated

Supports independent User and Admin PINs

Bootable feature

Install an OS on the datAshur PRO² and boot directly from it.

Lock override mode

Ideal in certain cases where the datAshur PRO² needs to remain unlocked through USB port re-enumeration, such as during a reboot process or passing the device through a virtual machine.

One-time User recovery PIN

Admin configurable, extremely useful in situations where a User has forgotten their PIN, allowing the User to unlock the device and set a new User PIN.

Self-destruct feature

Pre-program the datAshur PRO² with a self-destruct PIN, once entered, the encrypted encryption key and all PINs are deleted and all data is rendered as lost forever.

Whitelisting on networks

Configured with a unique VID/PID and internal/external serial number with barcode, allowing easy integration into standard end-point management software (white-listing), to meet internal corporate requirements.

Immune to Bad USB

Both the USB Cryptochip and Secure Microprocessor incorporate digitally-signed flash lock mechanisms making the datAshur PRO² immune to Bad USB.

Brute force hack defence mechanism

If the User PIN is entered incorrectly 10 consecutive times, the User PIN will be deleted and the drive can only be accessed by entering the Admin PIN in order to reset the User PIN. (Admin can change this from the default 10 incorrect PIN entries, to 1-9, for the User only)

If the Admin PIN is entered incorrectly 10 consecutive times, all PINs and the encrypted encryption key will be lost forever.

Device reset feature

Deletes the encrypted encryption key, all PINs and renders all data as lost forever. The device can then be redeployed which randomly generates a new encrypted encryption key, a process that can be repeated as many times as required.

Customisation services available

Offering an in-house PIN configuration and laser-etching service whereby the datAshur PRO² sleeve or side of the device can be customised with your name, company name and/or logo, web/email address, phone number.



Technical specifications

Hardware	Hardware encrypted USB flash drive	
Interface	USB 3.2 (Gen 1x1) SuperSpeed - backwards compatible 1/2	
Data transfer rates ²	Read: 130.3 MB/s Write: 116.5 MB/s	
Battery	3.7V Li-Polymer rechargeable battery	
Dimension - H/W/D	87.40mm / 19.40 mm / 13.40mm	
Weight	Without sleeve: approx. 28 grams With sleeve: approx. 37 grams	
Compatibility	MS Windows, macOS, Linux, Chrome, Android, Thin Clients, Zero Clients, Embedded Systems, Citrix and VMware	
Hardware data encryption	AES-XTS 256-bit full disk hardware encryption	
Certifications	FIPS 140-2 Level 3, NCSC CPA, NLNCSA BSPA & NATO Restricted validation (Pending Q3)	
Approvals		
Capacities ¹	4 / 8 / 16 / 32 / 64 / 128 / 256 / 512GB	
Ordering information	IS-FL-DP2-256-XX	XX = Capacity
Warranty	3 year warranty with free lifetime technical support	



¹ - Some of the listed capacity on a flash storage device is used for formatting and other functions and is thus not available for data storage. As such, the actual available capacity for data storage is less than what is listed on the products.

² - Speed may vary due to host hardware, software and usage.



Designed and Developed in the UK
Assembled in China

