

STUMPJUMPER EVO COMP ALLOY 29

3.599,00 €



SATIN / TI PAB / BLACK

Das Stumpjumper EVO Comp Alloy 29 lebt für die anspruchsvollen Trails. Die lang- und tiefgezogene Geometrie des Bikes verleiht ihm eine außergewöhnliche Vorderrad-Traktion und bittet förmlich darum, jedes Feature auf dem Trail mitzunehmen. 29 Zoll Räder überwinden Felsen und Wurzeln mit Leichtigkeit und halten das Momentum durch raues Gelände.

STUMPJUMPER EVO COMP ALLOY 29	S2	S3
Stack (mm)	619	623
Reach (mm)	445	475
Steuerrohrlänge (mm)	100	105
Steuerrohrwinkel (degrees)	63.5	63.5
Tretlagerhöhe (mm)	328	328
Tretlagerabsenkung (mm)	47	47
Nachlauf (mm)	138	138
Gabellänge, gesamt (mm)	560	560
Gabelversatz / Offset (mm)	44	44
Mitte Tretlager - Mitte V.-achse (mm)	781	813
Kettenstreben-Länge (mm)	443	443
Radstand (mm)	1220	1252
Oberrohrlänge horizontal (mm)	599	635
Überstandshöhe (mm)	754	770
Sitzrohrlänge (mm)	400	450
Sitzrohrwinkel (degrees)	76	75.6
Kurbellänge (mm)	165	165
Lenkerbreite (mm)	800	800
Vorbaulänge (mm)	45	45
Sattelbreite (mm)	143	143
Länge Sattelstütze (mm)	438	478

SPECS	Technische Änderungen vorbehalten.
RAHMEN	M5 alloy frame, asymmetrical design, 29 style-specific EVO Trail Geometry, threaded BB, fully enclosed internal cable routing, 12x148mm dropouts, sealed cartridge bearing pivots, replaceable derailleur hanger, 140mm of travel
DÄMPFER	FOX FLOAT DPX2 Performance, Rx Trail Tune, EVOL Air sleeve, 3-position adjustment, 210x50mm
GABEL	FOX FLOAT 36 Rhythm, GRIP damper, two position Sweep adjustment, 15x110mm QR axle, 44mm offset, 150mm of travel
VORBAU	Specialized Trail, 3D-forged alloy, 4-bolt, 6-degree rise
LENKER	Specialized, 7050 alloy, 6-degree upsweep, 8-degree backsweep, 27mm rise, 800mm width
LENKERGRIFFE	Deity, Knuckleduster, Black
BREMSE VORNE	SRAM Code R, 4-piston caliper, hydraulic disc, 200mm
BREMSE HINTEN	SRAM Code R, 4-piston caliper, hydraulic disc, 200mm
SCHALTWERK	SRAM NX Eagle, 12-speed
SCHALTHEBEL	SRAM NX Eagle, trigger, 12-speed
KASSETTE	SRAM NX Eagle, 12-speed, 11-50t
KETTE	SRAM NX Eagle, 12-speed
KURBELGARNITUR	SRAM NX Eagle, DUB, 165mm, 30T
KETTENBLÄTTER	Steel, 30T
INNENLAGER	SRAM DUB, threaded BB
FELGEN	Roval Traverse 29, hookless alloy, 30mm inner width, tubeless ready
VORDERRADNABE	Specialized, sealed cartridge bearings, 15x110mm spacing, 28h
HINTERRADNABE	Specialized, sealed cartridge bearings, 12x148mm thru-axle, 28h
SPEICHEN	DT Swiss Industry
VORDERREIFEN	Butcher, GRID TRAIL casing, GRIPTON® compound, 2Bliss Ready, 29x2.6"
HINTERREIFEN	Butcher, GRID TRAIL casing, GRIPTON® compound, 2Bliss Ready, 29x2.3"
SATTEL	Body Geometry Henge Comp, hollow Cr-Mo rails, 143mm
SATTELSTÜTZE	X-Fusion Manic, infinite adjustable, two-bolt head, bottom mount cable routing, remote SRL LE lever, 34.9mm, 150mm of travel

ART.-NR.	BESCHREIBUNG	FARBE	GRÖSSE
97520-5302	SJ COMP ALLOY EVO 29	SATIN / TI PAB / BLACK	S2
97520-5303			S3