

# Data Sheet

## BBBLOCKGFB1 GLOSS WHITE BLOCKOUT VINYL

### Removable Adhesive

BBBLOCKGFB1 is a 200my Dual-layer blackout vinyl. The Dual-layer engineering allows for 100% opaque applications where total blackout is required. The 135gsm DSPE Liner provides excellent dimensional stability for digital printing. This Vinyl accepts a variety of Solvent, Eco-Solvent, Latex, UV Curable common to wide format digital printing systems. Also works well with UV offset & Screen inks.

#### Applications

This product is recommended for Window Graphics and Retail Displays that require total light blackout without grey or black adhesives being visible on the backside when applied to glass. The 200my construction makes applications easy and quick.

#### Thickness

Film 200my  
Adhesive 20 to 25 my  
Liner 135gr  
(Thickness variance +/- 10%)

#### Dimensional Stability Temperature Ranges

Good  
Minimum application temperature +4,4°C  
Service temperature -40 °C to +82°C

#### Expected Exterior Life Removability

3 years (Unprinted)  
Removable up to 1 year under normal conditions

#### Adhesion

To glass 5 N/25mm to 9 N/25mm (FTM01)  
To standard test panels 5 N/25mm to 9 N/25mm (FTM01)

Individual values may vary. Test thoroughly before production.

#### Water Resistance Humidity Resistance Storage Stability

Good (Test if immersed)  
Good  
1-year shelf life when stored at 21°C and 50% relative humidity.

#### Product Code

BBBLOCKGFB1 1.37m x 30.48m  
BBBLOCKGFB1 1.52m x 30.48m

#### Recommendations

Completely evaporate inkjet solvents before application. Failure to do so may facilitate solvent penetration resulting in vinyl degradation.

