

Data Sheet

BB7920GF

BB7920GF - 300my CLEAR UV OVERLAMINATE

BB7920GF is a 300my flexible gloss clear polymeric overlamine offering, UV protection. This film is designed for use as a protective overlaminating film on the EXTREEM. Recommended for the powersport, graphic and decal markets. This product is formulated for exceptional clarity and durability.

Applications

BB7920GF is intended for use as the overlaminating film on EXTREEM 100my. This overlamine and vinyl combination is used for a variety of Quads, Snowmobiles, Motocross, Powersport Vehicles, Helmets and Carts. The adhesive system is formulated to adhere to most common solvent, eco-solvent, latex, thermal, UV, offset and screen inks. However, specific formulations must be tested before use. Some ink may contain excessive flow additives that could reduce adhesion of this product. Testing is always suggested before production. Specifically test applications to gas tanks.

Thickness

Film	300my
Adhesive	45my
Liner	80gr
(Thickness variance +/- 10%)	

Temperature Ranges

Minimum application temperature	+4,4°C
Service temperature	-40°C to +93°C.

Expected Exterior Exposure

5 Years under normal exposure conditions and proper care.

Adhesion

To stainless steel	11 N/25mm (FTM01)
--------------------	-------------------

Individual values may vary. Test thoroughly before production.

Surface Gloss

Minimum 80 when measured at 60° MD fresh.

Water Resistance

Excellent.

Humidity Resistance

Excellent.

Storage Stability

One year shelf life when stored at 21°C and 50% relative humidity.

Product Series

BB7920GF	1,37m x 25m
BB7920GF	1,52m x 25m

Recommendations

Completely evaporate inkjet solvents before application. Failure to do so may facilitate solvent penetration resulting in vinyl degradation. Always thoroughly test this product to confirm that it meets your requirements. Proper preparation of plastic surfaces requires cleaning with alcohol or acetone to remove contaminants before application. Failure to prepare the surface can cause premature failure of the graphic or decal.

The above recommendations for these products usage does not suggest or constitute a verbal or written guarantee or warranty by the manufacture or its dealers of this product. Individual purchasers or users shall be responsible for determining the materials suitability as well as its intended use and application