

# Data Sheet

## BB9200CLGF

### OPTICALLY CLEAR CAST OVERLAMINATING FILM

BB9200CLGF is a Optically Clear Cast Overlaminating Film with a pressure sensitive optically clear permanent solvent adhesive on a smooth frosted polyester liner. This glossy flexible vinyl affords protection to graphics from ultra violet radiation, moisture and abrasion.

**Applications** BB9200CLGF is recommended as an overlay on any kind of Cast Car Wrapping Vinyls. Cold laminating techniques are recommended when applying this film.

**Thickness**

Film	50my
Adhesive	25my
Liner	50gr

(Thickness variance +/- 10%)

**Dimensional Stability** Good

**Temperature Ranges**

Minimum application temperature	+4,4°C
Service temperature range	-40°C to +82°C.

**Expected Exterior Exposure** Under normal conditions, up to 5 years resistance can be expected.

**Adhesion**

To stainless steel	13 N/25mm (FTM01)
--------------------	-------------------

Individual values may vary. Test thoroughly before production.

**Surface Gloss**

>60  
Gloss Meter 60° viewing angle

**Storage Stability** One year shelf life when stored at 21°C and 50% relative humidity.

**Product Series**

BB9200CLGF	1,37m x 50m
BB9200CLGF	1,52m x 50m