

# Polymeric Calendered Print Film

This polymeric print film is an 80 micron (0.080mm), white, polymeric calendered vinyl film with a permanent, solvent-based pressure-sensitive adhesive. It is suitable for a wide range of applications, including fleet, interior décor, and general signage. The product has a performance life of 5 years, and is recommended for use on flat and slightly curved surfaces.

Item	Description
Thickness (Face Only)	80 Micron
Liner	170 g/m <sup>2</sup> Double Sided PE
Tensile Strength	1600g/10mm
Dimensional Stability	< 0.6mm
Shelf Life	1 Year (Dry conditions, Temperature < 35°C)
Service Temperature Range	-30°C to +85°C
Adhesive Colour	Pressure Sensitive - Clear & Grey Permanent
Application Surface	Flat and slightly curved surfaces
Minimum Application Temperature	8°C
Elongation	150%
Peel Adhesion	1250g/25mm (20 mins) 1750g/25mm (24 hrs)

## Available Finishes

- Gloss White with Clear Permanent Adhesive
- Gloss White with Grey Permanent Adhesive
- Gloss White with Grey Permanent Air Release Adhesive
- Matte Finishes are available as special order only

## Features and Benefits

- Extremely high white-point face film
- Heavy duty 170gsm double sided PE coated lay-flat liner gives superior stability for printing and finishing
- High quality face film offers excellent printability
- High dimensional stability
- Grey adhesive option offers superior hiding power
- Printable in most latex, solvent, eco-solvent and UV printers
- 5 year performance life

## Applications

- Vehicle graphics, display graphics, internal and external signage and window graphics
- Flat and slightly curved surfaces only

## Terms and Conditions

*All information published on this product bulletin is based on tests believed to be accurate and reliable and are subject to change. There may be minor lot to lot variation of performance data. The provider shall not be liable for injury, loss or damage, direct or consequential, arising from the sale or use of this product.*