

P 534

PORTABLE AIR CONDITIONER

Download photos and docs on qlima.com!



Product data sheet

Brand name		Qlima
Model		P 534
Sound power level ¹	dB	65

Refrigerant GWP ²	Refrigerant leakage contributes to climate change. Refrigerant with lower global warming potential (GWP) would contribute less to global warming than a refrigerant with higher GWP, if leaked to the atmosphere. This appliance contains a refrigerant fluid with a GWP equal to 3. This means that if 1 kg of this refrigerant fluid would be leaked to the atmosphere, the impact on global warming would be 3 times higher than 1 kg of CO ₂ , over a period of 100 years. Never try to interfere with the refrigerant circuit yourself or disassemble the product yourself and always ask a professional.	3
------------------------------	---	---

EER ²	W/W	2,67
EE-Class / Heating performance ²		A
Indicative hourly electricity consumption (Q _{sd} /h)	kW	1,3
Capacity (P rated) Cooling ²	kW	3,34

Product specifications

Colour		white
EAN code		8713508778150

Technical specifications

Power consumption Cooling	kW	1,25
Power consumption standby mode	W	0,5
Power supply	V/Hz/Ph	220-240 / 50 / 1
Current	A	5,43
Air flow ¹	m ³ /h	300
For rooms up to ¹	m ³	80-110
Dehumidification capacity ³	L/ 24h	36
Operating range	°C	18-35
Thermostatic range	°C	18-32
Sound pressure level	dB(A)	54-56
Fan speed		3 positions
Control		electronic / remote
Refrigerant	type/charge (g)	R290 / 235
Refrigerant / GWP		3
CO ₂ equivalent	tonnes	0,0007
Dimensions (w x d x h)	mm	440 x 355 x 715
Compressor type		rotary
Protection class	IP	X0
Weight	kg	31
Guarantee	years	2

¹ To be used as indication

² Measured conform EN 14511-2011



³ Moisture removal at 35°C, 60% RH

Accessories

1 Exhaust hose
1 Hose inlet
1 Hose outlet
1 Window slider kit
Remote control (with battery)
Manual

Most important spare parts

Spare part description	EAN Code



20 ft = 144
40 ft = 288
HQ = 432

W x D x H =
479 x 389 x 860 mm

Gross =
35 kg

Qlima

HOME MADE CLIMATES

P 534 PORTABLE AIR CONDITIONER



Remote control

Features

Electronic controls: The unit is equipped with electronic touch controls.



3 Fan speed settings

Fan speed setting: Select the fan speed: low, medium or high. The display will show the chosen speed.

Timer: Operating time to be set up to 24 hours. The unit switches off or on automatically when the set time has run down.



Cooldown effect

Air conditioning: The unit produces, with relatively high energy efficiency (A-rating), a pleasant and refreshing high capacity cool airflow. Unhealthy particles are captured by the air filters. Performance is optimal when the entering of warm outside air

Airflow: Move the air vent direction by adjusting the grill at the front side of the air conditioner and by moving the vertical and horizontal louvers.



Environmental friendly refrigerant

Cooldown effect: The unit removes humidity by condensation. The condensate cools the condenser and is removed by the hot air discharge. This will increase the energy efficiency; the so called "cool down" effect.

Dehumidification: The unit can also be used as dehumidifier only. In that case the exhaust hose is not connected and warm air returns in the room.



Dehumidification function

Continuous drainage: In case of use as dehumidifier only it is necessary to connect a continuous drainage tube (not included) to the unit.

Exhaust duct: Hot air and humidity is transported, by an easy to install exhaust duct, outside the room.

Full colour box: The unit is delivered complete with auxiliary parts in a stylish full colour box showing application and operation information in multiple languages.

* Measured conform EN 14511