# G-kit Bonanza Bench Model

# Installation instructions





## G-kit Bonanza Bench model:

#### **Specifications:**

**Material:** aluminium extrusion profiles

patented plastic g-tools corner connectors

moist and fire resistant PVC/XPS sandwich panels

**Dimensions:** external (h x w x d): 119 X 61,5 X 61,5cm

internal (h x w x d): 104 X 58,5 X 58,5cm

#### Items below are only delivered when you've bought a complete version:

**Timer** Legrand Omnirex

minimum switch on period 15 min.

230V, 50Hz, 16A

maximum capacity 3680W

**Ventilator** Winflex 125 VKO in line axial ventilator, 185m3 / uur

230V. 50Hz, 0,1A

**Filter** maximum air flow: 240 m3/hour

optimal air flow: 160 m3/hour

height: 250mm

diameter filter: 190mm diameter flange: 125mm

weight: 1,5kg

Lamp Hanspanel 100/180Watt

or

E.T.I. 150 Watt

Philips Son T PIA plus, 150 Watt

Powerlux reflector

### Warranty procedure:

G-tools offers a 1 year warranty on all components of the Bonanza except bulbs and filters. Please contact your G-tools rep to explain the problem as there might be an easy fix without having to replace a part.

#### Maintenance and safety regulations:

The G-Kit Bonanza is a maintenance free object. Nevertheless there are a few factors to take into account.



- Only use grounded wall outlets to plug the Bonanza in.
- Do not plug the Bonanza into the wall outlet untill the machine is fully assembled and you have read the instructions.
- Avoid contact of water with all electrical equipment
- When changing the light bulb always unplug the Bonanza from the wall outlet.
- Make sure the light bulb has had plenty of time to cool of before touching it.
- After screwing in the HPS bulb wipe finger prints of the bulb with a clean dry cloth to ensure its full life.
- Wait 20 minutes after the light has turned of before turning it on again.
- It's recommanded that no more than 1 G-Kit Bonanza goes on a single 15A breaker. We also recommend the Bonanza is plugged into a surge protector. This will protect the machine from any power spikes due to storms, power outages, etc.
- Avoid contact with water with the non-laminated sides of the panels.

#### G-kit Bonanza Bench model:

Box A:  $top + bottom panel-box 62 \times 62 \times 30cm$ 

Amount	Description	Length (mm)	Width
		- 4 7	-1 -
1	roof panel in alu frame (with timer,	615	615
	fan, filter, Hanspanel or E.T.I 150 Watt and reflector*)		
1	bottom pannel in alu frame	615	615
4	feet with protection cover	80	
2	handle with 4 x screw and washers		
3	air inlet		
1	plug		
4	plastic U profile	530	
1	flange ∅125mm		

**Box B:** panels – box 120 x 73 x 5cm

Amount	Description	Length (	(mm) Width
2	side panels left and right	1028	564
1	door	1014	295
1	door with aluminium strip and weather	strip 1014	295
1	back panel :-1 x hole ∅121mm	1028	564
	-3 x hole Ø 76mm		
	-1 x hole Ø 21mm		
4	angle profile	1000	

Total packing 2 boxes (without box or pallet) -30,0kg Items marked with a \* are only part of a complete version.

# G-kit Bonanza Bench model installation instructions:

### 1. General:

To prevent transport damage the bottom and roof of the cabinet are connected with 4 aluminium profiles. These profiles serve no further purpose and can be thrown away.	
Push the 4 aluminium feet on the plastic connectors underneath the bottom panel.	
Push the 4 angle profiles (100cm) on the connectors.	1 1
Place the back panel and side panels. Install the air inlets (more details on how to install the inlets in chapter 2).	

Place the roof panel on the 4 angle profiles and push it tight carefully.	
Pull the electricity cord through the cable through entry.	
Mount the cable through entry in the 21mm hole in the back panel of the cabinet and mount the supplied plug.	
Push the air grid through the hole in the back panel in to the silencer. From outside to within.	
Hang the lamp, set the timer (chapter 3) and place the doors (chapter 4). The door with the aluminium profile and weather strip slides through the rail in the back so the strip seals the gap where the doors overlap.	

#### 2. The air inlets

Each air inlet consists of 2 parts.







- -Push part 1 inwards through the hole in the back.
- -Push part 2 on part 1 and twist & lock.

#### 3. Setting the timer

- a. Set the switch on the right side of the timer at the clock symbol.b. Set the current time by turning the dial of the timer.
- c. The pins in the outer ring mean: Positioned outside - OFF Positioned inside - ON

Set the timer for lights ON by pushing the pins inward

#### 4. The plastic door profiles

In order to have better access to your plants both top doors are removable.

Place the four plastic U profiles inside the lips of the aluminium profile where te doors slide through. Two in every profile. The plastic profiles should be placed on top of each other. The doors will slide through this profile. (see picture 6). The doors can now be simply removed by lifting them and pulling them towards you.



picture 5

#### Frequently asked questions (F.A.Q.'s)

#### How much will my electricity-bill go up?

For a G-kit Bench model 150 W HPS:

When the lights are on for an average of 14/hours /day: approx.. €15,-/ month

For a G-kit Bench model Hanspanel 100W:

When the lights are on for an average of 14/hours /day: approx.. €9,-/ month

#### Won't the cabinets get to warm?

Normally it gets 5 to 6 degrees warmer inside the cabinet than outside.

It's best to have it in a room where you can leave a window open.

If you have more than one G-Kit in a room make sure that the light of one switches on when the light of the other switches off (the lights are on 12 hours a day).

#### The humidity is too low, what to do?

Especially in the beginning it is important the plant get enough water. To spray them with water in the first two weeks is the best.

#### Is it possible to put a G-kit in a barn or garage?

No problem, make sure there is enough fresh air and keep it warm in the winter.

#### Do I get warranty?

There's a one year warranty on all electrical equipment except for the light-bulb and filter. New parts shall be send to you after the broken parts have been received at the distribution center.

#### **Contact:**

For all your questions visit our website www.g-tools.nl or send an e-mail to: info@g-tools.nl

**WEEE registration number:** DE 68161470

The symbol of the crossed-out wheelie bin on electrical and electronic equipment means that it mustn't be removed in household waste. There are free collection points for the return of WEEE available nearby. Please inquire at your city or municipality about the addresses. You can also contact us regarding other options to return old equipment. By separate collection of WEEE, the reuse and recycling of old equipment are made possible and any negative impact on the environment and human health due to hazardous substances in old equipment is eliminated. You are responsible for the erasure of any private data which could still be stored on old equipment. Further information can be found on <a href="https://www.elektrogesetz.de">www.elektrogesetz.de</a>.

—— DEUTSCH ——
---------------

Das Symbol des durchgestrichenen Mülleimers auf einem Elektro- oder Elektronikgerät besagt, dass dieses am Ende seiner Lebensdauer nicht im Hausmüll entsorgt werden darf. Zur kostenfreien Rückgabe stehen in Ihrer Nähe Sammelstellen für Elektro- und Elektronikaltgeräte zur Verfügung. Die Adressen erhalten Sie von Ihrer Stadt- bzw. Kommunalverwaltung. Sie können sich auch an uns wenden, um sich über weitere, von uns geschaffene Rückgabemöglichkeiten zu informieren. Durch die getrennte Sammlung von Elektro- und Elektronikaltgeräten soll die Wiederverwendung, die stoffliche Verwertung bzw. andere Formen der Verwertung von Altgeräten ermöglicht sowie negative Folgen bei der Entsorgung der in den Geräten möglicherweise enthaltenen gefährlichen Stoffe auf die Umwelt und die menschliche Gesundheit vermieden werden. Sie sind verantwortlich für die Löschung von möglicherweise auf den zu entsorgenden Altgeräten vorhandenen personenbezogenen Daten. Weitere Informationen finden Sie auch auf www.elektrogesetz.de.