





Power	15-27 W	Voltage	230 V
Colour temperature	3000 K	Light colour	WW
Beam angle	36, 60 °	Protection class	IP20




See more on dedicated page 



 User manual



 Declaration of Conformity



 Photometric file



Technical data:

Product code	SLI033021WW_PW
Power	15-27 W
Nominal current	120 mA
Voltage	230 V
Energy consumption	27 kWh/1000h
Frequency	50HZ Hz
Protection class	II
Power supply included	Yes
Power factor	0.9
Useful luminous flux*	3000 lm (360°)
Luminous flux**	1500-2500 lm (360°)
Light efficiency	111 lm/W
Luminous intensity	6100 cd
Colour temperature	3000 K
Light colour	WW
Beam angle	36, 60 °
RA	>90
Light source included	Yes
Uniformity of color SDCM max	5
Dimmable	No
Working temperature range	-20/+40 °
Lifespan	50000 h
Housing material	Aluminum, PLASTIC
Protection class	IP20
Colour	Black
Dimension (axbxc)	74x170x170 mm
For use	Inside
Assembly method	On 3-circuit system
Application	Inside
Made in	PRC
Other	DIP SWITCH - regulowana moc oprawy ,



*Applies to the LED source used. **Luminaire luminous flux