

Specsheet transparent labels



Westland
Verpakkingen

Facestock

A semi transparent paper. The facestock is made from FSC® certified paper (FSC Mix Credit, chain-of-custody number: CU-COC-807907, Licence Code: FSC-C004451)

Basis Weight	63 g/m ²	ISO 536
Caliper	55 µm	ISO 534

Adhesive

A general purpose permanent, acrylic based adhesive.

Liner

Hygroflat 80, a one side coated, bleached kraft paper.

Basis Weight	81 g/m ²	ISO 536
Caliper	79 µm	ISO 534

Laminate

Total Caliper	147 µm±10%	ISO 534
---------------	------------	---------

Performance Data

Initial Tack	10 N/25mm	FTM 9 Glass
Peel Adhesion	90° 5.5 N/25mm	FTM 2 St.St.
Min. Application Temp.	0 °C	
Service Temperature	-20 °C to 80 °C	

Adhesive Performance

The adhesive features good tack and adhesion performance on a wide range of substrates, even at low temperatures. The adhesive has very low bleeding characteristics for optimal use in hot laser and copier machines.

Specsheet transparent labels



Applications and Use

Product suitable for the use of transparent matt laser and inkjet labels, e.g. no label look address labels. The hygroflat backing paper is generally suited to the refolding demands of high-speed computer printers, providing optimum layflatness and excellent interfolding characteristics.

Compliance and Approvals

The adhesive S2012HT is suitable for contact with dry, moist, and fatty foodstuffs that have a reduction factor of 4 or higher in this construction in this construction.

Shelf Life

To obtain optimal performance, use this product within two years of the date of manufacture, under storage conditions as defined by FINAT (20-25°C; 40-50%RH). Prolonged storage outside these conditions might reduce the shelf life.