Following the regulation (EC) n° 453 /2018

ULTRAMARINE PURPLE





Version 4

1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND THE COMPANY UNDERTAKING

The information contained herein is specific to the following grades:

Ultramarine Purple

11, 12, 13, 20, CM34, CM125

Uses

Ultramarine purple & pink are used as colorants in plastics, paper,

food contact packaging, inks, paints, cosmetics, ...

Supplier

Holliday Pigments SAS

Address

203, route de Wervicq

France - 59559 - Comines Cedex

2 +33 (0)3.20.63.12.00 Fax +33 (0)3.20.39.20.83 HPlabo@holliday-pigments.com www.holliday-pigments.com

Emergency Telephone

Europe:

+44 (0) 3700 492 795 (CareChem24)

2. HAZARD IDENTIFICATION

Ultramarine Pigments are not classified as dangerous for supply or transport according to regulation (EC) n°1272/2008 and Directive 67/548/EC.

As with all clay minerals Ultramarine can create a nuisance dust which may aggravate existing respiratory problems.

Contact with acids liberates hydrogen sulphide, a highly flammable toxic gas.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Component

Ultramarine Purple

Ultramarine Pink

Chemical Name

Sodium alumino sulpho silicate

Colour Index number

Pigment violet 15: 77007

Pigment red 259: 77007

CAS number

12769-96-9

12769-96-9

EC number

235-811-0

235-811-0

REACH registration number:

01-2119917334-42-0001



Following the regulation (EC) no 453/ 2018

ULTRAMARINE PURPLE

Version 4

4. FIRST AID MEASURES

> Inhalation Skin Contact

Remove patient to fresh air Wash with soap and water

Eye Contact

Rinse immediately with plenty of water, also under the eyelids,

for at least 15 minutes. If irritation persists seek medical attention

Ingestion

This product is non-toxic

5. FIRE FIGHTING MEASURES

Any convenient extinguishing medium is safe to use on this product

Specific Dangers

Sulphur Dioxide gas can be liberated if this product undergoes

chemical change during a fire sustained by other materials.

Protective Equipment :

Suitable breathing apparatus should be worn

6. ACCIDENTAL RELEASE MEASURES

Protective Equipment

Refer to Section 8 for details

Personal Precautions

None necessary unless contact with acids or fire should

occur, in which case self contained breathing apparatus

should be worn.

Environmental Precautions

: Do not flush into surface water or sanitary sewer systems.

Methods for Cleaning

Sweep up spillages. In case of accidental major discharge

into drains, flush with copious amounts of water to dilute

any acidic conditions that may prevail.

7. HANDLING AND STORAGE

Protective Measures

Avoid excessive dust generation. Use extraction where possible

and wear a dust mask (EN149, FFP1).

Storage

Store in a dry, well ventilated area. Do not store near acids or

flammable materials.

Packaging Materials

Paper sacks, PE sacks or drums

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

OEL (UK)

10mg/m³, 8 hour TWA (inhalable dust)

OEL (UK)

4mg/m³, 8 hour TWA (respirable dust)

Ultramarine pigments are considered non-toxic, the limits quoted are the UK limits for nuisance dusts. Consult local regulations before using this product.





Following the regulation (EC) no 453/ 2018

ULTRAMARINE PURPLE

Respiratory Protection

Version 4

:Wear a suitable dust mask rated to EN149 FFP 1.

In the event of contact with acids or fire use self-contained

HOLLIDAY PIGMENTS

breathing apparatus.

This product is non-irritating, therefore protection is not essential. Hand Protection

However it is recommended to use disposable nitrile or vinyl

gloves when handling bulk quantities.

Eye Protection

Safety eyewear rated to EN166. Use goggles in windy conditions.

Wear overalls (cotton or polyester) when handling bulk quantities.

Chemical resistant materials are not required.

PHYSICAL AND CHEMICAL PROPERTIES 9.

> Form Fine violet or pink powder (19, 5029)

pH (10% suspension)

None present

6 - 9

Decomposition temp.

Body Protection

Loss of sulphur at 400°C / 750°F

Flammability

Odour

Not applicable. This product is not flammable and does not

provide conditions favourable to combustion.

Explosive Limits

Ultramarine dusts do not form explosive mixtures in air.

Specific Gravity Solubility

Insoluble in water and organic solvents

10. STABILITY AND REACTIVITY

Stability

Stable in air up to 260°C / 500°F

Conditions to Avoid

At temperatures above 400°C/750°F in the presence of air an

exothermic reaction can occur with the liberation of Sulphur Dioxide

(50₂) gas.

Contact with acids liberates Hydrogen Sulphide (H2S) gas.

Decomposition Products:

Hydrogen Sulphide - on contact with acids

Sulphur Dioxide - in combustion

11. TOXICOLOGICAL INFORMATION

Oral LD50 (rat)

>10000mg/Kg

Skin Irritation

a. short term (rabbit)

b. long term (guinea pig) 6.25% conc

None None

Mutagenicity

None

Teratogenicity

None



Following the regulation (EC) no 453/ 2018

ULTRAMARINE PURPLE

Version 4



12. ECOLOGICAL EFFECTS

Ultramarine pigments are synthetic equivalents of the mineral Lapis Lazuli.

They are extremely stable, except under acidic conditions when they will decompose to white siliceous material with the evolution of Hydrogen Sulphide gas (see sections 3 and 10).

CL50 - 96 hours (fish)

:>32000 mg/Kg

WGK

: 1

Biodegradability : not applicable Bio-accumulation : not applicable

13. DISPOSAL CONSIDERATIONS

Method of Disposal

Dispose of in accordance with local and national regulations

governing chemical waste.

Other Information

Ultramarine pigments should not be washed into waste-water

drains

Ultramarine pigments should not be disposed of where there

is a risk of contact with acids.

14. TRANSPORT INFORMATION

Ultramarine pigments are not classified as dangerous substances for supply or transport under international regulations.

Do not transport with acids.

15. REGULATORY INFORMATION

OTHER INFORMATION

Although Ultramarine pigments are non toxic, inhalation of dusts and powders should be avoided in the general interests of health and safety. Use dust extraction systems and wear a dust protection mask if necessary.

The revisions made since the previous report are indicated by an * next to the entry.

The information contained in this document comes from sources which we consider to be credible. Nevertheless this information is supplied without any guarantee – expressed or implied of its correctness. The conditions and methods of handling, storage, usage, or disposal of this product are beyond our control and cannot fall within our capability. For these reasons and others we decline all responsibility in the event of loss, damage or expense caused by or because of the handling, storage, use or disposal of the product.

The MSDS has been written for the products listed in section 1 and must only be used for these products. If this product is used as a component in another product the information provided may no longer be applicable.

