

Textile clamping frame LED CURTAIN


Light box solution from S to XXL in an elegant aluminum profile with extremely homogeneous and very bright illumination approx. 3500 lux. The system can be set up quickly and easily.

CONSTRUCTION




Double-sided hanging

disassembled shipping




On one side on frames

disassembled shipping



On one side on aluminum composite plate

assembled shipping




Depths:

Primex 55er profile
new Art. : 60804
Primex 100er profile
Art. : 60971
Primex 150er profile
new Art. : 61214


EQUIPMENT




Corner connector
55 profile
Art. : 60203




claplock corner connector
100er profile
Art. : 60188




claplock corner connector
150er profile
Art. : 60222




Base plates for
100 and 150 profile
10 x 60 cm center hole
Art. : 60444




Base plates for
100 and 150 profile
10 x 40 cm center hole
Art. : 60442




Base plates for
100 and 150 profile
10 x 60 cm
back hole
Art .: 60445




Base plates for
100 and 150 profile
10 x 40 cm
back hole
Art .: 60443




Lateral Delta Feet
Art .: 60171




Wall holder
100 profile
Art .: 60184




Wall holder
150 profile
Art .: 60164
+ Art .: 60271




Ceiling hanger with
wire rope
Art .: 60502 + 60503




Base plates for
100 and 150 profile
15 x 45 cm
center hole
Art .: 60404



Profile connector
55er profile
Art .: 60847



Folding profile
connector
100 profile
Art .: 60211



Folding profile
connector
150 profile
Art .: 60223

INFO & DETAILS
LIGHTBOX

overall depth	55 mm one-sided on aluminum composite panel, 100 mm and 150 mm one-sided on frames, single-sided and double-sided hanging.
formats	Individual production. Maximum frame size: The width is limited by the web width to 5 m, in the length we recommend max. 20 m for wall mounting.
variants	Wall-mounted, freestanding, suspended from the ceiling
assembly	Lighting technology largely pre-assembled Simple plug-and-play installation of disassembled parts (without electrician) Pre-assembled safety plug (white, 2m cable). VDE compliant.

INFO & DETAILS
LIGHTING TECHNOLOGY

brightness	Per light box about 3400 lux, dimming possible
Power / volt	1 watts per lens / 24 volts
light color	Standard approx. 6500 Kelvin (+/- 500 Kelvin)
LEDs	Primex uses only reliable LEDs (Nichia, Cree, Epistar, etc.).