



Textile clamping frame LED Modul

Light box solution from S to XL in an elegant aluminum profile with a bright illumination of approx. 1600 lux. The system can be set up quickly and easily.


CONSTRUCTION




LED modules
3 and 9



One-sided and double-sided illumination




Plug-and-play plug-ins




Depths:
Primex 100er profile
Art.: 60971
Primex 150er profile new
Art.: 61214


EQUIPMENT




claplock corner connector
100er profile
Art.: 60188




claplock corner connector
150er profile
Art.: 60222




Base plates for
100 and 150 profile
10 x 60 cm center
hole Art.:
60444




Base plates for
100 and 150 profile
10 x 40 cm
center hole
Art.: 60442




Base plates for
100 and 150 profile
10 x 60 cm
back hole
Art. : 60445




Base plates for
100 and 150 profile
10 x 40 cm
back hole
Art. : 60443




Lateral Delta Feet
Art. : 60171




Wall holder
100 profile
Art. : 60184




Wall holder
150 profile
Art. : 60164
+ Art. : 60271




Ceiling hanger with
wire rope
Art. : 60502 + 60503




Base plates for
100 and 150 profile
15 x 45 cm
center hole
Art. : 60404



Profile connector
55er profile
Art. : 60847



Folding profile
connector
100 profile
Art. : 60211



Folding profile
connector
150 profile
Art. : 60223

INFO & DETAILS
LIGHTBOX
overall depth

100 mm and 150 mm one-sided and double-sided illumination.

formats

Individual production. Maximum Frame Size: The width is due to the illumination 2.5 m limited, in the length we recommend max. 20 m for wall mounting.

variants

Wall-mounted, freestanding, suspended from the ceiling

assembly

Lighting technology lateral radiation largely pre-assembled
Easy plug-and-play mounting of disassembled parts (without electrician)
Schuko plug pre-mounted (white, 2m cable). VDE compliant.

INFO & DETAILS
LIGHTING TECHNOLOGY
brightness

Per light box about 1600 lux, dimming possible

Power / volt

3 module 4 watts, 9 module 12 Watt / 12 - 24 volts

light color

Standard approx. 6500 Kelvin (+/- 500 Kelvin)

LEDs

Primex uses only reliable LEDs (Nichia, Cree, Epistar, etc.).