

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 02.28.2024

Grey V5 Resin

SECTION 1: Identification

Product Identifier

Product Name: Grey V5 Resin Product code: FLGPGR05

Recommended Use of the Product and Restriction on Use

Relevant Identified Uses: For use in Formlabs SLA Printers Uses Advised Against: Not determined or not applicable. Reasons Why Uses Advised Against: Not determined or not applicable.

Manufacturer or Supplier Details

Manufacturer: United States Formlabs, Inc 35 Medford St Suite 201 Somerville, MA 02143 +1 617 855 0762 sds@formlabs.com

Emergency Telephone Number:

United States CHEMTREC 1-800-424-9300 (24/7)

SECTION 2: Hazard(s) Identification

GHS Classification:

Skin irritation, category 2 Eye irritation, category 2A Skin sensitization, category 1 Chronic aquatic hazard, category 2

Label elements

Hazard Pictograms:



Signal Word: Warning

Hazard statements:

H315 Causes skin irritation

H319 Causes serious eye irritation

H317 May cause an allergic skin reaction

H411 Toxic to aquatic life with long lasting effects

Precautionary Statements:

P264 Wash skin thoroughly after handling

Page 1 of 11

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 02.28.2024

Grey V5 Resin

P280 Wear protective gloves, protective clothing and eye protection.

P261 Avoid breathing dust/fume/gas/mist/vapors/spray

P272 Contaminated work clothing must not be allowed out of the workplace

P273 Avoid release to the environment

P302+P352 IF ON SKIN: Wash with plenty of soap and water

P332+P313 If skin irritation occurs: Get medical advice/attention

P362 Take off contaminated clothing and wash it before reuse

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

P337+P313 If eye irritation persists: Get medical advice/attention.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention

P363 Wash contaminated clothing before reuse

P391 Collect spillage

P501 Dispose of contents/container in accordance with local/regional/national regulations

Hazards Not Otherwise Classified: None

SECTION 3: Composition/Information on Ingredients

Identification	Name	Weight %
CAS Number: Trade Secret	Methacrylate Oligomer(s)	10-15
CAS Number: Trade Secret	Methacrylate Monomer(s)	65-85
CAS Number: Trade Secret	Urethane dimethacrylate	10-15
CAS Number: Trade Secret	Photoinitiators	<3

Additional Information: None

SECTION 4: First Aid Measures

Description of First Aid Measures

General Notes:

Show this Safety Data Sheet to the doctor in attendance.

After Inhalation:

If inhaled, remove person to fresh air and place in a position comfortable for breathing. If respiratory symptoms develop or persist, seek medical advice/attention.

After Skin Contact:

Wash affected area with plenty of soap and water. Remove contaminated clothing and launder before reuse. If skin irritation develops or persists, seek medical advice/attention.

After Eye Contact:

Rinse eyes with plenty of water for several minutes. Remove contact lenses if present and easy to do so. Protect unexposed eye. If symptoms develop or persist, seek medical advice/attention.

After Swallowing:

If swallowed, DO NOT induce vomiting unless told to do so by a physician or poison control center. Rinse mouth with water. Never give anything by mouth to an unconscious person. If spontaneous vomiting occurs, place on the left side with head down to prevent aspiration of liquid into the lungs. If symptoms develop or persist, seek medical advice/attention.

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 02.28.2024

Grey V5 Resin

Most Important Symptoms and Effects, Both Acute and Delayed Acute Symptoms and Effects:

Skin contact may result in redness, pain, burning and inflammation.

Eye contact may result in irritation, redness, pain, inflammation, itching, burning and tearing.

Dermal exposure may cause an allergic skin reaction. Symptoms may include irritation, redness, pain, rash, inflammation, itching, burning and dermatitis.

Delayed Symptoms and Effects:

Effects are dependent on exposure (dose, concentration, contact time).

Immediate Medical Attention and Special Treatment

Specific Treatment:

Not determined or not applicable.

Notes for the Doctor:

Treat symptomatically.

SECTION 5: Firefighting Measures

Extinguishing Media

Suitable Extinguishing Media:

Water mist/fog, carbon dioxide, dry chemical or alcohol resistant foam.

Unsuitable Extinguishing Media:

Do not use water jet.

Specific Hazards During Fire-Fighting:

Thermal decomposition may produce irritating/toxic fumes/gases.

Special Protective Equipment for Firefighters:

Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA).

Special precautions:

Avoid contact with skin, eyes, hair and clothing. Do not breathe fumes/gas/mists/aerosols/vapors/dusts. Move containers from fire area if safe to do so. Use water spray/fog for cooling fire exposed containers. Avoid unnecessary run-off of extinguishing media which may cause pollution.

SECTION 6: Accidental Release Measures

Personal Precautions, Protective Equipment, and Emergency Procedures:

Evacuate unnecessary personnel. Ventilate area. Extinguish any sources of ignition. Wear recommended personal protective equipment (see Section 8). Avoid contact with skin, eyes and clothing. Avoid breathing mist, vapor, dust, fume and spray. Do not walk through spilled material. Wash thoroughly after handling.

Environmental Precautions:

Prevent further leakage or spillage if safe to do so. Prevent from reaching drains, sewers and waterways. Discharge into the environment must be avoided.

Methods and Material for Containment and Cleaning Up:

Do not touch damaged containers or spilled material unless wearing appropriate personal protective clothing. Stop leak if you can do it without risk. Contain and collect spillage and place in suitable container for future disposal. Dispose of in accordance with all applicable regulations (see Section 13).

Reference to Other Sections:

For personal protective equipment see Section 8. For disposal see Section 13.

SECTION 7: Handling and Storage

Precautions for Safe Handling:

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 02.28.2024

Page 4 of 11

Grey V5 Resin

Use appropriate personal protective equipment (see Section 8). Use only with adequate ventilation. Avoid breathing mist/vapor/spray/dust. Do not eat, drink, smoke, or use personal products when handling chemical substances. Avoid contact with skin, eyes and clothing. Wash affected areas thoroughly after handling. Keep away from incompatible materials (See Section 10). Keep containers tightly closed when not in use.

Conditions for Safe Storage, Including Any Incompatibilities:

Store in cool, dry, well-ventilated location out of direct sunlight. Keep away from food and beverages. Protect from freezing and physical damage. Store away from heat, open flames and other sources of ignition. Keep container tightly sealed. Store away from incompatible materials (See Section 10).

SECTION 8: Exposure Controls/Personal Protection

Only those substances with limit values have been included below.

Occupational Exposure Limit Values:

No occupational exposure limits noted for the ingredient(s).

Biological Limit Values:

No biological exposure limits noted for the ingredient(s).

Information on Monitoring Procedures:

Not determined or not applicable.

Appropriate Engineering Controls:

Emergency eye wash stations and safety showers should be available in the immediate vicinity of use or handling. Provide adequate ventilation to maintain the airborne concentrations of vapor, mists, and/or dusts below the applicable workplace exposure limits, while observing recognized national standards (or equivalent).

Personal Protection Equipment

Eye and Face Protection:

Safety glasses or goggles. Use eye protection equipment that has been tested and approved by recognized national standards (or equivalent).

Skin and Body Protection:

Chemical resistant, impervious gloves approved by the appropriate standards. Gloves must be inspected prior to use. Avoid skin contact with used gloves. Appropriate techniques should be used to remove used gloves and contaminated clothing. Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. Ensure that all personal protective equipment is approved by recognized national standards (or equivalent).

Respiratory Protection:

If engineering controls do not maintain airborne concentrations below the applicable workplace exposure limits, or to an acceptable level (if exposure limits have not been established), a respirator approved by recognized national standards (or equivalent) must be worn.

General Hygienic Measures:

When handling chemical products, do not eat, drink or smoke. Wash hands after handling, before breaks, and at the end of the workday. Avoid contact with skin, eyes and clothing. Wash contaminated clothing before reuse. Perform routine housekeeping.

SECTION 9: Physical and Chemical Properties

Information on Basic Physical and Chemical Properties

Appearance	Opaque grey liquid
Odor	Characteristic acrylate

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 02.28.2024

Grey V5 Resin

Not determined or not available.
Not determined or not available.
Not determined or not available.
> 100°C
> 93.5°C
Not determined or not available.
Not flammable
Not determined or not available.
1.11 gm/cm3
Not determined or not available.
800 cP @ 25°C
Not determined or not available.
Not determined or not available.
Not determined or not available.

SECTION 10: Stability and Reactivity

Reactivity:

Not reactive under recommended handling and storage conditions.

Chemical Stability:

Stable under recommended handling and storage conditions.

Possibility of Hazardous Reactions:

Hazardous reactions are not anticipated under recommended conditions of handling and storage. Stable under recommended handling and storage conditions.

Conditions to Avoid:

Extreme heat, open flames, hot surfaces, sparks, ignition sources and incompatible materials. Avoid storage >38°C (100°F) and exposure to light/direct sunlight and heat.

Incompatible Materials:

ncompatible materials: Polymerization initiators, including peroxides, strong oxidizing agents, alcohols, copper, copper alloys, carbon steel, iron, rust, and strong bases.

Hazardous Decomposition Products:

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological Information

Acute Toxicity

Assessment: Based on available data, the classification criteria are not met. Product Data: No data available. Substance Data:

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 02.28.2024

Grey V5 Resin

Name	Route	Result
Methacrylate Monomer(s)	oral	LD50 Rat: 5564 mg/kg
	dermal	LD50 Rabbit: >5000 mg/kg
Urethane dimethacrylate	oral	LD50 Rat: >5000 mg/kg
	dermal	LD50 Rat: >2000 mg/kg
Photoinitiators	oral	LD50 Rat: >5000 mg/kg
	dermal	LD50 Rat: >=2000 mg/kg
Methacrylate Oligomer(s)	oral	LD50 Rat: >5110 mg/kg

Skin Corrosion/Irritation

Assessment:

Causes skin irritation.

Product Data:

No data available.

Substance Data:

Name	Result
Methacrylate Monomer(s)	Causes skin irritation.

Serious Eye Damage/Irritation

Assessment:

Causes serious eye irritation.

Product Data:

No data available.

Substance Data:

Name	Result
Methacrylate Monomer(s)	Causes serious eye irritation.

Respiratory or Skin Sensitization

Assessment:

May cause an allergic skin reaction.

Product Data:

No data available.

Substance Data:

Name	Result
Methacrylate Monomer(s)	May cause an allergic skin reaction.
Urethane dimethacrylate	May cause an allergic skin reaction.
Photoinitiators	May cause an allergic skin reaction.

Carcinogenicity

Assessment: Based on available data, the classification criteria are not met.

Product Data: No data available.

Substance Data: No data available.

International Agency for Research on Cancer (IARC):

Name	Classification
Methacrylate Monomer(s)	Not Applicable
Urethane dimethacrylate	Not Applicable
Photoinitiators	Not Applicable

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 02.28.2024

Grey V5 Resin

Name	Classification
Methacrylate Monomer(s)	Not Applicable
Urethane dimethacrylate	Not Applicable
Photoinitiators	Not Applicable
OSHA Carcinogens: Not app	blicable
Germ Cell Mutagenicity	
-	able data, the classification criteria are not met.
Product Data:	
No data available.	
Substance Data: No data av	vailable.
Reproductive Toxicity	
• •	able data, the classification criteria are not met.
Product Data:	
No data available.	
Substance Data: No data av	vailable.
Specific Target Organ Toxicity	v (Single Exposure)
	able data, the classification criteria are not met.
Product Data:	
No data available.	
Substance Data: No data av	vailable.
Specific Target Organ Toxicity	v (Repeated Exposure)
	able data, the classification criteria are not met.
Product Data:	
No data available.	
Substance Data: No data av	vailable.
Aspiration toxicity	
	able data, the classification criteria are not met.
Product Data:	
No data available.	
Substance Data: No data av	vailable.
nformation on Likely Routes	of Exposure:
No data available.	
Symptoms Related to the Phy	vsical, Chemical, and Toxicological Characteristics:
No data available.	
Other Information:	

Acute (Short-Term) Toxicity

Assessment: Based on available data, the classification criteria are not met. **Product Data:** No data available.

Substance Data:

Name	Result
Methacrylate Monomer(s)	Fish LC50 Oryzias latipes: >100 mg/L (96 hr)
	Aquatic Invertebrates EC50 Daphnia magna: 380 mg/L (48 hr [mobility])

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 02.28.2024

Grey V5 Resin

Name	Result
Urethane dimethacrylate	Fish LC50 Danio rerio: 10.1 mg/L (96 hr)
	Aquatic Invertebrates EC50 Daphnia magna: > 1.2 mg/L (48 hr [mobility])
	Aquatic Plants EC50 Desmodesmus subspicatus: > 0.68 mg/L (72 hr [growth rate])
Photoinitiators	Aquatic Plants EC50 Pseudokirchneriella subcapitata: >2.01 mg/L (72 hr [growth rate; read-across[)
	Fish LC50 Danio rerio: 1 mg/L (96 hr [read-across])
	Aquatic Invertebrates EC50 Daphnia magna: 3.53 mg/L (48 hr [read- across])
Methacrylate Oligomer(s)	Fish LC50 Poecilia reticulata: ≥ 100 mg/L (96 hr)

Chronic (Long-Term) Toxicity

Assessment:

Toxic to aquatic life with long lasting effects.

Product Data: No data available.

Substance Data:

Name	Result
	Aquatic Invertebrates EC50 Daphnia magna: 90.1 mg/L (21 d [reproduction])

Persistence and Degradability

Product Data: No data available.

Substance Data:

Name	Result
Methacrylate Monomer(s)	Readily biodegradable (92 - 100% degradation after 14 days, measured by Oxygen consumption).
Urethane dimethacrylate	The substance is not readily biodegradable. 22% degradation, measured by CO2 evolution, after 28 days.
Photoinitiators	The substance is not readily biodegradable. <10 % degradation in water, measured by O2 consumption, after 28 days.
Methacrylate Oligomer(s)	The substance is not readily biodegradable.

Bioaccumulative Potential

Product Data: No data available.

Substance Data:

Name	Result	
Methacrylate Monomer(s)	This substance has low potential to bioaccumulate (log kow: <=3).	
Photoinitiators	The substance has a low potential for bioaccumulation based on a log Kow of 2.91.	
Methacrylate Oligomer(s)	The substance has the potential to bioaccumulate (BCF=292.4, Calculation method).	

Mobility in Soil

Product Data: No data available.

Substance Data:

Name	Result
	The substance has moderate potential to adsorb to organic soil and sediment particles (log Koc: 3.66 dimensionless).
Photoinitiators	Based on a log Koc of 3.37, adsorption to solid soil phase is expected.

Results of PBT and vPvB assessment

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 02.28.2024

Grey V5 Resin

Product Data:

PBT assessment: This product does not contain any substances that are assessed to be a PBT. **vPvB assessment:** This product does not contain any substances that are assessed to be a vPvB.

Substance Data: PRT assessment:

Methacrylate Monomer(s)	This substance is not PBT.	
Urethane dimethacrylate	The substance is not PBT.	
vPvB assessment:		
Methacrylate Monomer(s)	This substance is not vPvB.	
Urethane dimethacrylate	The substance is not vPvB.	

Other Adverse Effects: No data available.

SECTION 13: Disposal Considerations

Disposal Methods:

As supplied, this material is not considered a hazardous waste under RCRA. If the material has been altered or contaminated, or it has exceeded its recommended shelf life, the guidance may be inapplicable. Do not discharge into public wastewater or surface waters. It is the responsibility of the waste generator to properly characterize all waste materials according to applicable regulatory entities.

Contaminated packages:

Dispose contaminated packages in a safe manner in accordance with local and national regulations. Do not allow the product to be released into the environment.

SECTION 14: Transport Information

United States Transportation of Dangerous Goods (49 CFR DOT)

UN Number	UN 3082	
UN Proper Shipping Name	Environmentally hazardous liquid, N.O.S. Urethane dimethacrylate	
UN Transport Hazard Class(es)	9	
Packing Group		
nvironmental Hazards Marine Pollutant		
Special Precautions for User	ecautions for User None	
Additional Information49 CFR 171.4(c)(2) Not regulated as dangerous goods we transported in single or inner packaging of 5 L or less for or net mass of 5 Kg or less for solids provided the packag meets the requirements of 49 CFR 173.24(a).		

International Maritime Dangerous Goods (IMDG)

UN Number	UN 3082	
UN Proper Shipping Name	Environmentally hazardous liquid, N.O.S. Urethane dimethacrylate	
UN Transport Hazard Class(es)	9	
Packing Group	III	
Environmental Hazards	Marine Pollutant	
Special Precautions for User	None	

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 02.28.2024

Page 10 of 11

Grey V5 Resin

This product is not regulated as a dangerous good when transported in sizes of \leq 5L provided the packaging meets the
general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.

International Air Transport Association Dangerous Goods Regulations (IATA-DGR)

UN Number	UN 3082	
UN Proper Shipping Name	Environmentally hazardous liquid, N.O.S. Urethane dimethacrylate	
UN Transport Hazard Class(es)	9	
Packing Group	111	
Environmental Hazards	ards Marine Pollutant	
Special Precautions for User	None	
Additional Information	This product is not regulated as a dangerous good when transported in sizes of \leq 5L provided the packaging meet the general provisions of 5.0.2.4.1, 5.0.2.6.1 and 5.0.2.8.	

SECTION 15: Regulatory Information

United States Regulations

Inventory Listing (TSCA):

	· /-	
Trade Secret	Methacrylate Monomer(s)	Listed - Active
Trade Secret	Urethane dimethacrylate	Listed - Active
Trade Secret	Photoinitiators	Listed
Trade Secret	Methacrylate Oligomer(s)	Listed

Significant New Use Rule (TSCA Section 5): None of the ingredients are listed.

Export Notification under TSCA Section 12(b): None of the ingredients are listed.

SARA Section 302 Extremely Hazardous Substances: None of the ingredients are listed.

SARA Section 313 Toxic Chemicals: None of the ingredients are listed.

CERCLA: None of the ingredients are listed.

RCRA: None of the ingredients are listed.

Section 112(r) of the Clean Air Act (CAA): None of the ingredients are listed.

Massachusetts Right to Know: None of the ingredients are listed.

New Jersey Right to Know: None of the ingredients are listed.

New York Right to Know: None of the ingredients are listed.

Pennsylvania Right to Know: None of the ingredients are listed.

California Proposition 65: None of the ingredients are listed.

Additional information: Not determined.

SECTION 16: Other Information

Abbreviations and Acronyms: None

Disclaimer:

This product has been classified in accordance with OSHA HCS 2012 guidelines. The information provided in this SDS is correct, to the best of our knowledge, based on information available. The information given is

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 02.28.2024

Grey V5 Resin

designed only as a guidance for safe handling, use, storage, transportation and disposal and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials, unless specified in the text. The responsibility to provide a safe workplace remains with the user.

NFPA: 2-1-1

HMIS: 2-1-1

Initial Preparation Date: 02.28.2024

End of Safety Data Sheet