

Portable

PERFORMER TPX153

3 Way Dual 15" Full Range Loudspeaker for Portable PA Applications

- 3 way full range loudspeaker for portable PA applications
- 500 Watts continuous, 2,000 Watts peak power
- High excursion dual 15" low frequency drivers with low mass coil for improved transient response
- Aluminium dome 1" compression driver with extended high frequency reproduction
- Low distortion waveguide provides 70° H x 50° V dispersion
- Hard wearing carpet covered 18mm (¾") wood construction
- Rugged powder coated perforated steel mesh grille
- Durable handles for easy lifting and carrying
- Neutrik speakON® NL4 connectors for reliable long life operation
- 10-Year Warranty Program*
- Designed and engineered in the U.K.



The 3-way full range TPX153 is a passive dual 15" 2,000 Watt loudspeaker system that is ideally suited for a wide range of portable speech and music sound reinforcement, including FOH, side and drum fill applications. Engineered as a standalone 3-way system not requiring any external equalization or filtering, the TPX153 achieves optimal performance when paired with a subwoofer and **TURBOSOUND** loudspeaker management systems.



The TPX153 loudspeaker features dual high excursion 15" low frequency drivers with low mass voice coils for improved transient response, and an aluminium dome 1" compression driver mounted on a 70° horizontal by 50° vertical dispersion low distortion waveguide. All drivers are matched with an internal passive crossover network in a reflex-loaded enclosure.

Covered in hard wearing black carpet, the cabinet is of 18 mm (¾") wood construction – and includes a rugged powder coated perforated steel mesh grille backed with reticulated foam, and durable handles for easy transport. The rear panel connector plate carries Neutrik speakON® NL4 connectors for input and link connections to additional enclosures.

Portable

PERFORMER TPX153

3 Way Dual 15" Full Range Loudspeaker for
Portable PA Applications



You Are Covered


We always strive to provide the best possible Customer Experience. Our products are made in our own [MUSIC Tribe](#) factory using state-of-the-art automation, enhanced production workflows and quality assurance labs with the most sophisticated test equipment available in the world. As a result, we have one of the lowest product failure rates in the industry, and we confidently back it up with a generous [Warranty program](#).

Portable


PERFORMER TPX153

3 Way Dual 15" Full Range Loudspeaker for
Portable PA Applications

Frequency Response Sensitivity 1 W / 1 m



Impedance




Portable


PERFORMER TPX153

3 Way Dual 15" Full Range Loudspeaker for
Portable PA Applications

Horizontal Beamwidth



Vertical Beamwidth








Portable

PERFORMER TPX153

3 Way Dual 15" Full Range Loudspeaker for
Portable PA Applications

Horizontal Polar Plots








Portable

PERFORMER TPX153

3 Way Dual 15" Full Range Loudspeaker for
Portable PA Applications

Vertical Polar Plots




Portable

PERFORMER TPX153

3 Way Dual 15" Full Range Loudspeaker for
Portable PA Applications

Dimensions



Portable

PERFORMER

TPX153

3 Way Dual 15" Full Range Loudspeaker for
Portable PA Applications

Technical Specifications

System

Frequency Response	50 Hz – 20 kHz \pm 3 dB 40 Hz – 20 kHz -10 dB
Nominal Dispersion	70° H x 50° V @ -6 dB points
Power Handling (IEC)	500 W continuous, 2,000 W peak
Sensitivity	97 dB (1 W @ 1 m)
Maximum SPL	124 dB continuous, 130 dB peak
Impedance	4 Ohms
Components	2 x 15" (388 mm) LF driver 1 x 1" (25 mm) HF compression driver

Enclosure

Connectors	2 x Neutrik speakON NL4
Wiring	Pins 1+ / 1- input, pins 2+ / 2- link
Dimensions HWD	1090 x 460 x 430 mm (42.9 x 18.1 x 16.9")
Net Weight	38.6 kg (84.9 lbs)
Construction	18 mm (¾") particle board
Finish	Black carpet covering
Grille	Powder-coated perforated steel

Portable

PERFORMER TPX153

3 Way Dual 15" Full Range Loudspeaker for
Portable PA Applications



Portable

PERFORMER TPX153

3 Way Dual 15" Full Range Loudspeaker for
Portable PA Applications



Portable

PERFORMER TPX153

3 Way Dual 15" Full Range Loudspeaker for
Portable PA Applications



For service, support or more information contact the TURBOSOUND location nearest you:

Europe
MUSIC Tribe Brands UK Ltd.
 Tel: +44156 273 2290
 Email: CARECrea@music-group.com
 CAREEnte@music-group.com
 CARELife@music-group.com

USA/Canada
MUSIC Tribe Commercial NV Inc.
 Tel: +1 702.800 8290
 Email: CARECrea@music-group.com
 CAREEnte@music-group.com
 CARELife@music-group.com

Japan
MUSIC Tribe Services JP K.K.
 Tel: +81 3 6231 0453
 Email: CARECrea@music-group.com
 CAREEnte@music-group.com
 CARELife@music-group.com

MUSIC Tribe accepts no liability for any loss which may be suffered by any person who relies either wholly or in part upon any description, photograph, or statement contained herein. Technical specifications, appearances and other information are subject to change without notice. All trademarks are the property of their respective owners. MIDAS, KLARK TEKNIK, LAB GRUPPEN, LAKE, TANNØY, TURBOSOUND, TC ELECTRONIC, TC HELICON, BEHRINGER, BUGERA and COOLAUDIO are trademarks or registered trademarks of MUSIC Group IP Ltd. © MUSIC Group IP Ltd. 2018 All rights reserved.