

Test Report Number: SHAH01215411

Date:

28 May, 2020

Applicant: WENZHOU OUTLOOK OPTICAL CO., LTD

12 SHENGYE RD.,LUCHENG SPECIALIZED,LIGH INDUSTRIAL PARK WENZHOU ZHEJIANG

Attn: HELLA

Sample Description:

One(1) style of submitted sample said to be:

Item Name : A2125A.

Supplier : WENZHOU OUTLOOK OPTICAL CO., LTD

Factory : ZHEJIANG OUTLOOK OPTICAL MANUFACTORY CO., LTD.

Tests Conducted:

As requested by the applicant, for details refer to attached page(s).

Conclusion:

Tested samplesStandardResultSubmitted samplesEN 166:2001 – Personal eye-protection — SpecificationsPass

Excluding:

- Clause 9 - Marking

- Clause 10 - Information supplied by the manufacturer

To be continued

Authorized By:

Intertek Testing Services Ltd, Shanghai, Wenzhou Branch

Peter Chen General Manager







Test Report Number: SHAH01215411

Tests Conducted

Requirements for Eye-protectors

Test standard: EN 166:2001 - Personal eye-protection - Specifications

Number of samples tested: Eighteen (18) pairs.

Product type: Spectacles

Claimed property:

Protection against high-speed particles: F.

Note:

(1) The submitted eye-protectors were declared by applicant for Adult use.

- (2) The applicant's attention was drawn that the manufacturer should not use the materials which are known to cause any skin irritation
- (3) CE marking is not specified in EN 166:2001 but per Regulation (EU) 2016/425, Article 16 & Article 17, the CE marking shall be affixed visibly, legibly and indelibly to the product. The format of this CE marking was given in Annex II of Regulation (EC) No 765/2008.
- (4) It was found that the CE marking on the submitted sample was in a different font height.

Clause	Requirement	Result		
6	Design and manufacturing requirements			
6.1	General construction	Р		
6.2	Materials	Note (2)		
6.3	Headbands	NA		
7	Basic, particular and optional requirements			
7.1	Basic requirements			
7.1.1	Field of vision	Р		
7.1.2.1	Spherical, astigmatic and prismatic refractive powers			
7.1.2.1.1	Unmounted oculars covering one eye	NA		
7.1.2.1.2	Mounted oculars and unmounted oculars covering both eyes	Р		
7.1.2.1.3	Cover plates	NA		
7.1.2.2	Transmittance			
7.1.2.2.1	Oculars without filtering action	Р		
7.1.2.2.2	Oculars with filtering action (filters) and housings for oculars with filtering action	NA		
7.1.2.2.3	Variations in transmittance	NA		
7.1.2.3	Diffusion of light	Р		
7.1.3	Quality of material and surface	Р		
7.1.4	Robustness			
7.1.4.1	Minimum robustness	NA		
7.1.4.2	Increased robustness			
7.1.4.2.1	Unmounted oculars	NA		
7.1.4.2.2	Complete eye-protectors and frames	Р		

学院)4 楼 8205 室 325000

Tel: +86 577 8555 6055



SHAH01215411 **Test Report** Number:

Tests Conducted

Clause	Requirement	Result		
7.1.5	5 Resistance to ageing			
7.1.5.1	Stability at an elevated temperature			
7.1.5.2	Resistance to ultraviolet radiation (oculars only)	Р		
7.1.6	Resistance to corrosion	Р		
7.1.7	Resistance to ignition	Р		
7.2	Particular requirements			
7.2.1	Protection against optical radiation	NA		
7.2.2	Protection against high-speed particles	NR		
7.2.3	Protection against molten metals and hot solids	NA		
7.2.4	Protection against droplets and splashes of liquids	NA		
7.2.5	Protection against large dust particles	NA		
7.2.6	Protection against gases and fine dust particles	NA		
7.2.7	Protection against short circuit electric arc	NA		
7.2.8	Lateral Protection	NR		
7.3	Optional requirements			
7.3.1	Resistance to surface damage by fine particles	NA (No claim)		
7.3.2	Resistance to fogging of oculars	NA (No claim)		
7.3.3	Oculars with enhanced reflectance in the infrared	NA (No claim)		
7.3.4	Protection against high speed particles at extremes of temperature	NA (No claim)		
9	Marking	#1 (Note 3)		
10	Information supplied by the manufacturer	#2		

Abbreviation: P = Pass; NA = Not Applicable;

Test data:

7.1.2.1 Spherical, astigmatic and prismatic refractive powers

Optical power		Left ocular	Right ocular	<u>Limit</u> Optical class			
					1	2	3
Spherical power (m ⁻¹)		0.00	+0.01	±0.06	±0.12	+0.12 -0.25	
Astigmatic power (m ⁻¹)		0.00	0.00	≤ 0.06	≤ 0.12	≤ 0.25	
Prismatic power Difference Cm/m	Horizontal	Base out			≤ 0.75	≤ 1.00	≤ 1.00
	Base in	0.05		≤ 0.25	≤ 0.25	≤ 0.25	
	Vert	ical	0.	00	≤ 0.25	≤ 0.25	≤ 0.25

The samples satisfied the requirements for optical class 1.

To be continued





SHAH01215411 **Test Report** Number:

Tests Conducted

7.1.2.2 Transmittance

Dange	Transmitt	Deguirement	
Range	Left ocular	Right ocular	<u>Requirement</u>
380 - 780nm (T _V)	91.54	92.00	≥ 74.4%

7.1.2.3 Diffusion of light

The reduced luminous Coefficient	Left ocular	0.16	Requirement
(cd.m ⁻² /lx)	Right ocular	0.20	≤ 0.75 cd.m ⁻² /lx

7.1.5.2 Resistance to ultraviolet radiation

Relative change in luminous transmittance after	Left ocular	+0.4	Requirement +5 %
irradiation (%)	Right ocular	-1.9	±5 % (17.8% ≤ T _V ≤ 100%)
			_

The reduced luminous coefficient	Left ocular	0.08	Requirement
(cd.m ⁻² /lx)	Right ocular	0.11	$\leq 0.75 \text{ cd.m}^{-2}/\text{lx}$

Abbreviation:

- \geq = More than or equal to
- \leq = Less than or equal to

Remarks:

#1 - Eye-protectors in which the frame and ocular form a single unit shall be marked on the frame.

The marking shall comprise the full ocular marking, a hyphen, the number of this standard and then any appropriate symbols for field of use and level of impact.

The following example illustrate the principle defined above:

Single unit eye-protector with infrared filter effect resistant to low energy impact, resistant to adherence of molten metal and penetration of hot solids, with the frame offering protection against liquids, molten metals and hot solids and being resistant to low energy impact.

Code number for infra-red filters Shade number Identification of the manufacturer Optical class Symbol for low energy impact Symbol for molten metals and hot solids The number of this standard Symbol for liquids Symbol for molten metals and hot solids

Symbol for low energy impact

To be continued



Tel: +86 577 8555 6055

Fax: +86 577 8881 2119 www.intertek.com www.intertek.com.cn 学院)4 楼 8205 室 325000



Test Report SHAH01215411 Number:

Tests Conducted

#2 - The manufacturer shall provide with each eve-protector, replacement ocular and replacement frame at least the following information:

- name and address of the manufacturer;
- the number of this standard; (b)
- the eye-protector model identification; (c)
- (d)instructions for storage, use and maintenance;
- specific instructions for cleaning and disinfection; (e)
- details of the field of use, protection capabilities and performance characteristics; (f)
- (g) details of suitable accessories and spare parts. Instructions for fitting shall be included with the original eyeprotector and/or with the spare part or accessory; the obsolescence deadline or period of obsolescence, if applicable, for the complete eye-protector and/or
- (h) component parts;
- the type of packaging suitable for transport, if applicable;
- the significance of the marking on the frame and the ocular; (j)
- (k) a warning that optical class 3 oculars are not intended for long term use, if applicable;
- a warning concerning the compatibility of marking (see notes (4), (5) and (6) to Table 12);
- (m) a warning that materials which may come into contact with the wearer's skin could cause allergic reactions to susceptible individuals;
- a warning that scratched or damaged oculars should be replaced; (n)
- a warning that eye-protectors against high speed particles worn over standard ophthalmic spectacles may (o) transmit impacts, thus creating a hazard to the wearer;
- a note to instruct that if protection against high speed particles at extremes of temperature is required then (p) the selected eye-protector should be marked with the letter T immediately after the impact letter, i.e. FT, BT or AT. If the impact letter is not followed by the letter T then the eye protector shall only be used against high speed particles at room temperature.

Date sample received : May 7, 2020 & May 14, 2020 & May 26,2020 Testing period : May 7, 2020 To May 28, 2020

To be continued



学院)4楼 8205室 325000

Fax: +86 577 8881 2119 www.intertek.com www.intertek.com.cn

Tel: +86 577 8555 6055



SHAH01215411 **Test Report** Number:

Tests Conducted



End of report

This report is made solely on the basis of your instructions and/or information and materials supplied by you. It is not intended to be a recommendation for any particular course of action. Intertek does not accept a duty of care or any other responsibility to any person other than the Client in respect of this report and only accepts liability to the Client insofar as is expressly contained in the terms and conditions governing Intertek's provision of services to you. Intertek makes no warranties or representations either express or implied with respect to this report save as provided for in those terms and conditions. We have aimed to conduct the Review on a diligent and careful basis and we do not accept any liability to you for any loss arising out of or in connection with this report, in contract, tort, by statute or otherwise, except in the event of our gross negligence or wilful misconduct.

This report shall not be reproduced except in full, without written approval of the laboratory.

Tel: +86 577 8555 6055