

# SAFETY DATA SHEET

Based upon Regulation (EC) No 1907/2006, as amended by Regulation (EU) No 2020/878

## Fusion Mineral Paint - colour group B

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

**Product name** : Fusion Mineral Paint - colour group B  
**Synonyms** : Ash; Bayberry; Enchanted Echinacea; Midnight Blue; Mustard; Park Bench; Pressed Fern; Tuscan Orange; Twilight Geranium  
**Registration number REACH** : Not applicable (mixture)  
**Product type REACH** : Mixture

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

##### 1.2.1 Relevant identified uses

Paint

##### 1.2.2 Uses advised against

No uses advised against known

#### 1.3. Details of the supplier of the safety data sheet

##### Supplier of the safety data sheet

OLD RED BARN BV  
Scheppersstraat 21  
2200 Herentals  
België  
+32 465 00 86 84  
info@oldredbarn.be

#### 1.4. Emergency telephone number

24h/24h :  
+32 473 23 09 91

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

Not classified as dangerous according to the criteria of Regulation (EC) No 1272/2008

#### 2.2. Label elements

Not classified as dangerous according to the criteria of Regulation (EC) No 1272/2008

##### Supplemental information

EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

#### 2.3. Other hazards

No other hazards known

### SECTION 3: Composition/information on ingredients

#### 3.1. Substances

Not applicable

#### 3.2. Mixtures

Name REACH Registration No	CAS No EC No	Conc. (C)	Classification according to CLP	Note	Remark	M-factors and ATE
silicon dioxide	7631-86-9 231-545-4	C > 1 %		(2)	Constituent	
titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm] 01-2119489379-17	13463-67-7 236-675-5	C > 1%	Carc. 2; H351	(1)(2)	Constituent	
Carbon black	1333-86-4 215-609-9	C > 1 %		(25)(2)	Constituent	

(1) For H- and EUH-statements in full: see section 16  
(2) Substance with a Community workplace exposure limit  
(25) Concentration of Carbon black is only > 1 % in the colour: Ash

Created by: Brandweerinformatiecentrum voor gevaarlijke stoffen vzw (BIG)  
Technische Schoolstraat 43 A, B-2440 Geel  
<http://www.big.be>  
© BIG vzw

Publication date: 2021-02-02

Revision number: 0000

BIG number: 66748

1 / 11

878-17528-016-en

# Fusion Mineral Paint - colour group B

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

#### General:

If you feel unwell, consult a doctor/medical service.

#### After inhalation:

Remove victim into fresh air. In case of respiratory problems, consult a doctor/medical service.

#### After skin contact:

If possible, wipe up/dry remove chemical. Then rinse/shower immediately with (lukewarm) water.

#### After eye contact:

Rinse immediately with (lukewarm) water. Remove contact lenses, if present and easy to do. Continue rinsing. If irritation persists, consult a doctor/medical service.

#### After ingestion:

Rinse mouth with water. If you feel unwell, consult a doctor/medical service. Do not wait for symptoms to occur to consult Poison Center.

### 4.2. Most important symptoms and effects, both acute and delayed

#### 4.2.1 Acute symptoms

##### After inhalation:

No effects known.

##### After skin contact:

No effects known.

##### After eye contact:

No effects known.

##### After ingestion:

No effects known.

#### 4.2.2 Delayed symptoms

No effects known.

### 4.3. Indication of any immediate medical attention and special treatment needed

If applicable and available it will be listed below.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

#### 5.1.1 Suitable extinguishing media:

Small fire: Quick-acting ABC powder extinguisher, Quick-acting BC powder extinguisher, Quick-acting class B foam extinguisher, Quick-acting CO2 extinguisher.  
Major fire: Class B foam (alcohol-resistant), Water spray if puddle cannot expand.

#### 5.1.2 Unsuitable extinguishing media:

Small fire: Water (quick-acting extinguisher, reel); risk of puddle expansion.  
Major fire: Water; risk of puddle expansion.

### 5.2. Special hazards arising from the substance or mixture

Upon combustion CO and CO2 are formed and formation of metal oxides.

### 5.3. Advice for firefighters

#### 5.3.1 Instructions:

No specific fire-fighting instructions required.

#### 5.3.2 Special protective equipment for fire-fighters:

Gloves (EN 374). Protective clothing (EN 14605 or EN 13034). Heat/fire exposure: self-contained breathing apparatus (EN 136 + EN 137).

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

No naked flames.

#### 6.1.1 Protective equipment for non-emergency personnel

See section 8.2

#### 6.1.2 Protective equipment for emergency responders

Gloves (EN 374). Protective clothing (EN 14605 or EN 13034).

##### Suitable protective clothing

See section 8.2

### 6.2. Environmental precautions

Contain released product. Plug the leak, cut off the supply.

### 6.3. Methods and material for containment and cleaning up

Take up liquid spill into inert absorbent material. Scoop absorbed substance into closing containers. Clean contaminated surfaces with an excess of water. Wash clothing and equipment after handling.

### 6.4. Reference to other sections

See section 13.

Publication date: 2021-02-02

# Fusion Mineral Paint - colour group B

## SECTION 7: Handling and storage

The information in this section is a general description. If applicable and available, exposure scenarios are attached in annex. Always use the relevant exposure scenarios that correspond to your identified use.

### 7.1. Precautions for safe handling

Keep away from naked flames/heat. In finely divided state: use spark-/explosionproof appliances. Finely divided: keep away from ignition sources/sparks. Observe normal hygiene standards. Keep container tightly closed.

### 7.2. Conditions for safe storage, including any incompatibilities

#### 7.2.1 Safe storage requirements:

Meet the legal requirements.

#### 7.2.2 Keep away from:

Heat sources.

#### 7.2.3 Suitable packaging material:

Plastics.

#### 7.2.4 Non suitable packaging material:

No data available

### 7.3. Specific end use(s)

If applicable and available, exposure scenarios are attached in annex. See information supplied by the manufacturer.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### 8.1.1 Occupational exposure

##### a) Occupational exposure limit values

If limit values are applicable and available these will be listed below.

##### Belgium

Carbone (noir de)	Time-weighted average exposure limit 8 h	3 mg/m <sup>3</sup>
Silices amorphes : silice fondue SiO <sub>2</sub> (poussières alvéolaires)	Time-weighted average exposure limit 8 h	0.1 mg/m <sup>3</sup>
Silices amorphes : terre de diatomées, non calcinées (fraction inhalable)	Time-weighted average exposure limit 8 h	10 mg/m <sup>3</sup>
Silices amorphes : fumées (fraction alvéolaire)	Time-weighted average exposure limit 8 h	2 mg/m <sup>3</sup>
Titane (dioxyde de)	Time-weighted average exposure limit 8 h	10 mg/m <sup>3</sup>

##### France

Noir de carbone	Time-weighted average exposure limit 8 h (VL: Valeur non réglementaire indicative)	3.5 mg/m <sup>3</sup>
Titane (dioxyde de), en Ti	Time-weighted average exposure limit 8 h (VL: Valeur non réglementaire indicative)	10 mg/m <sup>3</sup>

##### Germany

Kieselsäuren, amorphe	Time-weighted average exposure limit 8 h (TRGS 900)	4 mg/m <sup>3</sup>
-----------------------	---	---------------------

##### UK

Carbon black	Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))	3.5 mg/m <sup>3</sup>
	Short time value (Workplace exposure limit (EH40/2005))	7 mg/m <sup>3</sup>
Silica, amorphous inhalable dust	Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))	6 mg/m <sup>3</sup>
Silica, amorphous respirable dust	Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))	2.4 mg/m <sup>3</sup>
Titanium dioxide respirable	Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))	4 mg/m <sup>3</sup>
Titanium dioxide total inhalable	Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))	10 mg/m <sup>3</sup>

##### USA (TLV-ACGIH)

Carbon black	Time-weighted average exposure limit 8 h (TLV - Adopted Value)	3 mg/m <sup>3</sup> (I)
Titanium dioxide	Time-weighted average exposure limit 8 h (TLV - Adopted Value)	10 mg/m <sup>3</sup>

(I): Inhalable fraction

##### b) National biological limit values

If limit values are applicable and available these will be listed below.

#### 8.1.2 Sampling methods

Product name	Test	Number
Carbon Black	NIOSH	5000
Carbon Black	NIOSH	5100
Carbon Black	OSHA	ID 196
Silica, Amorphous (Respirable)	NIOSH	7501
TiO <sub>2</sub>	NIOSH	7302

Publication date: 2021-02-02

# Fusion Mineral Paint - colour group B

Product name	Test	Number
TiO2	NIOSH	7304

## 8.1.3 Applicable limit values when using the substance or mixture as intended

If limit values are applicable and available these will be listed below.

## 8.1.4 Threshold values

### DNEL/DMEL - Workers

silicon dioxide

Effect level (DNEL/DMEL)	Type	Value	Remark
DNEL	Long-term systemic effects inhalation	4 mg/m <sup>3</sup>	

Carbon black

Effect level (DNEL/DMEL)	Type	Value	Remark
DNEL	Long-term local effects inhalation	0.5 mg/m <sup>3</sup>	

### PNEC

Carbon black

Compartment	Value	Remark
Fresh water	1 mg/l	
Marine water	0.1 mg/l	
Fresh water (intermittent releases)	10 mg/l	

## 8.1.5 Control banding

If applicable and available it will be listed below.

## 8.2. Exposure controls

The information in this section is a general description. If applicable and available, exposure scenarios are attached in annex. Always use the relevant exposure scenarios that correspond to your identified use.

### 8.2.1 Appropriate engineering controls

Keep away from naked flames/heat. In finely divided state: use spark-/explosionproof appliances. Finely divided: keep away from ignition sources/sparks. Measure the concentration in the air regularly. Carry operations in the open/under local exhaust/ventilation or with respiratory protection.

### 8.2.2 Individual protection measures, such as personal protective equipment

Observe normal hygiene standards. Do not eat, drink or smoke during work.

#### a) Respiratory protection:

Respiratory protection not required in normal conditions. Dust production: dust mask with filter type P1.

#### b) Hand protection:

Protective gloves against chemicals (EN 374).

#### c) Eye protection:

Eye protection not required in normal conditions.

#### d) Skin protection:

Protective clothing (EN 14605 or EN 13034).

### 8.2.3 Environmental exposure controls:

See sections 6.2, 6.3 and 13

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical form	Liquid
Odour	Mild odour
Odour threshold	No data available in the literature
Colour	Variable in colour, depending on the composition
Particle size	Not applicable (liquid)
Explosion limits	No data available in the literature
Flammability	Not classified as flammable
Log Kow	Not applicable (mixture)
Dynamic viscosity	350 mPa.s - 500 mPa.s
Kinematic viscosity	No data available in the literature
Melting point	0 °C
Boiling point	100 °C
Relative vapour density	No data available in the literature
Vapour pressure	No data available in the literature
Solubility	Water ; miscible
Relative density	1.02 - 1.67
Absolute density	1020 kg/m <sup>3</sup> - 1670 kg/m <sup>3</sup>
Decomposition temperature	No data available in the literature
Auto-ignition temperature	No data available in the literature
Flash point	No data available in the literature
pH	8.4 - 9.2

### 9.2. Other information

No data available

Publication date: 2021-02-02

# Fusion Mineral Paint - colour group B

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

Heating increases the fire hazard.

### 10.2. Chemical stability

Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

No data available.

### 10.4. Conditions to avoid

#### Precautionary measures

Keep away from naked flames/heat. In finely divided state: use spark-/explosionproof appliances. Finely divided: keep away from ignition sources/sparks.

### 10.5. Incompatible materials

No data available.

### 10.6. Hazardous decomposition products

Upon combustion CO and CO<sub>2</sub> are formed and formation of metal oxides.

## SECTION 11: Toxicological information

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### 11.1.1 Test results

#### Acute toxicity

##### Fusion Mineral Paint - colour group B

No (test)data on the mixture available

Judgement is based on the relevant ingredients

##### silicon dioxide

Route of exposure	Parameter	Method	Value	Exposure time	Species	Value determination	Remark
Oral	LD50		> 10000 mg/kg		Rat		
Dermal	LD50		> 5000 mg/kg		Rabbit		

##### titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm]

Route of exposure	Parameter	Method	Value	Exposure time	Species	Value determination	Remark
Oral	LD50	OECD 401	> 2000 mg/kg bw		Rat (male / female)	Experimental value	
Dermal						Data waiving	
Inhalation (dust)	LC50	OECD 403	> 5.09 mg/l	4 h	Rat (male)	Experimental value	

##### Carbon black

Route of exposure	Parameter	Method	Value	Exposure time	Species	Value determination	Remark
Oral	LD50	Equivalent to OECD 401	> 10000 mg/kg		Rat (male / female)	Experimental value	
Dermal						Data waiving	
Inhalation (dust)	LC50	Equivalent to OECD 403	> 4.6 mg/l air	4 h	Rat	Experimental value	

#### Conclusion

Not classified for acute toxicity

#### Corrosion/irritation

##### Fusion Mineral Paint - colour group B

No (test)data on the mixture available

Judgement is based on the relevant ingredients

##### titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm]

Route of exposure	Result	Method	Exposure time	Time point	Species	Value determination	Remark
Eye	Not irritating	OECD 405		1; 24; 48; 72 hours	Rabbit	Experimental value	
Skin	Not irritating	Equivalent to OECD 404	4 h	48 hours	Rabbit	Experimental value	

Publication date: 2021-02-02

# Fusion Mineral Paint - colour group B

## Carbon black

Route of exposure	Result	Method	Exposure time	Time point	Species	Value determination	Remark
Eye	Not irritating	OECD 405		24; 48; 72 hrs; 4 days	Rabbit	Experimental value	
Skin	Not irritating	Equivalent to OECD 404	4 h	1; 24; 48; 72 hours	Rabbit	Experimental value	

## Conclusion

Not classified as irritating to the respiratory system  
 Not classified as irritating to the skin  
 Not classified as irritating to the eyes

## Respiratory or skin sensitisation

### Fusion Mineral Paint - colour group B

No (test)data on the mixture available

Judgement is based on the relevant ingredients

titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter  $\leq 10 \mu\text{m}$ ]

Route of exposure	Result	Method	Exposure time	Observation time point	Species	Value determination	Remark
Skin	Not sensitizing	Equivalent to OECD 429			Mouse (female)	Experimental value	
Inhalation (dust)	Not sensitizing				Mouse (female)	Experimental value	

## Carbon black

Route of exposure	Result	Method	Exposure time	Observation time point	Species	Value determination	Remark
Skin	Not sensitizing	OECD 406			Hamster (female)	Experimental value	
Inhalation	Not sensitizing				Mouse (female)	Experimental value	

## Conclusion

Not classified as sensitizing for inhalation  
 Not classified as sensitizing for skin

## Specific target organ toxicity

### Fusion Mineral Paint - colour group B

No (test)data on the mixture available

Judgement is based on the relevant ingredients

titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter  $\leq 10 \mu\text{m}$ ]

Route of exposure	Parameter	Method	Value	Organ	Effect	Exposure time	Species	Value determination
Oral (stomach tube)	NOAEL	OECD 408	> 1000 mg/kg bw/day		No effect	90 day(s)	Rat (male / female)	Experimental value
Dermal								Data waiving

## Carbon black

Route of exposure	Parameter	Method	Value	Organ	Effect	Exposure time	Species	Value determination
Oral (diet)	Dose level	Equivalent to OECD 452	2050 mg/kg bw/day		No effect		Rat (female)	Experimental value
Dermal	NOEL		20 %		No effect	12 month(s) - 18 month(s)	Mouse (male / female)	Experimental value
Inhalation (aerosol)	NOEC	Subchronic toxicity test	1 mg/m <sup>3</sup> air	Lungs	No effect	13 weeks (6h / day, 5 days / week)	Rat (female)	Experimental value
Inhalation (aerosol)	LOEC	Subchronic toxicity test	7 mg/m <sup>3</sup> air	Lungs	Pneumonia	13 weeks (6h / day, 5 days / week)	Rat (female)	Experimental value

## Conclusion

Not classified for subchronic toxicity

## Mutagenicity (in vitro)

### Fusion Mineral Paint - colour group B

No (test)data on the mixture available

Judgement is based on the relevant ingredients

Publication date: 2021-02-02

# Fusion Mineral Paint - colour group B

titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter  $\leq 10 \mu\text{m}$ ]

Result	Method	Test substrate	Effect	Value determination	Remark
Negative with metabolic activation, negative without metabolic activation	OECD 473	Chinese hamster ovary (CHO)		Experimental value	
Negative with metabolic activation, negative without metabolic activation	OECD 471	Bacteria (S.typhimurium)		Experimental value	

Carbon black

Result	Method	Test substrate	Effect	Value determination	Remark
Negative with metabolic activation, negative without metabolic activation	OECD 471	Bacteria (S.typhimurium)	No effect	Experimental value	
Negative with metabolic activation, negative without metabolic activation	OECD 479	Chinese hamster ovary (CHO)	No effect	Experimental value	
Negative with metabolic activation, negative without metabolic activation	OECD 476	Mouse (lymphoma L5178Y cells)	No effect	Experimental value	

## Mutagenicity (in vivo)

Fusion Mineral Paint - colour group B

No (test)data on the mixture available

Judgement is based on the relevant ingredients

titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter  $\leq 10 \mu\text{m}$ ]

Result	Method	Exposure time	Test substrate	Organ	Value determination
Negative (Oral (stomach tube))	OECD 474		Mouse (male / female)		Experimental value

Carbon black

Result	Method	Exposure time	Test substrate	Organ	Value determination
Ambiguous (Inhalation (dust))		13 weeks (6h / day, 5 days / week)	Rat (female)		Experimental value

## Conclusion

Not classified for mutagenic or genotoxic toxicity

## Carcinogenicity

Fusion Mineral Paint - colour group B

No (test)data on the mixture available

Judgement is based on the relevant ingredients

The classification as a carcinogen by inhalation applies only to mixtures in powder form containing 1 % or more of titanium dioxide which is in the form of or incorporated in particles with aerodynamic diameter  $\leq 10 \mu\text{m}$ .

titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter  $\leq 10 \mu\text{m}$ ]

Route of exposure	Parameter	Method	Value	Exposure time	Species	Effect	Organ	Value determination
Inhalation (dust)	NOAEC	OECD 453	5 mg/m <sup>3</sup> air	104 weeks (6h / day, 5 days / week)	Rat (male / female)	No carcinogenic effect	Lungs	Experimental value
Oral (diet)	NOEL	Carcinogenic toxicity study	50000 ppm	103 weeks (7 days / week)	Rat (male / female)	No carcinogenic effect		Experimental value

Carbon black

Route of exposure	Parameter	Method	Value	Exposure time	Species	Effect	Organ	Value determination
Inhalation (aerosol)	LOAEC	Equivalent to OECD 451	7.5 mg/m <sup>3</sup> air - 12 mg/m <sup>3</sup> air	104 weeks (5 days / week)	Rat (female)	Carcinogenicity		Experimental value
Dermal	NOEC	Equivalent to OECD 451	50 %	9 month(s) - 24 month(s)	Mouse	No carcinogenic effect		Experimental value
Oral (diet)	NOEC		52 mg/kg bw/day	104 week(s)	Rat (female)	No carcinogenic effect		Experimental value

## Conclusion

Not classified for carcinogenicity

## Reproductive toxicity

Fusion Mineral Paint - colour group B

No (test)data on the mixture available

Judgement is based on the relevant ingredients

Publication date: 2021-02-02

# Fusion Mineral Paint - colour group B

titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter  $\leq 10 \mu\text{m}$ ]

	Parameter	Method	Value	Exposure time	Species	Effect	Organ	Value determination
Developmental toxicity (Oral (stomach tube))	NOAEL	OECD 414	1000 mg/kg bw/day	2 weeks (7 days / week)	Rat	No effect		Experimental value
Maternal toxicity (Oral (stomach tube))	NOAEL	OECD 414	1000 mg/kg bw/day	2 weeks (7 days / week)	Rat	No effect		Experimental value

Carbon black

	Parameter	Method	Value	Exposure time	Species	Effect	Organ	Value determination
Developmental toxicity (Inhalation (aerosol))	NOEC	Developmental toxicity study	41.7 mg/m <sup>3</sup> air	11 days (gestation, daily)	Mouse	No effect		Experimental value
Maternal toxicity (Inhalation (aerosol))	LOAEC	Developmental toxicity study	41.7 mg/m <sup>3</sup> air	11 days (gestation, daily)	Mouse	Lung tissue affection/degeneration	Lungs	Experimental value

## Conclusion

Not classified for reprotoxic or developmental toxicity

## Toxicity other effects

Fusion Mineral Paint - colour group B

No (test)data on the mixture available

## Chronic effects from short and long-term exposure

Fusion Mineral Paint - colour group B

No effects known.

## 11.2. Information on other hazards

No evidence of endocrine disrupting properties

## SECTION 12: Ecological information

### 12.1. Toxicity

Fusion Mineral Paint - colour group B

No (test)data on the mixture available

Judgement of the mixture is based on the relevant ingredients

silicon dioxide

	Parameter	Method	Value	Duration	Species	Test design	Fresh/salt water	Value determination
Acute toxicity fishes	LC50		> 10000 mg/l	96 h	Brachydanio rerio			Literature study
Acute toxicity crustacea	EC50		> 10000 mg/l	24 h	Daphnia magna			Literature study
Toxicity algae and other aquatic plants	EC50		440 mg/l	72 h	Selenastrum capricornutum			Literature study; Growth rate

titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter  $\leq 10 \mu\text{m}$ ]

	Parameter	Method	Value	Duration	Species	Test design	Fresh/salt water	Value determination
Acute toxicity fishes	LC50		> 1000 mg/l		Pisces		Fresh water	
Acute toxicity crustacea	EC50		> 1000 mg/l		Invertebrata		Fresh water	
Toxicity algae and other aquatic plants	EC50	OECD 201	> 100 mg/l	72 h	Pseudokirchneriella subcapitata	Static system	Fresh water	Experimental value; Growth rate
	NOEC	OECD 201	$\geq 100$ mg/l	72 h	Pseudokirchneriella subcapitata	Static system	Fresh water	Experimental value; Growth rate

Carbon black

	Parameter	Method	Value	Duration	Species	Test design	Fresh/salt water	Value determination
Acute toxicity fishes	LC50	OECD 203	> 1000 mg/l	96 h	Danio rerio	Semi-static system	Fresh water	Experimental value; Lethal
Acute toxicity crustacea	EC50	OECD 202	> 5600 mg/l	24 h	Daphnia magna	Static system	Fresh water	Experimental value; Locomotor effect
Toxicity algae and other aquatic plants	ErC50	OECD 201	> 10000 mg/l	72 h	Desmodesmus subspicatus	Static system	Fresh water	Experimental value; Nominal concentration
Toxicity aquatic micro-organisms	EC10	TTC-test	800 mg/l	3 h	Activated sludge	Static system	Fresh water	Experimental value; Enzyme effect

## Conclusion

Not classified as dangerous for the environment according to the criteria of Regulation (EC) No 1272/2008

Publication date: 2021-02-02



# Fusion Mineral Paint - colour group B

## 12.2. Persistence and degradability

### Water

No test data of component(s) available

## 12.3. Bioaccumulative potential

Fusion Mineral Paint - colour group B

### Log Kow

Method	Remark	Value	Temperature	Value determination
	Not applicable (mixture)			

silicon dioxide

### Log Kow

Method	Remark	Value	Temperature	Value determination
	No data available			

titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter  $\leq 10 \mu\text{m}$ ]

### Log Kow

Method	Remark	Value	Temperature	Value determination
	No data available			

Carbon black

### Log Kow

Method	Remark	Value	Temperature	Value determination
	No data available			

## Conclusion

No test data of component(s) available

## 12.4. Mobility in soil

Contains component(s) that adsorb(s) into the soil

## 12.5. Results of PBT and vPvB assessment

Due to insufficient data no statement can be made whether the component(s) fulfil(s) the criteria of PBT and vPvB according to Annex XIII of Regulation (EC) No 1907/2006.

## 12.6. Endocrine disrupting properties

No evidence of endocrine disrupting properties

## 12.7. Other adverse effects

Fusion Mineral Paint - colour group B

### Greenhouse gases

None of the known components is included in the list of fluorinated greenhouse gases (Regulation (EU) No 517/2014)

### Ozone-depleting potential (ODP)

Not classified as dangerous for the ozone layer (Regulation (EC) No 1005/2009)

## SECTION 13: Disposal considerations

The information in this section is a general description. If applicable and available, exposure scenarios are attached in annex. Always use the relevant exposure scenarios that correspond to your identified use.

## 13.1. Waste treatment methods

### 13.1.1 Provisions relating to waste

#### European Union

Can be considered as non hazardous waste according to Directive 2008/98/EC, as amended by Regulation (EU) No 1357/2014 and Regulation (EU) No 2017/997.

Waste material code (Directive 2008/98/EC, Decision 2000/0532/EC).

08 01 12 (wastes from MFSU and removal of paint and varnish: waste paint and varnish other than those mentioned in 08 01 11).

Depending on branch of industry and production process, also other waste codes may be applicable.

### 13.1.2 Disposal methods

Remove waste in accordance with local and/or national regulations. Do not discharge into drains or the environment. Dispose of at authorized waste collection point.

### 13.1.3 Packaging/Container

#### European Union

Waste material code packaging (Directive 2008/98/EC).

15 01 02 (plastic packaging).

## SECTION 14: Transport information

### Road (ADR), Rail (RID), Inland waterways (ADN), Sea (IMDG/IMSBC), Air (ICAO-TI/IATA-DGR)

#### 14.1. UN number

Transport	Not subject
-----------	-------------

#### 14.2. UN proper shipping name

#### 14.3. Transport hazard class(es)

Hazard identification number	
Class	

Publication date: 2021-02-02

# Fusion Mineral Paint - colour group B

Classification code	
14.4. Packing group	
Packing group	
Labels	
14.5. Environmental hazards	
Environmentally hazardous substance mark	no
14.6. Special precautions for user	
Special provisions	
Limited quantities	
14.7. Maritime transport in bulk according to IMO instruments	
Annex II of MARPOL 73/78	Not applicable, based on available data

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### European legislation:

VOC content Directive 2010/75/EU

VOC content	Remark
0.05785 %	

VOC content Directive 2004/42/EC

Maximum value	EC limit value	Category	Subcategory	Notation
0.810 g/l	130 g/l	IIA	d: Interior/exterior trim and cladding paints for wood and metal	2004/42/IIA(d)(130)0.810

#### National legislation Belgium

Fusion Mineral Paint - colour group B

No data available

#### National legislation The Netherlands

Fusion Mineral Paint - colour group B

Waterbezwaarlijkheid	B (4); Algemene Beoordelingsmethodiek (ABM)
----------------------	---

#### National legislation France

Fusion Mineral Paint - colour group B

No data available

#### National legislation Germany

Fusion Mineral Paint - colour group B

WGK	1; Verordnung über Anlagen zum Umgang mit wassergefährdenden Stoffen (AwSV) - 18. April 2017
-----	--

silicon dioxide

TA-Luft	5.2.1
TRGS900 - Risiko der Fruchtschädigung	Kieselsäuren, amorphe; Y; Risiko der Fruchtschädigung braucht bei Einhaltung des Arbeitsplatzgrenzwertes und des biologischen Grenzwertes nicht befürchtet zu werden

titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter  $\leq 10 \mu\text{m}$ ]

TA-Luft	5.2.1
---------	-------

Carbon black

TA-Luft	5.2.1
---------	-------

#### National legislation United Kingdom

Fusion Mineral Paint - colour group B

No data available

#### Other relevant data

Fusion Mineral Paint - colour group B

No data available

silicon dioxide

IARC - classification	3; Silica
-----------------------	-----------

titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter  $\leq 10 \mu\text{m}$ ]

TLV - Carcinogen	Titanium dioxide; A4
IARC - classification	2B; Titanium dioxide

Carbon black

TLV - Carcinogen	Carbon black; A3
IARC - classification	2B; Carbon black

### 15.2. Chemical safety assessment

No chemical safety assessment has been conducted for the mixture.

Publication date: 2021-02-02

# Fusion Mineral Paint - colour group B

## SECTION 16: Other information

### Full text of any H- and EUH-statements referred to under section 3:

H351 Suspected of causing cancer if inhaled.

EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

(*)	INTERNAL CLASSIFICATION BY BIG
ADI	Acceptable daily intake
AOEL	Acceptable operator exposure level
ATE	Acute Toxicity Estimate
CLP (EU-GHS)	Classification, labelling and packaging (Globally Harmonised System in Europe)
DMEL	Derived Minimal Effect Level
DNEL	Derived No Effect Level
EC50	Effect Concentration 50 %
ErC50	EC50 in terms of reduction of growth rate
LC50	Lethal Concentration 50 %
LD50	Lethal Dose 50 %
NOAEL	No Observed Adverse Effect Level
NOEC	No Observed Effect Concentration
OECD	Organisation for Economic Co-operation and Development
PBT	Persistent, Bioaccumulative & Toxic
PNEC	Predicted No Effect Concentration
STP	Sludge Treatment Process
vPvB	very Persistent & very Bioaccumulative

The information in this safety data sheet is based on data and samples provided to BIG. The sheet was written to the best of our ability and according to the state of knowledge at that time. The safety data sheet only constitutes a guideline for the safe handling, use, consumption, storage, transport and disposal of the substances/preparations/mixtures mentioned under point 1. New safety data sheets are written from time to time. Only the most recent versions may be used. Unless indicated otherwise word for word on the safety data sheet, the information does not apply to substances/preparations/mixtures in purer form, mixed with other substances or in processes. The safety data sheet offers no quality specification for the substances/preparations/mixtures in question. Compliance with the instructions in this safety data sheet does not release the user from the obligation to take all measures dictated by common sense, regulations and recommendations or which are necessary and/or useful based on the real applicable circumstances. BIG does not guarantee the accuracy or exhaustiveness of the information provided and cannot be held liable for any changes by third parties. This safety data sheet is only to be used within the European Union, Switzerland, Iceland, Norway and Liechtenstein. Any use outside of this area is at your own risk. Use of this safety data sheet is subject to the licence and liability limiting conditions as stated in your BIG licence agreement or when this is failing the general conditions of BIG. All intellectual property rights to this sheet are the property of BIG and its distribution and reproduction are limited. Consult the mentioned agreement/conditions for details.

Publication date: 2021-02-02