

PB-Li 12-90 D

Fits under the seat console
- also for VW Bus



POWER BOOSTER[®]

high power **battery series**

LFP LiFePO₄
LITHIUM BATTERY



ELECTRICAL SPECIFICATIONS

Nominal Voltage	12,8 V
Nominal Capacity	90 Ah
Open Circuit Volt. @ 100%	13,6 V
Energy	1152 Wh
Internal Resistance	≤ 50 mΩ
Self Discharge	< 3 % /month

DISCHARGING

Max. cont. Discharge Current	100 A
Peak Discharge Current	300 A (3 s)
BMS Discharge Cut-Off	150 A (30s)
Rec. Low Voltage Cut-Off	11 V
BMS Cut-Off	10,4 V
Reconnect Voltage	11,2 V

TEMPERATURES

Discharge Temperature	-20 to +60°C
Charge Temperature	0 to +60 °C
Storage Temperature	0 to +60 °C

COMMUNICATION

Bluetooth 4.0 with App Android/iOS

MECHANICAL SPECIFICATIONS

Dimensions (LxWxH)	318 x 176 x188 mm
Weight	11,8 kg
Terminal Type	Autom. Post
Case Material	ABS
Enclosure Protection	IP 56
Cell Type / Chemistry	Cylindrical/LiFePO ₄

CHARGING

Recomm. Charge Current	20 A
Max. Charge Current	100 A
Recomm. Charge Voltage	14,6 V
BMS Voltage Cut-Off	15 V

COMPLIANCE

Certificates	CE UN38.3 UL1642 & IEC2133
Shipping Classification	UN 3480, Class 9



A. Müller GmbH
Tholeyer Straße 32
D-66620 Nonnweiler-Primstal
Mail: info@batterien-mueller.de

