

Haier



Energy Gateway

- Meerdere posities voor zekeringen gereserveerd voor de Smart cube of andere belastingen
- Naadloze omschakeling naar back-up modus, voor zorgeloos energiegebruik
- Klaar voor een generator, warmtepomp of andere regelbare belastingen
- Ondersteunt zowel volledige als gedeeltelijke noodstroomvoorziening voor thuis
- 350 ms omgekeerde stroombeveiliging voor net & generator
- Ononderbroken stroomvoorziening via PV+batterij/net/generator

Energy Gateway

Gateway	HG-SS	HG-TS	Units
Grid Connection			
Grid connection type	Single phase	Three phase	
Nominal AC input / output voltage	220 / 230 / 240	380 / 400	V
Nominal AC input / output current	100	76	A
Nominal AC input / output power	22 / 23 / 24	50 / 52.6	kW
Nominal AC frequency		50 / 60	Hz
Disruption time of backup switch ¹		0	ms
AC Output to Backup port			
Nominal AC output voltage	220 / 230 / 240	380 / 400	V
Nominal AC output current	100	76	A
Nominal AC output power	22 / 23 / 24	50 / 52.6	kW
Nominal AC frequency		50 / 60	Hz
Overvoltage category		III	
Inverter Connection / EV Charger Port (optional)			
Max. number of connection	3	2	
Nominal AC voltage	220 / 230 / 240	380 / 400	V
Nominal AC input current	32	38	A
Compatible EV charger power	7	11 / 22	kW
EV charging mode	Solar boost charging, time-based charging, load balancing		
Smart Port Connection			
Generator output voltage	220 / 230 / 240	380 / 400	
Nominal input / output current	63	76	A
Nominal AC input / output power	13.8 / 14.5 / 15.1	50 / 52.6	kW
Generator 2-wire start		Supported	
General Data			
Dimensions (W / H / D)	455 / 660 / 179	510 / 750 / 179	mm
Weight	19	23	kg
Storage temperature range		-40 ~ 70	°C
Operating temperature range		-30 ~ 55	°C
Relative humidity range		0% ~ 95%	
Max. operation altitude		4000	m
Cooling	Natural convection		
Ingress protection rating	IP54		
Communication	Fast Ethernet, RS485, dry contact		
Installation method	Wall mounted		

1. This refers to the load-side disruption time, to achieve this functionality needs to be used together with Smart Cube Energy Controller and Battery. Test conditions: In the open-circuit state of the power grid, the nominal power of Smart Cube Energy Controller is higher than the total power of the home loads.