





CE

Power	30/40/48 W	Voltage	230 V
Luminous flux*	6300 lm (360°)	Colour temperature	3000/4000/6000 K
Light colour	CCT	Beam angle	120 °
Protection class	IP20		



 User manual



 Declaration of Conformity



 Photometric file

Technical data:

Product code	SLI035073CCT_PW
Power	30/40/48 W
Nominal current	210 mA
Voltage	230 V
Energy consumption	48 kWh/1000h
Frequency	50HZ Hz
Protection class	I
Power supply included	+
Power factor	0.9
Useful luminous flux*	6300 lm (360°)
Luminous flux**	3600/4800/5760 lm (360°)
Light efficiency	131 lm/W
Colour temperature	3000/4000/6000 K
Light colour	CCT
Beam angle	120 °
RA	>80
Uniformity of color SDCM max	5
Dimmable	No
Working temperature range	-20/+40 °
Lifespan	50000 h
Housing material	Aluminum/Plastic
Protection class	IP20
Colour	White
Dimension (axbxc)	595x595x35 mm
For use	Inside
Assembly method	surface mounted, recessed
Application	INT
Made in	PRC
Other	DIP SWITCH - regulowana moc oprawy ,



*Applies to the LED source used. **Luminaire luminous flux