





CE

|                  |                       |                    |               |
|------------------|-----------------------|--------------------|---------------|
| Power            | <b>14 W</b>           | Voltage            | <b>230 V</b>  |
| Luminous flux*   | <b>1700 lm (360°)</b> | Colour temperature | <b>4000 K</b> |
| Light colour     | <b>Neutral white</b>  | Beam angle         | <b>120 °</b>  |
| Protection class | <b>IP20</b>           |                    |               |



 User manual



 Declaration of Conformity



 Photometric file

**Technical data:**

|                              |                          |
|------------------------------|--------------------------|
| Product code                 | SLI045005NW_PW           |
| Power                        | 14 W                     |
| Nominal current              | 105 mA                   |
| Voltage                      | 230 V                    |
| Energy consumption           | 14 kWh/1000h             |
| Frequency                    | 50HZ Hz                  |
| Protection class             | II                       |
| Power factor                 | 0.5                      |
| Useful luminous flux*        | 1700 lm (360°)           |
| Luminous flux**              | 1500 lm (360°)           |
| Light efficiency             | 121 lm/W                 |
| Colour temperature           | 4000 K                   |
| Light colour                 | Neutral white            |
| Beam angle                   | 120 °                    |
| RA                           | 80                       |
| Uniformity of color SDCM max | 5                        |
| Dimmable                     | No                       |
| Working temperature range    | -20/+40 °                |
| Lifespan                     | 17000 h                  |
| Housing material             | PC                       |
| Protection class             | IP20                     |
| Colour                       | White                    |
| Dimension (axbxc)            | 76x580x26 mm             |
| For use                      | Inside                   |
| Assembly method              | On the ceiling/Suspended |
| Application                  | Inside                   |
| Made in                      | PRC                      |



\*Applies to the LED source used. \*\*Luminaire luminous flux