RISLONE .	
ISO 9001 CERTIFIED	

RISLONE TECHNICAL BULLETIN		
Tech Bulletin #: TB-31197-0	Page 1 of 1	
Date 1 st Issued: 15 February, 2013	Date Revised: 08, June 2018	
Rislone Radiator Stop Leak Concentrate	Part #: 31197	

RADIATOR STOP LEAK CONCENTRATE

Rislone Radiator Stop leak Concentrate is specifically designed to stop minor cooling system leaks and drops caused by normal cooling system wear and age.

Works with ALL types of antifreeze coolant and/or water.

- Stops & Seals Coolant Leaks
- Seals Leaks in Radiators, Gaskets, Heater Cores & Freeze Plugs.



DANGER: Opening cooling system while engine is hot or running may cause severe burns.

INSTRUCTIONS:

Cooling systems that are dirty or partially clogged should be flushed before usage. Shake well. Pour Stop Leak into a cool radiator. If direct access to radiator is not available, install in overflow tank. Fill radiator and overflow tank to proper level and reinstall cap. Drive / idle engine for 15 to 30 minutes. If leak continues, a second application may be required or mechanical attention is needed. Leave Rislone in the cooling system for continued protection.

DOSAGE:

One bottle treats up to 15 liters. Use ½ bottle for four cylinder engines.

Part Number:	31197
UPC Item:	0 69181 31197 8
UPC Case:	1 00 69181 31197 5
Bottle Size:	325 ml
Bottle Size (cm):	7,6 x 4,6 x 16,5
Bottle Cube:	577
Case Pack:	6 bottles
Case Size (cm):	15,5 x 14 x 17,5
Case Cube:	3846
Case Weight (kg):	2,4
Pallet:	TI 50 HI 6 Total 300
Pallet Height (cm):	110 cm