


19" Wall Housing 12U, Acoustically Insulated



Description

Acoustically high-quality insulated wall housing, basing on EFB standard wall housings
 For realisation of network projects in SoHo environments and acoustical insulation of loud, active devices like e.g. switches, router etc.
 For installation in immediate near of working places, in seminar- or conference rooms without noise pollution
 Complete inner lining with especially noise absorbers
 Attenuation (typ.) 8 .. 25 dB (frequency-dependent, see data sheet)
 Special decoupled Super-Silent fans (evacuating) in roof area
 Converted air volume 196 m³/h
 Closeable fresh air inlets in bottom
 Cable entry in bottom via noise bridge and brush
 Front door with window of certified safety glass (4 mm), lockable
 Side walls detachable, lockable, lock equal to door lock
 Paint finish RAL7035, light grey
 Delivery incl. 2 x key, 1 x power supply for the fans

All EFB housings are available as acoustical insulated type - ask your sales contact!

General data

Mounting level	Front side
Type of profile rail	L-shaped
Type of ventilation	Active
Modular spacing	482.6 mm (19 inch)

This datasheet was created automatically on 20-04-2020 . Technical changes reserved.

19" Wall Housing 12U, Acoustically Insulated

General data

With roof plate	True
With earthing	True
With front door	True
With sidewall	True
Demountable	False
Model	With permanent frame
Material	Steel
Type of surface	With powder coating
Degree of protection (IP)	IP20
Number of doors	1
Number of cartons	1

Available variants

Article no.	Title	Number of height units	Width	Height	Depth	Max. Load	RAL-number	Colour
691712.1-AK	19" Wall Housing 12U, Depth 500 mm, Acoustically Insulated, incl. Silent-Fans	12	600 mm	600 mm	500 mm	50 kg	7035	Grey Grey