



DATASHEET

19" Roll Container 15U, Acoustically Insulated, Office Design



Description

19" Network cabinet acc. to DIN41494 as roll container or undercounter housing for office environments
 High-quality acoustical insulated variant for ergonomic work, suitable for installation directly at the working place
 Attractive, stable MDF plate at the upper side enables parking of further devices (printer etc.) on the cabinet
 Use of sound insulation mats in studio technology in thickness 20, 40 und 50 mm, equal to the acoustical problem zones in cabinets

Attenuation (typ.) 8 .. 25 dB (frequency-dependent, see data sheet)

Especially decoupled, smooth running "Silent" fans at the rear wall guide the heat to outside, converted air volume 294 m³/h

Fresh air feeding from bottom-front via filter grid

Cable entry rear-sided below via sound bridge and brush

Inside 4 x 19" rails (2 front, 2 rear), depth-adjustable in 25 mm raster

Front door with window of certified safety glass (5 mm), 1-part, with turning handle and profile half-cylinder acc. to DIN18252, PHC exchangeable by customer

Rear door with 1 x latch, lock equal to door lock

Side walls detachable with 2 x latch, lock equal to door lock

Max. load 300 kg (castors) / 600 kg (leveling feet)

Dimensions (W x D x H) 600 x 800 x 900 mm

Paint finish und MDF plate RAL7035, light grey

Delivery incl. set of 4 castors (2 with brake), 2 x key, 1 x power supply for fans

All EFB housings are available as acoustical insulated type and in individual design - ask your sales contact!

This datasheet was created automatically on 20-04-2020 . Technical changes reserved.



DATASHEET

19" Roll Container 15U, Acoustically Insulated, Office Design

General data	
Mounting level	Front and rear
Type of profile rail	Crank
Type of ventilation	Active
Modular spacing	482.6 mm (19 inch)
With roof plate	True
With earthing	True
With front door	True
With sidewall	True
Demountable	False
Model	With permanent frame
Material	Steel
Type of surface	With powder coating
Degree of protection (IP)	Other
Number of doors	2

Available variants								
Article no.	Title	Number of height units	Width	Height	Depth	Max. Load	RAL-number	Colour
692615N-AK-GR	19" Roll Container 15U, 600 x 800 mm, Acoustically Insulated, Office Design	15	600 mm	900 mm	800 mm	300 kg	7035	grey

This datasheet was created automatically on 20-04-2020 . Technical changes reserved.

