

# DATASHEET

## 19" Wall Housing IP55, Glass Door, Depth 450 mm, RAL7035



### Description

Steel sheet housing with welded frame, completely pre-assembled  
 Right- and left-sided metal protected air inlets for passive climatisation  
 Side walls not detachable  
 Roof hinged, inner roof prepared for mounting of Plug&Play fan unit Art.-No. 691656GR (cable not included, please order separately, e.g. Art.-No. EK504.x)  
 Bottom with PG glands 1 x PG48, 2 x PG21 and 3 x Ø 20 mm PVC blind grommets  
 Inside front 2 x 19" profile rails, galvanised  
 Front door with glass window made of cert. safety glass, reinforcement and 3-point bar locking, lockable, with profile half-cylinder acc. to DIN 18252 / EN1303  
 Profile half-cylinder exchangeable by customer  
 Cabinet parts inside completely earthed  
 Max. load 100 kg  
 Paint finish RAL7035, light grey  
 Protection degree IP55  
 Plinth for use as standing cabinet available as option  
 Included accessories: 4 x Wall mount angle, 2 x key

### General data

Mounting level	Front side
Type of profile rail	L-shaped
Type of ventilation	Passive
Modular spacing	482.6 mm (19 inch)

This datasheet was created automatically on 23-04-2020 . Technical changes reserved.



# DATASHEET

## 19" Wall Housing IP55, Glass Door, Depth 450 mm, RAL7035

### General data

With roof plate	True
With earthing	True
With front door	True
With sidewall	True
Demountable	False
Model	With permanent frame
Material	Steel
Type of surface	With powder coating
Degree of protection (IP)	IP55
Number of doors	1
Number of cartons	1

### Available variants

Article no.	Title	Number of height units	Width	Height	Depth	Max. Load	RAL-number	Colour
691707IP55.1G	19" Wall Housing IP55, 7U, Glass Door, Depth 450 mm, RAL7035	7	600 mm	410 mm	450 mm	100 kg	7035	Grey
691709IP55.1G	19" Wall Housing IP55, 9U, Glass Door, Depth 450 mm, RAL7035	9	600 mm	500 mm	450 mm	100 kg	7035	Grey
691712IP55.1G	19" Wall Housing IP55, 12U, Glass Door, Depth 450 mm, RAL7035	12	600 mm	630 mm	450 mm	100 kg	7035	Grey
691716IP55.1G	19" Wall Housing IP55, 16U, Glass Door, Depth 450 mm, RAL7035	16	600 mm	810 mm	450 mm	100 kg	7035	Grey
691720IP55.1G	19" Wall Housing IP55, 20U, Glass Door, Depth 450 mm, RAL7035	20	600 mm	1000 mm	450 mm	100 kg	7035	Grey

### accessory

691675.07	19" Profile Rails for Wall Housing IP55
691750WIP.1	Plinth for 19" Wall Housing IP55, Depth 450 mm
EK504.2	Power Cable CEE7/7 90° - C13 180°, black
691656GR	Fan Unit, 2-Fans for Wall Housings, Plug & Play, RAL7035

This datasheet was created automatically on 23-04-2020 . Technical changes reserved.



# DATASHEET

19" Wall Housing IP55, Glass Door, Depth 450 mm,  
RAL7035

## spare part

102115.2

Spare Keys for Wall Housing IP55 and 3+5U

This datasheet was created automatically on 23-04-2020 . Technical changes reserved.



EFB-Elektronik GmbH  
Striegauer Straße 1  
33719 Bielefeld

fon: +49 521 40 41 8-0  
fax: +49 521 40 41 8-50

info@efb-elektronik.de  
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG  
WE CARE FOR CONNECTION

