

BRAKED AXLE 3,500 KG BASIC

205 x 6





TECHNOLOGY

Model:	BASIC	Swing arm:	150 mm
Axle type:	B 3500-2	Wheel connection:	205x6
Axle load:	SA 3,500 kg	Wheel bearing:	Tapered roller bearing
Wheel brake:	3081B	Rim centre hole:	Min. 161 mm
Suspension:	Hexagonal rubber suspension		



SAP: ACHSE GU LNGS GRM EA3500

B 3500-2		Single axle	Front axle		
		Wheel nuts M 18x1.5	with top hat profile and fixing bolts		
		Ball	Wheel brake		
		Wheel brake	3081 B	Single axle	
		3081 B	Axle	kg	
OHF in	BC in	Axle	Axle		
mm	mm	cpl.	cpl.		
1,780	1,300	1 223 408	1 223 411	140	20
1,980	1,500	1 223 409	1 223 412	143	20
2,180	1,700	1 223 410	1 223 413	146	20

SCOPE OF DELIVERY

- ┃ Single axle adapter bracket welded on
- ┃ Compensation profile
- ┃ Bowden cable loose
- ┃ Wheel nuts mounted

SURFACE TREATMENT

- ┃ Axle profile hot-dip galvanised
- ┃ Wheel brake 3081B dip primed black

ACCESSORIES

- ┃ Shock absorber
(see table of contents)

