

# BRAKED AXLE 3,500 / 4,000 KG PLUS

205 x 6



## TECHNOLOGY

Model:	PLUS	Suspension:	Steel torsion bar suspension
Axle type:	BT 3500	Swing arm:	200 mm
	BT 4000	Wheel connection:	205x6
Axle load:	SA 3,500 kg	Wheel bearing:	Tapered roller bearing
Wheel brake:	3081B	Rim centre hole:	Min. 161 mm



SAP: ACHSE ST LNKS GRM EA3500

BT 3500, 3,500 kg		Single axle	Front axle with top hat profile and fixing bolts	Single axle in kg	
OHF in mm	BC in mm	Wheel nuts M 18x1.5 Ball Axle cpl.	Wheel nuts M 18x1.5 Ball Axle cpl.		
1,640	1,100	274 165	200 396 03	182	20

BT 4000, 4,000 kg		Single axle	Front axle with top hat profile and fixing bolts	Single axle in kg	
OHF in mm	BC in mm	Wheel nuts M 18x1.5 Ball Axle cpl.	Wheel nuts M 18x1.5 Ball Axle cpl.		
1,640	1,100	274 166	200 397 03	182	20

**SCOPE OF DELIVERY**

- I Single axle adapter bracket welded on
- I Compensation profile
- I Bowden cable loose
- I Wheel nuts mounted

**SURFACE TREATMENT**

- I Axle profile hot-dip galvanised
- I Wheel brake 3081B dip primed black

**ACCESSORIES**

- I Shock absorber
- (see table of contents)

