








Antifouling Guide

| Boat type | Cruising motor & Sailing boats (max 25 knots) | Aluminium boats & propellers | Fast going motor & sailing boats (*suitable for boats on drying out berths) | Racing motor boats & regata sailing boats |
|-------------------------|---|---|--|--|
| Antifouling type | Self Polishing/Erodible | Self Polishing/Erodible | Hard | Hard |
| Benefits | <ul style="list-style-type: none"> Controlled release of active substances throughout the season Works gradually throughout the season Easy maintenance & minimum preparation time Launch and re-launch without re-painting | <ul style="list-style-type: none"> Antifouling for propellers and stern gear, medium strength, self polishing suitable for most substrates including aluminium (Surfaces must be suitably primed.) | <ul style="list-style-type: none"> Solid & durable through whole season More resistant to polishing and scratching Needs to be abraded prior to subsequent applications | <ul style="list-style-type: none"> For competition & regatas: increases speed reduces fuel consumption extends motor life ensures lower coating thickness |
| Products |  <p>Broads</p> <p>Ocean Performer</p> <p>Tiger Xtra Tiger Xtra White</p> <p>Cruising Performer</p> <p>Ecopower Cruise</p> |  <p>Mille Prop</p> <p>Ecopower Cruise</p> |  <p>Hard Racing Hard Racing White</p> <p>Ecopower Racing</p> |  <p>Hard Racing Hard Racing White</p> <p>Ecopower Racing</p> |

| | LOA | 6m 20ft | 7.5m 25ft | 8.5m 28ft | 10m 33ft | 11.5m 38ft | 13m 43ft | 14.5m 48ft | 16m 53ft | 18m 60ft | 20m 66ft | 23m 76ft |
|---|---------------|------------|--------------|--------------|-------------|---------------|-------------|---------------|-------------|-------------|-------------|-------------|
|  | Fin keel | 1.5l | 1.5l | 3l | 4l | 5l | 6l | 7l | 8l | 9.5l | 11l | 13l |
| | 750ml | 2 | 2 | 4 | 2 | 0 | 2 | 3 | 1 | 2 | 1 | 1 |
| | 2.5l | 0 | 0 | 0 | 1 | 2 | 2 | 2 | 3 | 3 | 4 | 5 |
|  | Full keel | 2l | 3l | 4l | 5l | 6l | 7.5l | 9l | 11l | 13l | 15.5l | 19l |
| | 750ml | 3 | 4 | 2 | 0 | 2 | 0 | 2 | 2 | 1 | 1 | 2 |
| | 2.5l | 0 | 0 | 1 | 2 | 2 | 3 | 3 | 4 | 5 | 6 | 7 |
|  | Motor cruiser | 2l | 3.5l | 4.5l | 6l | 7l | 9l | 10l | 12l | 15l | 18.5l | 23l |
| | 750ml | 3 | 2 | 3 | 2 | 3 | 2 | 0 | 3 | 0 | 2 | 1 |
| | 2.5l | 0 | 1 | 1 | 2 | 2 | 3 | 4 | 4 | 6 | 7 | 9 |

As hull designs vary this table is intended as a guide only. Use Antifouling products safely. Always read the label and product information before use.

Recoating

| Old antifouling | New antifouling | | | | | | | |
|------------------------------|-----------------|---------|-----------------|--------------------|-------------|--------|---------|------------------------|
| Hempel's | Tiger Xtra | Aluxtra | Ocean Performer | Cruising Performer | Hard Racing | Broads | Classic | Ecopower Racing/Cruise |
| Aluxtra | C | C | C | C | C | C | C | C |
| Ocean Performer | C | C | C | C | C | C | C | C |
| Cruising Performer | C | C | C | C | C | C | C | C |
| Hard Racing | A/C | A/C | A/C | A/C | A/C | A/C | A/C | A/C |
| Tiger Xtra | A/C | A/C | A/C | A/C | A/C | A/C | A/C | A/C |
| Broads | A/C | A/C | A/C | A/C | A/C | A/C | A/C | A/C |
| Classic | A/C | A/C | A/C | A/C | A/C | A/C | A/C | A/C |
| Unknown antifouling | A/C/P | A/C/P | A/C/P | A/C/P | A/C/P | A/C/P | A/C/P | A/C/P |
| Antifouling in bad condition | R | R | R | R | R | R | R | R |

| | |
|--------------|---|
| C | Clean Wash thoroughly with a brush or sponge using fresh water. All weed, barnacles and slime must be removed. Allow to dry before you apply Antifouling. |
| A/C | Abrade / Clean / Wash off with fresh water Abrade thoroughly with abrasive paper (wet) grade 100-240. Remove all weed, barnacles and slime. Wash with fresh water and allow to dry before you apply Antifouling. |
| A/C/P | Abrade / Clean / Wash off with fresh water / Apply Hempel Underwater primer Abrade thoroughly with abrasive paper (wet) grade 100-240. Remove all weed, barnacles and slime. Wash with fresh water and allow to dry before you apply Hempel Underwater Primer, followed by Antifouling. |
| R | FRemove old AF Remove old paint completely using Paint Stripper or / and abrading. Wash thoroughly with Hempel PreClean and rinse with fresh water. Allow to dry before you apply Primer / Antifouling. |