



VIKING-YACHTING.COM



Learn more about
VIKING RescYou™
on YouTube

RescYou™ liferaft



Classic leisure liferaft

Our high quality standard yachting liferaft is ideal for ocean cruising and short international voyages.

- The oversized entrance, with inflatable boarding ramp and ladder, allows for swift embarkation and ensures easy access to extract evacuees by boat or helicopter
- Viewing port for cross ventilation and view of the horizon
- Insulated floor provides extra protection against hypothermia
- Rain water collector
- Internal and external lifelines
- Approved for inflation in -15°C to +65°C

Container



Valise

Type of liferaft	Dimensions LxWxH*	Weight incl. ISO pack II	ISO pack I in grab bag
4 person RescYou™ in container	75 x 45 x 32 cm	36 kg	9 kg
4 person RescYou™ in valise	80 x 41 x 36 cm	29 kg	9 kg
6 person RescYou™ in container	80 x 57 x 32 cm	42 kg	12 kg
6 person RescYou™ in valise	85 x 47 x 38 cm	36 kg	12 kg
8 person RescYou™ in container	80 x 57 x 35 cm	48 kg	15 kg
8 person RescYou™ in valise	80 x 45 x 45 cm	39 kg	15 kg

* Height for liferaft in container includes cradle (approx 2 cm).

Specifications

Type:	Traditional yachting and fishing liferaft
Colour:	Fluorescent yellow canopy and ballast bags for enhanced visibility from a distance. Black buoyancy compartments
Sizes:	4, 6 and 8 persons
Materials:	Natural rubber and acrylic/silicon coated nylon
Ballast bags:	4 large quick filling bags - each containing 55 litres – for maximum stability
Retro-reflective tape:	Fitted with SOLAS high-visibility retro-reflective tape on roof, sides and buoyancy compartments
Lights:	Internal and external automatic light
Emergency pack:	Equipped with the ISO emergency pack II. On longer voyages upgrading the emergency pack to an ISO emergency pack I can be recommended. The additional ISO emergency pack I comes in a handy orange grab bag
Storage options:	Packed in a fibreglass container or a handy water resistant valise
Main areas of application:	Coastal and offshore sailing and fishing
Approval:	ISO 9650-1 group A certified and third-party approved by DNV. The liferaft also meets the ISAF rules

All specifications are subject to alteration

VIKING LIFE-SAVING EQUIPMENT A/S

VIKING RescYou™ liferafts range



RescYou™ Pro

The ultimate liferaft for all types of sailing, where comfort and safety go hand in hand

- Top of the line with all the ultimate features
- Automatically self-righting
- ISO 9650-1 approved



RescYou™

The traditional liferaft for ocean cruising and short international voyages

- Classic leisure liferaft
- Durable and stable
- ISO 9650-1 approved



RescYou™ Coastal

The smart solution for coastal sailing near rescue points

- For coastal waters
- Compact and portable
- ISO 9650-2 approved

Choose the liferaft that fits your needs

Feature	RescYou™ Pro	RescYou™	RescYou™ Coastal
Capacity	4, 6 or 8	4, 6 or 8	6
ISO 9650-1 and ISAF approved	X	X	-
ISO 9650-2 approved	-	-	X
Self-righting	X	-	-
Room: m ² per person	0,4	0,372	0.25
Buoyancy: m ³ per person	0,1	0,096	0.082
Freeboard (mm)	350	250	200
Inflation temperature range	-15°C to +65°C	-15°C to +65°C	0°C to +65°C
Entrances	2	1	1
Openings / observation slots	4	2	2
Two curtained windows	X	-	-
Blue inner lining (calming effect)	X	-	-
Rain collector on canopy	X	X	-
Insulated floor	X	X	-
Insulated and inflatable double floor	X		
Ballast bags (55 l)	4	4	4
SOLAS grade high-visibility retro-reflective tape	X	X	X
Internal and external automatic light	X	X	X
Emergency pack: Standard coastal (ISO 9650-2)	-	-	X
ISO emergency pack II	X	X	-
Optional upgrade to ISO emergency pack I	X	X	-
Option: Water-resistant valise	X	X	X
Option: Durable glass-fibre container	X	X	X
3 year recommended service interval	X	X	X

VIKING LIFE-SAVING EQUIPMENT A/S

Tel +45 76 11 81 00, Email: VIKING@VIKING-life.com