

# Liquid Rubbing

## Boatcare

Cleaning and polishing Liquid Rubbing is a two component epoxy primer for use as a high build



### PRODUCT DESCRIPTION

A liquid polishing product that restores the former shine on gelcoat and painted surfaces. Does not contain wax or silicone. For both manual and machine polishing (800-1000 rpm).

- \* Easy to use
- \* Removes light scratches and oxidation
- \* Also suitable for use on caravans or garden furniture

### PRODUCT INFORMATION

Colour	YMB825
Specific Gravity	1.06
Volume Solids	13%
Typical Shelf Life	2 yrs
VOC (As Supplied)	158 g/lt
Unit Size	500 ml

### DRYING/OVERCOATING INFORMATION

#### Drying

#### Overcoating

##### Substrate Temperature

Overcoated By	5°C (41°F)		10°C (50°F)		23°C (73°F)		35°C (95°F)	
	Min	Max	Min	Max	Min	Max	Min	Max

### APPLICATION AND USE

<b>Preparation</b>	Clean with Super Cleaner. Rinse with fresh water and allow to dry.
<b>Method</b>	Apply Liquid Rubbing with a clean, dry cloth. Polish with circular movements. Machine polishing (800-1000 rpm) is the most effective method. Polish the surface further with a dry, clean cloth. Protect the surface with Marine Polish, Marine Wax or UV Wax Sealer.
<b>Hints</b>	Mixing - Shake well before use.
<b>Some Important Points</b>	Avoid working in direct sunlight. Product temperature should be minimum 5°C/41°F and maximum 35°C/95°F. Ambient temperature should be minimum 5°C/41°F and maximum 35°C/95°F. Substrate temperature should be minimum 5°C/41°F and maximum 35°C/95°F.
<b>Compatibility/Substrates</b>	Suitable for use on GRP and painted surfaces.

### TRANSPORTATION, STORAGE AND SAFETY INFORMATION

<b>Storage</b>	<b>GENERAL INFORMATION:</b> Exposure to air and extremes of temperature should be avoided. For the full shelf life of Liquid Rubbing to be realised ensure that between use the container is firmly closed and the temperature is between 5°C/41°F and 35°C/95°F. Keep out of direct sunlight. <b>TRANSPORTATION:</b> Liquid Rubbing should be kept in securely closed containers during transport and storage.
<b>Safety</b>	<b>GENERAL:</b> Read the label safety section for Health and Safety Information, also available from our Technical Help Line. <b>DISPOSAL:</b> Do not discard tins or pour paint into water courses, use the facilities provided. It is best to allow paints to harden before disposal. Remainders of Liquid Rubbing cannot be disposed of through the municipal waste route or dumped without permit. Disposal of remainders must be arranged for in consultation with the authorities.
<b>IMPORTANT NOTES</b>	<i>The information given in this sheet is not intended to be exhaustive. Any person using the product without first making further written enquiries as to the suitability of the product for the intended purpose does so at their own risk and we can accept no responsibility for the performance of the product or for any loss or damage (other than death or personal injury resulting from negligence) arising out of such use. The information contained in this sheet is liable to modification from time to time in the light of experience and our policy of continuous product development.</i>

Please refer to your local representative or visit [www.yachtpaint.com](http://www.yachtpaint.com) for further information.

All trademarks mentioned in this publication are owned by, or licensed to, the AkzoNobel group of companies. © AkzoNobel 2015.

Liquid Rubbing

Boatcare

Cleaning and polishing Liquid Rubbing is a two component epoxy primer for use as a high build

---



---

Please refer to your local representative or visit [www.yachtpaint.com](http://www.yachtpaint.com) for further information.

All trademarks mentioned in this publication are owned by, or licensed to, the AkzoNobel group of companies. © AkzoNobel 2015.

Ref:3195 Liquid Rubbing Issue Date:17/08/2017