



M-Series International

Mobile/Marine True Sinewave Inverter/Charger

Sealed FX

- Sinewave Output
- Intelligent Battery Charging
- Modular, Stackable Design
- High Operating Efficiency
- Weather-Resistant Sealed Chassis
- Corrosion Resistant Internal Components
- Field Serviceable
- Neutral/Ground Switching
- Integrated Network Communications
- Standard 5-Year Warranty

Vented VFX

- Sinewave Output
- Intelligent Battery Charging
- Modular, Stackable Design
- High Operating Efficiency
- "Bug Proof" Chassis
- Corrosion Resistant Internal Components
- Field Serviceable
- Neutral/Ground Switching
- Integrated Network Communications
- Standard 5-Year Warranty



Vented VFX

Sealed FX



OutBack Power's M-Series inverter/chargers provide true sinewave power output and intelligent battery charging. They are modularly expandable to your power needs providing a complete power conversion solution. They incorporate a DC to AC inverter, battery charger, and an AC transfer switch, which combines 30 amp pass-through and neutral/ground switching.

All OutBack inverter/chargers produce nearly distortion free sinewave AC power for onboard electronics like sensitive home theater equipment and microwaves with minimal RF interference. Industry leading surge power starts heavy loads like air conditioning.

Power factor-corrected battery charging gets the most out of your shore cord and generator while maximizing the life and performance of your batteries. Ultra fast AC transfer switch with neutral/ground switching seamlessly transfers shore cord current without dropping loads. Modular expandability is achieved through networked communications, allowing your inverter system to grow with your power consumption needs.

The OutBack M-Series inverter is the superior choice when you need a reliable, powerful, modular, and true sinewave inverter/charger.

OutBack
POWER[™]
member of The  Group[™]


www.outbackpower.com

M-Series International Specifications

		Sealed Models			Vented Models		
		FX2012EMT	FX2024EMT	FX2348EMT	VFX2612EM	VFX3024EM	VFX3048EM
Nominal DC Input Voltage		12 Vdc	24 Vdc	48 Vdc	12 Vdc	24 Vdc	48 Vdc
Continuous Power Rating at 25°C (77°F)		2000 VA	2000 VA	2300 VA	2600 VA	3000 VA	3000 VA
AC Voltage/Frequency		230 Vac / 50 Hz	230 Vac / 50 Hz	230 Vac / 50 Hz	230 Vac / 50 Hz	230 Vac / 50 Hz	230 Vac / 50 Hz
Continuous AC RMS Output at 25°C (77°F)		8.7 Aac	8.7 Aac	10.0 Aac	11.3 Aac	13.0 Aac	13.0 Aac
Idle Power	Full	~ 20 Watts	~ 20 Watts	~ 23 Watts	~ 20 Watts	~ 20 Watts	~ 23 Watts
	Search	~ 6 Watts	~ 6 Watts	~ 6 Watts	~ 6 Watts	~ 6 Watts	~ 6 Watts
Typical Efficiency		90%	92%	93%	90%	92%	93%
Total Harmonic Distortion	Typical	2%	2%	2%	2%	2%	2%
	Maximum	5%	5%	5%	5%	5%	5%
Output Voltage Regulation		± 2%	± 2%	± 2%	± 2%	± 2%	± 2%
Maximum Output Current	Peak	28 Aac	35 Aac	35 Aac	28 Aac	35 Aac	35 Aac
	RMS	20 Aac	25 Aac	25 Aac	20 Aac	25 Aac	25 Aac
AC Overload Capability	Surge	4600 VA	5750 VA	5750 VA	4600 VA	5750 VA	5750 VA
	5 Seconds	4000 VA	4800 VA	4800 VA	4000 VA	4800 VA	4800 VA
	30 Minutes	2500 VA	3100 VA	3100 VA	3100 VA	3300 VA	3300 VA
AC Input Current Maximum		30 Aac	30 Aac	30 Aac	30 Aac	30 Aac	30 Aac
AC Input Voltage Range (MATE Adjustable)		160 to 300 Vac	160 to 300 Vac	160 to 300 Vac	160 to 300 Vac	160 to 300 Vac	160 to 300 Vac
AC Input Frequency Range		44 to 56 Hz	44 to 56 Hz	44 to 56 Hz	44 to 56 Hz	44 to 56 Hz	44 to 56 Hz
DC Input Voltage Range		10.5 to 17.0 Vdc	21.0 to 34.0 Vdc	42.0 to 68.0 Vdc	10.5 to 17.0 Vdc	21.0 to 34.0 Vdc	42.0 to 68.0 Vdc
Operating Temperature Range		-40 to 60°C (power derated above 25°C)			-40 to 60°C (power derated above 25°C)		
Continuous Battery Charger Output		100 Adc	55 Adc	35 Adc	120 Adc	85 Adc	45 Adc
Warranty		Standard 5 year Warranty			Standard 5 year Warranty		
Weight (lbs/kg)	Unit	62.2 / 28.4			61 / 27.7		
	Shipping	67 / 31			67 / 31		
Dimensions H x W x L (in/cm)	Unit	13 x 8.25 x 16.25 / 33 x 21 x 41			12 x 8.25 x 16.25 / 30 x 21 x 41		
	Shipping	21.75 x 13 x 22 / 55 x 33 x 56			21.75 x 13 x 22 / 55 x 33 x 56		

Specifications subject to change without notice

Available From:



Corporate Office:
5917 195th St. NE
Arlington, WA 98223 USA
Phone: (360) 435.6030
Fax: (360) 435.6019

European Office:
Hansastrasses 8
D-91126
Schwabach, Germany
Phone: +49. 9133.79889.0
Fax: +49.9122.79889.21

Asia Office:
Suite 1903, 19/F., Tower 1
33 Canton Road, Tsun Sha Tsui
China Hong Kong City, Kowloon
Hong Kong
Phone: +852.2736.8663
Fax: +852.2199.7988

Latin American Office:
15105 Cedar Bluff Pl.
Wellington, FL 33414 USA
Phone: (561) 792.9651
Fax: (561) 792.7157