


### CLIXX PENDANT35



**DIMENSIONS**



**ACCESSORIES**




Anti-glare honeycomb louver

<b>Category</b>	Track lighting
<b>Colour</b>	Black / White / Gold
<b>Light source</b>	LED (integrated)
<b>Power</b>	5W
<b>Luminous flux</b>	440 lm
<b>Colour temperature</b>	2700K / 3000K (standard) / 4000K
<b>Colour Rendering Index</b>	CRI>90
<b>Efficacy</b>	88 lm/W
<b>Lifetime</b>	>50.000h
<b>Beam angle</b>	20D / 30D (standard) / 40D / 60D
<b>Driver</b>	Not included
<b>Voltage</b>	24V
<b>Input voltage</b>	110 – 240 V
<b>Dimming</b>	Triac / 1-10V / DALI / Zigbee
<b>IP rating</b>	IP20
<b>Weight</b>	550 g
<b>Material</b>	Aluminium
<b>Warranty</b>	5 years




LIGHT DISTRIBUTION

**20°**




h(m)	E(lx)	Φ(m)
2	563	Φ0.69
3	250	Φ1.03
3.5	183	Φ1.20
4	140	Φ1.38
5	90	Φ1.55

**30°**




h(m)	E(lx)	Φ(m)
1	2519	Φ0.32
2	629	Φ0.65
3	279	Φ0.98
4	157	Φ1.31
5	100	Φ1.64

**40°**



h(m)	E(lx)	Φ(m)
2	278	Φ0.96
3	124	Φ1.44
3.5	91	Φ1.68
4	69	Φ1.92
5	44	Φ2.40

**60°**



h(m)	E(lx)	Φ(m)
1	799	Φ0.75
2	199	Φ1.51
3	88	Φ2.27
4	49	Φ3.02
5	31	Φ3.78