国 elinchrom

Get the perfect shot right from the start.





ELB 500 TTL Focus on the stories you want to share.

Enjoy Simplicity

Challenging situations are now simple thanks to TTL. Be ready within seconds and enjoy beautiful light right from the first shot with TTL. If necessary, quickly switch to manual on your transmitter to take full control of your ELB 500 TTL.

Set the light you want, in all simplicity.

Power with HSS

With 500 Ws, the ELB 500 TTL easily overpowers the sun. The Elinchrom Pro transmitter gives you access to High Speed Sync to seamlessly synchronise at speeds of up to 1/8000s. Freeze motion, darken and overpower the ambient light or use wider aperture.

Creating a dreamy background has never been easier.

Endless Freedom

The ELB 500 TTL offers you total freedom in a lightweight and portable solution while still delivering 400 full power flashes on a single charge. Freeze motion in action mode or use HSS, rely on the battery for on location work or plug into the mains while shooting in studio with the Active Charge feature.

No matter what you want to shoot, the ELB 500 TTL will deliver!

Exceptional Light Quality

10 times more powerful than an on-camera flash, the ELB 500 TTL doesn't sacrifice light quality for ease of use and portability. Together with the Elinchrom range of accessories, benefit from perfect light distribution and generate high-end light quality with countless setups wherever you shoot.

With unmatched colour and light consistency, get the perfect shot right from the start.

Unlimited Creativity

The ELB 500 TTL offers you the fun and creativity of flash photography. It is the perfect all-round portable studio flash for all your imaging. The unit offers a wide variety of lighting possibilities when used with two asymmetrical controllable flash heads.

Combined with the TTL and HSS feature, it's effortless to use while delivering exceptional high-end results.

Seamless From Top to Bottom

Your workflow becomes easier and faster than ever with the ELB 500 TTL thanks to the TTL and seamless HSS features. The unit works just like an assistant.

Concentrate on the story you want to tell and produce better images in just a few steps.

Flash Power	500 Ws/J
Power Distribution	Full asymmetry
Power Range	7 F-stops
Best Flash Duration	Action: 1/20000s - Normal: 1/3400s
Recycling Time	0.05 - 2 seconds
Dimensions (LxWxH)	16.3 x 9.0 x 18.1 cm
Weight (Unit + Battery)	2.48 kg
Weight of Battery	0.73 kg
Battery	Removable - Li-Ion 14,4 V - 72 W/h
Battery Capacity	400 / 28000 flashes (full power/min. power)
Compatibility	Skyport: Elinchrom Transmitter Pro Phottix: Phottix Odin II Transmitter

SPECIFICATIONS



ELB 500 TTL To Go

N° 10309.1

- ELB 500 TTL Unit
- ELB 500 TTL Battery
- ELB 500 Head
- ELB 500 Charger
- ELB 500 Snappy
- Q-Reflector 18 cm
- ProTec Location Bag

ELB 500 TTL Dual To Go

N° 10310.1

- ELB 500 TTL Unit
- ELB 500 TTL Battery
- ELB 500 Head (x2)
- ELB 500 Charger
- ELB 500 Snappy
- Q-Reflector 18 cm
- Q-Wide Refector 13.5 cm
- ProTec Location Bag





ELB 500 TTL ACCESSORIES

Elinchrom Transmitter Pro

Nº 19366 / Nº 19367

The Elinchrom Transmitter Pro enables seamless control and synchronisation up to 1/8000s.

Available for Canon[®] and Nikon[®] and soon other brands.



The ELB 500 TTL is also compatible with the Phottix® Odin II system, extending compatibility with Canon® and Nikon® on-camera flashes with the Odin II receivers.

Recommended Accessories

- Q-Reflector Adapter MKII N° 26342
- Q-Wide Refector 13.5 cm N° 26145
- Q-Reflector Grid 18 cm N° 26056
- Q-Octa 56 cm N° 26600
- Silver Deep Umbrella 105 cm N° 26352
- Tripod Air Click 105-244 cm N° 31038

The Most Powerful Portable TTL Light Ever.



"The ELB 500 TTL gives me the freedom to truly connect with my subject."

Brett Florens





ELB 500 TTL



This brochure may show images of products with accessories which are not part of sets or single units. Elinchrom sets and single unit configurations may change without notice and they might be different in other countries. Tolerances of specifications and components conform to IEC and CE standards Brett Florens except page 5 by Quentin Décaillet and Nikon[®] are protected trademarks which do not belong to Elinchrom LTD. Photo: All photos by he listed values can differ due to tolerances in components, or measuring instruments. Technical data, subject to change. No liability for misprints. Canon 72128 - EN - ELB 500 TTL - 01.2018 - Elinchrom - Switzerland

