

Flash Unit		HS	TTL	Power Control	Display on Transmitter	Triggering
Quadra★ 1st series	Action (A)	●	✘	✔	✘	✔
	Pro (S)	●				
Quadra RX★ 2nd series	HS	●	✘	✔	✔	✔
	RQ Ringflash Pro	●				
Quadra Hybrid AS RX★ 3rd series	RQ Ringflash Pro	●				
ELB 400★	RQ Ringflash Eco	●	✘	✔	✔	✔
ELB 500 TTL	ELB 500 Head	●	✔	✔	✔	✔
Ranger RX (Speed and Speed AS) with Transceiver RX ¹	A	●	✘	✔	✔	✔
	S	●				
ELB 1200★	Action	●				
	Pro	●	✘	✔	✔	✔
	HS	●				
D-Lite it	2	●	✘	✘	✘	✔
	4	●				
D-Lite RX	ONE / 2	●	✘	✔	✔	✔
	4	●				
BXRi	250 / 500	●	✘	✔	✘	✔
BRX	250 / 500	●	✘	✔	✔	✔
ELC Pro HD	500	●	✘	✔	✔	✔
	1000	●	✘	✔	✔	✔
Style RX with Transceiver RX ¹	300 / 600	●	✘	✔	✔	✔
	1200	●				
Digital RX 1200 Digital RX 2400 with Transceiver RX ¹	Zoom Action	●				
	Zoom Pro	●	✘	✔	✔	✔
	Zoom Pro HD	●				
	Ringflash 3000	●				
Universal Receiver★		●	✘	✘	✘	✔
Receiver Plus★		●	✘	✘	✘	✔

★ We recommend using just one flash head on outlet A.
A second connected flash head reduces the Hi-Sync performance.

● Recommended.

● Not optimised.
High shutter speeds might produce unexpected results depending on the flash unit, power levels, camera model and sensor size.

● Not compatible.

✔ Feature available.

✘ Feature not available.

¹ Refer to the 1st Generation Skyport information above.