



# DEEP ASYM

CEILING RECESSED



p. 587



## 1.0 LED

LED LED 7/10W | 350/500mA | 18Vf  
COB 3-step | excl. power supply  
aluminium powder coated

0.25kg IP20 35° 100 4-30

87 35°/35° 355° 100 4-30

CODE
112461W
112461S
112461G
112461B

### Light Colour Selection

LUMEN	CRI	CODE
2700K	450/610	>90 3
3000K	470/640	>90 5
1800-2850K	16V 290/390	>95 9

## ALWAYS USE

power supply

CODE	
350mA   10W	90223401
500mA   10W	90214404
500mA   15W dim	90224501

more power supplies on page 588



## 1.0 MR16

QR-CBC51 max.35W | GU5.3  
12V | excl. power supply  
aluminium powder coated

0.19kg IP20 35° 90 4-30

87 35°/35° 355° 90 4-30

CODE
112410W0
112410S0
112410G0
112410B0

## ALWAYS USE

power supply

CODE	
12V   10W dim	90221401
12V   25W dim	90221701
12V   70W dim	90221904

more specs on page 591



## 1.0 PAR16

PAR16 max.12W | GU10  
100-240VAC | 50-60Hz  
aluminium powder coated

0.23kg IP20 35° 115 4-30

87 35°/35° 355° 115 4-30

CODE
112420W0
112420S0
112420G0
112420B0

## OPTIONAL

PAR16 LED GU10 7W  
phase-cut dim

CODE	
2700K	901228W2
3000K	901228W4
1800-2850K	901229S9

more lamps and specs on page 593